

Page 1 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Motorbike 2T Synth Street Race 20 L

Art.: 1566

അ

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

No information available at present.

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions. PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

œ

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone: (+49) 0731-1420-0, Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number Emergency information services / official advisory body:

Telephone number of the company in case of emergencies: +49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture



Page 2 of 12

œ

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0, 1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

3.2 MIXTURE	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119456620-43-XXXX
Index	
EINECS, ELINCS, NLP	926-141-6 (REACH-IT List-No.)
CAS	
content %	10-30
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304
Baseoil - unspecified *	
Registration number (REACH)	
Index	
EINECS, ELINCS, NLP	
CAS	
content %	1-10
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

* The contained mineral oil can be described by one or more of the following numbers:

EINECS, ELINCS, NLP	Registration number (REACH)	Chemical name
265-157-1	01-2119484627-25-XXXX	Distillates (petroleum), hydrotreated heavy paraffinic
265-169-7	01-2119471299-27-XXXX	Distillates (petroleum), solvent-dewaxed heavy paraffinic
265-158-7	01-2119487077-29-XXXX	Distillates (petroleum), hydrotreated light paraffinic
265-159-2	01-2119480132-48-XXXX	Distillates (petroleum), solvent-dewaxed light paraffinic

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected! Never pour anything into the mouth of an unconscious person!

Inhalation



Page 3 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

ആ

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Keep Data Sheet available.

Ingestion

Do not induce vomiting. Consult doctor immediately. Danger of aspiration

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. The following may occur:

Drying of the skin.

Irritation of the skin.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2 Foam Dry extinguisher Water jet spray

Unsuitable extinguishing media

High volume water jet **5.2 Special hazards arising from the substance or mixture** In case of fire the following can develop: Oxides of carbon Flammable vapour/air mixtures

5.3 Advice for firefighters

Protective respirator with independent air supply. According to size of fire Full protection, if necessary. Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping. Do not carry cleaning cloths soaked in product in trouser pockets.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage



Page 4 of 12

ദ്ര

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use.

Take measures against electrostatic charging, if appropriate.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells. Store product closed and only in original packing.

Protect against moisture and store closed.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 1200 mg/m3

Chemical Name	Hydrocarbons, C1	1-C14, n-alkanes, isoalkanes, cyclics	s, <2% aromatics	Content %:10-30
WEL-TWA: 1200 mg/m3 (>=C7 nc	ormal and branched	WEL-STEL: 2(II) (AGW)		
chain alkanes)				
Monitoring procedures:	- [Draeger - Hydrocarbons 2/a (81 03 5	81)	
	- [Draeger - Hydrocarbons 0,1%/c (81 (03 571)	
	- (Compur - KITA-187 S (551 174)		
BMGV:			Other information:	
Chemical Name	Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (ACGIH)		WEL-STEL: 10 mg/m3 (ACGIH)		
Monitoring procedures:	- [Draeger - Oil 10/a-P (67 28 371)		
	- [Draeger - Oil Mist 1/a (67 33 031)		
BMGV:			Other information:	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

(8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction. If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn. Applies only if maximum permissible exposure values are listed here.



Page 5 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

ദ്ര

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection: Tight fitting protective goggles (EN 166) with side protection, with danger of projections.

Skin protection - Hand protection: Protective nitrile gloves (EN 374) Minimum layer thickness in mm: 0,35 Permeation time (penetration time) in minutes: >= 480 Protective Neoprene® / polychloroprene gloves (EN 374). Protective hand cream recommended. The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions. The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other: Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection: If OES or MEL is exceeded. Filter A - P2 (EN 14387) Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents. Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account. Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use. The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: Colour: Odour: Odour threshold: pH-value: Melting point/freezing point: Initial boiling point and boiling range: Flash point: Evaporation rate: Flammability (solid, gas): Liquid Red Characteristic Not determined n.a. Not determined 98 °C Not determined Not determined



Page 6 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

Lower explosive limit: Upper explosive limit: Vapour pressure: Vapour density (air = 1): Density: Bulk density: Solubility(ies): Water solubility: Partition coefficient (n-octanol/water): Auto-ignition temperature: Decomposition temperature: Viscosity: Viscosity: Explosive properties: Oxidising properties:

9.2 Other information

Miscibility: Fat solubility / solvent: Conductivity: Surface tension: Solvents content:

œ

Not determined Not determined Not determined 0,874 g/ml n.a. Not determined Insoluble Not determined Not determined Not determined 50 mm2/s (40°C) 9,2 mm2/s (100°C) Not determined No

Not determined Not determined Not determined Not determined Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

Hazardous reactions will not occur during storage and handling under normal conditions.

10.4 Conditions to avoid

Protect from humidity.

Open flame, ignition sources

10.5 Incompatible materials Avoid contact with strong oxidizing agents.

Avoid contact with strong oxidizing age

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Motorbike 2T Synth Street Race 20 L

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin						n.d.a.
sensitisation:						
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity -						n.d.a.
single exposure (STOT-SE):						



Page 7 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

œ.

Specific target organ toxicity -			n.d.a.
repeated exposure (STOT-RE):			
Aspiration hazard:			n.d.a.
Symptoms:			n.d.a.
Other information:			Classification
			according to
			calculation
			procedure.

Hydrocarbons, C11-C14, n-alka Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5000	mg/m3/8h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Skin corrosion/irritation:					OECD 404 (Acute Dermal Irritation/Corrosion)	Analogous conclusion, Drying of the skin., Dermatitis (skin inflammation)
Serious eye damage/irritation:					OECD 405 (Acute Eye Irritation/Corrosion)	Analogous conclusion, Slightly irritant
Respiratory or skin sensitisation:				Rat		Not sensitizising
Germ cell mutagenicity:				Salmonella typhimurium	in vivo	Negative
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Analogous conclusion, Negative
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No indications of such an effect.
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Analogous conclusion, Not to be expected
Aspiration hazard:						Yes
Symptoms:						drying of the skin., headaches, fatigue, dizziness, nausea, diarrhoea, vomiting
	J	11	1	1	1	
Baseoil - unspecified Toxicity / effect	Endnoint	Value	Unit	Organicm	Test method	Notos
ioxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 8 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.07.2018 / 0012
Replacing version dated / version: 21.08.2015 / 0011
Valid from: 12.07.2018
PDF print date: 13.07.2018
Motorbike 2T Synth Street Race 20 L
Art.: 1566

Respiratory or skin sensitisation:			Not sensitizising
Aspiration hazard:			Yes

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification). Motorbike 2T Synth Street Race 20 L Art.: 1566

œ

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							
12.3. Bioaccumulative							n.d.a.
potential:							
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT							n.d.a.
and vPvB assessment							
12.6. Other adverse							n.d.a.
effects:							
Other information:							According to the
							recipe, contains
							no AOX.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics								
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes	
12.1. Toxicity to fish:	NOELR	28d	0,17	mg/l	Oncorhynchus mykiss	QSAR		
12.1. Toxicity to daphnia:	NOELR	21d	1,22	mg/l	Daphnia magna	QSAR		
12.1. Toxicity to algae:	NOELR	72h	1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)		
12.2. Persistence and degradability:		28d	69	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable	
12.3. Bioaccumulative potential:	Log Pow		6-8				High	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance	

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Pimephales promelas		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>10	mg/l	Daphnia magna		
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Scenedesmus quadricauda		
12.2. Persistence and degradability:		28d	31	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

SECTION 13: Disposal considerations



Page 9 of 12

ദ്ര

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of. EC disposal code no .: The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU) 07 06 99 wastes not otherwise specified 13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils Recommendation: Sewage disposal shall be discouraged. Pay attention to local and national official regulations. E.g. dispose at suitable refuse site. E.g. suitable incineration plant. For contaminated packing material Pay attention to local and national official regulations. 15 01 01 paper and cardboard packaging 15 01 02 plastic packaging 15 01 04 metallic packaging **SECTION 14: Transport information General statements** 14.1. UN number: n.a. Transport by road/by rail (ADR/RID) 14.2. UN proper shipping name: 14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. Classification code: n.a. LQ: n.a. Not applicable 14.5. Environmental hazards: Tunnel restriction code: Transport by sea (IMDG-code) 14.2. UN proper shipping name: 14.3. Transport hazard class(es): n.a. 14.4. Packing group: na Marine Pollutant: n.a 14.5. Environmental hazards: Not applicable Transport by air (IATA) 14.2. UN proper shipping name: 14.3. Transport hazard class(es): n.a. 14.4. Packing group: n.a. 14.5. Environmental hazards: Not applicable 14.6. Special precautions for user Unless specified otherwise, general measures for safe transport must be followed. 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions: General hygiene measures for the handling of chemicals are applicable.



Page 10 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566

Directive 2010/75/EU (VOC):

253,5 g/l

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

œ

4, 8, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

Asp. Tox. — Aspiration hazard

Any abbreviations and acronyms used in this document:

AC Article Categories	
acc., acc. to according, according to	
ACGIH American Conference of Governmental Industrial Hygienists	
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerni	na the
International Carriage of Dangerous Goods by Road)	3
AOEL Acceptable Operator Exposure Level	
AOX Adsorbable organic halogen compounds	
approx. approximately	
Art., Art. no. Article number	
ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)	
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)	
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)	
BCF Bioconcentration factor	
BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)	
BHT Butylhydroxytoluol (= 2,6-Di-t-butyl-4-methyl-phenol)	
BMGV Biological monitoring guidance value (EH40, UK)	
BOD Biochemical oxygen demand	
BSEF Bromine Science and Environmental Forum	
bw body weight	
CAS Chemical Abstracts Service	
CEC Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids	
CESIO Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques	
CIPAC Collaborative International Pesticides Analytical Council	
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substa	nces
and mixtures)	
CMR carcinogenic, mutagenic, reproductive toxic	
COD Chemical oxygen demand	
CTFA Cosmetic, Toiletry, and Fragrance Association	
DMEL Derived Minimum Effect Level	
DNEL Derived No Effect Level	
DOC Dissolved organic carbon	
DT50 Dwell Time - 50% reduction of start concentration	
DVS Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)	
dw dry weight	
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance	
EC European Community	
ECHA European Chemicals Agency	
EEA European Economic Area	
EEC European Economic Community	



-089
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 12.07.2018 / 0012
Replacing version dated / version: 21.08.2015 / 0011
Valid from: 12.07.2018
PDF print date: 13.07.2018
Motorbike 2T Synth Street Race 20 L Art.: 1566
AIL. 1500
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
ERC Environmental Release Categories
ES Exposure scenario etc. et cetera
EU European Union
EWC European Waste Catalogue
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential HET-CAM Hen's Egg Test - Chorionallantoic Membrane
HET-CAM Hen's Egg Test - Chorionallantoic Membrane HGWP Halocarbon Global Warming Potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC Intermediate Bulk Container
IBC (Code) International Bulk Chemical (Code)
IC Inhibitory concentration
IMDG-code International Maritime Code for Dangerous Goods incl. including, inclusive
IUCLID International Uniform ChemicaL Information Database
LC lethal concentration
LC50 lethal concentration 50 percent kill
LCLo lowest published lethal concentration
LD Lethal Dose of a chemical
LD50 Lethal Dose, 50% kill
LDLo Lethal Dose Low LOAEL Lowest Observed Adverse Effect Level
LOEC Lowest Observed Effect Concentration
LOEL Lowest Observed Effect Level
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available n.c. not checked
n.d.a. no data available
NIOSH National Institute of Occupational Safety and Health (United States of America)
NOAECNo Observed Adverse Effective Concentration
NOAEL No Observed Adverse Effect Level
NOEC No Observed Effect Concentration
NOEL No Observed Effect Level ODP Ozone Depletion Potential
OECD Organisation for Economic Co-operation and Development
org. organisation of Economic co-operation and Development
PAH polycyclic aromatic hydrocarbon
PBT persistent, bioaccumulative and toxic
PC Chemical product category
PE Polyethylene PNEC Predicted No Effect Concentration
POCP Photochemical ozone creation potential
ppm parts per million
PROC Process category
PTFE Polytetrafluorethylene
REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,
Evaluation, Authorisation and Restriction of Chemicals) REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International
Carriage of Dangerous Goods by Rail)
SADT Self-Accelerating Decomposition Temperature
SAR Structure Activity Relationship



Page 12 of 12 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 12.07.2018 / 0012 Replacing version dated / version: 21.08.2015 / 0011 Valid from: 12.07.2018 PDF print date: 13.07.2018 Motorbike 2T Synth Street Race 20 L Art.: 1566 SU Sector of use SVHC Substances of Very High Concern Tel. Telephone ThOD Theoretical oxygen demand TOC Total organic carbon TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances) UN RTDG United Nations Recommendations on the Transport of Dangerous Goods Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria)) VbF VOC Volatile organic compounds vPvB very persistent and very bioaccumulative WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK). WHO World Health Organization wwt wet weight The statements made here should describe the product with regard to the necessary safety precautions - they are

not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

GB

These statements were made by: Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.