

Page 1 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 04.02.2021 / 0019
Replacing version dated / version: 12.07.2019 / 0018
Valid from: 04.02.2021
PDF print date: 26.02.2021
Fluessig-Metall

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Fluessig-Metall

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|-----------------|-----------------|---|
| Eye Irrit. | 2 | H319-Causes serious eye irritation. |
| Skin Irrit. | 2 | H315-Causes skin irritation. |
| Skin Sens. | 1 | H317-May cause an allergic skin reaction. |
| Aquatic Chronic | 2 | H411-Toxic to aquatic life with long lasting effects. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.02.2021 / 0019

Replacing version dated / version: 12.07.2019 / 0018

Valid from: 04.02.2021

PDF print date: 26.02.2021

Fluessig-Metall



Warning

H319-Causes serious eye irritation. H315-Causes skin irritation. H317-May cause an allergic skin reaction. H411-Toxic to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves and eye protection / face protection.

P302+P352-IF ON SKIN: Wash with plenty of water and soap. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314-Get medical advice / attention if you feel unwell.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH205-Contains epoxy constituents. May produce an allergic reaction.

Reaction product: bisphenol-A-(epichlorhydrin)

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

| | |
|--|--|
| Reaction product: bisphenol-A-(epichlorhydrin) | |
| Registration number (REACH) | --- |
| Index | 603-074-00-8 |
| EINECS, ELINCS, NLP | 500-033-5 (NLP) |
| CAS | 25068-38-6 |
| content % | 60-80 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411 |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.02.2021 / 0019

Replacing version dated / version: 12.07.2019 / 0018

Valid from: 04.02.2021

PDF print date: 26.02.2021

Fluessig-Metall

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.02.2021 / 0019

Replacing version dated / version: 12.07.2019 / 0018

Valid from: 04.02.2021

PDF print date: 26.02.2021

Fluessig-Metall

7.1.1 General recommendations

Ensure good ventilation.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Under all circumstances prevent penetration into the soil.

Store in a well ventilated place.

Store cool.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Chemical Name | Silica, amorphous | Content %: |
|--|------------------------|------------|
| WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |

| Chemical Name | Barium sulphate | Content %: |
|---|------------------------|------------|
| WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |

| Chemical Name | Aluminium powder (stabilised) | Content %: |
|---|-------------------------------|------------|
| WEL-TWA: 10 mg/m3 (total inh. dust), 4 mg/m3 (resp. dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |

| Reaction product: bisphenol-A-(epichlorhydrin) | | | | | | |
|--|--|------------------|------------|--------|----------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,003 | mg/l | |
| | Environment - marine | | PNEC | 0,0003 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 0,018 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 10 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,5 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 0,5 | mg/kg dw | |
| | Environment - soil | | PNEC | 0,05 | mg/kg dw | |

Page 5 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.02.2021 / 0019
 Replacing version dated / version: 12.07.2019 / 0018
 Valid from: 04.02.2021
 PDF print date: 26.02.2021
 Flüssig-Metall

| | | | | | | |
|---------------------|----------------------------------|------------------------------|------|-------|--------------|--|
| | Environment - oral (animal feed) | | PNEC | 11 | mg/kg | |
| Consumer | Human - dermal | Short term, systemic effects | DNEL | 3,571 | mg/kg bw/day | |
| Consumer | Human - oral | Short term, systemic effects | DNEL | 0,75 | mg/kg bw/day | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 0,75 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 0,75 | mg/m3 | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 0,75 | mg/m3 | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 3,6 | mg/kg bw/day | |
| Workers / employees | Human - dermal | Short term, systemic effects | DNEL | 8,33 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 12,25 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 8,3 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 12,3 | mg/m3 | |

| Silica, amorphous | | | | | | |
|---------------------|--|--------------------------|------------|-------|------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - oral (animal feed) | | PNEC | 60000 | mg/kg feed | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 4 | mg/m3 | |

| Barium sulphate | | | | | | |
|---------------------|--|-----------------------------|------------|-------|-----------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,115 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 600,4 | mg/kg dw | |
| | Environment - sewage treatment plant | | PNEC | 62,2 | mg/l | |
| | Environment - soil | | PNEC | 207,7 | mg/kg dw | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 13000 | mg/kg body weight/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 10 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 10 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 10 | mg/m3 | |

| Aluminium powder (stabilised) | | | | | | |
|-------------------------------|--|-----------------------------|------------|--------|-------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,0749 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 20 | mg/l | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 3,95 | mg/kg | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 3,72 | mg/m3 | |

Page 6 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.02.2021 / 0019
 Replacing version dated / version: 12.07.2019 / 0018
 Valid from: 04.02.2021
 PDF print date: 26.02.2021
 Flüssig-Metall

| | | | | | | |
|---------------------|--------------------|-----------------------------|------|------|-------|--|
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 3,72 | mg/m3 | |
|---------------------|--------------------|-----------------------------|------|------|-------|--|

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
 (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Not required in contained systems, as no exposure normally occurs here.
 If operational exposure (e.g. repair or maintenance work) cannot be avoided, corresponding protective measures need to be taken.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves.
 With short-term contact:
 Protective gloves in butyl rubber (EN 374).
 Minimum layer thickness in mm:
 > 0,4
 Permeation time (penetration time) in minutes:
 > 120
 With long-term contact:
 Protective gloves in butyl rubber (EN 374).
 Minimum layer thickness in mm:
 > 0,4
 Permeation time (penetration time) in minutes:
 > 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 If air supply is not sufficient, wear protective breathing apparatus.
 Observe wearing time limitations for respiratory protection equipment.

Page 7 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.02.2021 / 0019
 Replacing version dated / version: 12.07.2019 / 0018
 Valid from: 04.02.2021
 PDF print date: 26.02.2021
 Flüssig-Metall

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---------------------------|
| Physical state: | Paste, liquid. |
| Colour: | Grey |
| Odour: | Mild |
| Odour threshold: | Not determined |
| pH-value: | Not determined |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | Not determined |
| Flash point: | n.a. |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | n.a. |
| Lower explosive limit: | Not determined |
| Upper explosive limit: | Not determined |
| Vapour pressure: | Not determined |
| Vapour density (air = 1): | Not determined |
| Density: | 1,35-1,45 g/ml |
| Bulk density: | n.a. |
| Solubility(ies): | Not determined |
| Water solubility: | Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | Not determined |
| Decomposition temperature: | >200 °C |
| Viscosity: | 78000-87000 cP (25°C) |
| Explosive properties: | Product is not explosive. |
| Oxidising properties: | No |

9.2 Other information

| | |
|---------------------------|----------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | 0 % |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 04.02.2021 / 0019

Replacing version dated / version: 12.07.2019 / 0018

Valid from: 04.02.2021

PDF print date: 26.02.2021

Fluessig-Metall

10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

| Fluessig-Metall | | | | | | |
|---|----------|-------|------|----------|-------------|--------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

| Reaction product: bisphenol-A-(epichlorhydrin) | | | | | | |
|--|----------|--------|-------|------------|---|----------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >11400 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Skin Irrit. 2 |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Irrit. 2 |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | Sensitising (skin contact) |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Sensitising (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 472 (Genetic Toxicology - Escherichia coli, Reverse Assay) | Negative |
| Carcinogenicity: | | | | Rat | OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies) | Negative |
| Reproductive toxicity: | NOEL | 540 | mg/kg | | OECD 416 (Two-generation Reproduction Toxicity Study) | |
| Reproductive toxicity: | | | | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | Negative |
| Aspiration hazard: | | | | | | No |

Page 9 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.02.2021 / 0019
 Replacing version dated / version: 12.07.2019 / 0018
 Valid from: 04.02.2021
 PDF print date: 26.02.2021
 Fluessig-Metall

| | | | | | | |
|-----------|--|--|--|--|--|----------------------------------|
| Symptoms: | | | | | | diarrhoea, weight loss |
| Symptoms: | | | | | | eyes, reddened, watering eyes |

| Silica, amorphous | | | | | | |
|---|----------|--------|---------|------------|--------------------------------|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | Analogous conclusion |
| Acute toxicity, by dermal route: | LD50 | >5000 | mg/kg | Rabbit | | References |
| Acute toxicity, by inhalation: | LC50 | >0,139 | mg/l/4h | Rat | | References, Maximum achievable concentration. |
| Skin corrosion/irritation: | | | | Rabbit | | Not irritant, References |
| Serious eye damage/irritation: | | | | Rabbit | | Not irritant, Mechanical irritation possible., References |
| Respiratory or skin sensitisation: | | | | Guinea pig | | Not sensitising |
| Germ cell mutagenicity: | | | | | | Negative |
| Carcinogenicity: | | | | | | No indications of such an effect. |
| Reproductive toxicity (Developmental toxicity): | | | | | | No indications of such an effect. |
| Symptoms: | | | | | | eyes, reddened |

| Barium sulphate | | | | | | |
|------------------------------------|----------|--------|-------|----------|--|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >15000 | mg/kg | Rat | IUCLID Chem. Data Sheet (ESIS) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | | Rat | | Analogous conclusion |
| Skin corrosion/irritation: | | | | | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | No (skin contact), Analogous conclusion |
| Germ cell mutagenicity: | | | | | | Negative |

| Aluminium powder (stabilised) | | | | | | |
|------------------------------------|----------|-------|---------|----------|-------------|----------------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by inhalation: | LC50 | >5 | mg/l/4h | Rat | | Dust, Mist |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Serious eye damage/irritation: | | | | | | Not irritant |
| Respiratory or skin sensitisation: | | | | | | No (skin contact) |
| Symptoms: | | | | | | mucous membrane irritation |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Fluessig-Metall | | | | | | | |
|-------------------|----------|------|-------|------|----------|-------------|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |

| | | | | | | |
|--|--|--|--|--|--|---|
| 12.1. Toxicity to fish: | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | n.d.a. |
| Other information: | | | | | | Does not contain any organically bound halogens which can contribute to the AOX value in waste water. |
| Other information: | | | | | | DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a. |

| Reaction product: bisphenol-A-(epichlorhydrin) | | | | | | | |
|--|-----------|------|-------|------|---------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 2,4 | mg/l | Selenastrum capricornutum | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to fish: | LC50 | 96h | 2 | mg/l | Leuciscus idus | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 1,5 | mg/l | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 1,1 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 0,3 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | 9,4 | mg/l | Selenastrum capricornutum | U.S. EPA ECOTOX Database | |
| 12.1. Toxicity to algae: | EC50 | 96h | 220 | mg/l | Scenedesmus subspicatus | | |
| 12.2. Persistence and degradability: | | 28d | 5 | % | | OECD 301 F (Ready Biodegradability - Manometric Respirometry Test) | Not readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 3,242 | | | Regulation (EC) 440/2008 A.8 (PARTITION COEFFICIENT) | |

Page 11 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 04.02.2021 / 0019
Replacing version dated / version: 12.07.2019 / 0018
Valid from: 04.02.2021
PDF print date: 26.02.2021
Fluessig-Metall

| | | | | | | | |
|-----------------------|------|----|------|------|------------------|--|---|
| Other information: | | | | | | | Contains organically bound halogens, which may contribute to the AOX value in wastewater. |
| Toxicity to bacteria: | IC50 | 3h | >100 | mg/l | activated sludge | | |

| Silica, amorphous | | | | | | | |
|--|----------|------|--------|------|-------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >10000 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 24h | >10000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EL50 | 72h | >10000 | mg/l | | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Abiotically degradable. |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.4. Mobility in soil: | | | | | | | Not to be expected |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Barium sulphate | | | | | | | |
|--------------------------------------|-----------|------|-------|------|---------------------------------|--|--|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >3,5 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | Analogous conclusion |
| 12.1. Toxicity to fish: | NOEC/NOEL | 33d | >1,26 | mg/l | Brachydanio rerio | OECD 210 (Fish, Early-Life Stage Toxicity Test) | Analogous conclusion |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 2,9 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | Analogous conclusion |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 14,5 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | Analogous conclusion |
| 12.1. Toxicity to algae: | ErC50 | 72h | >1,15 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | Analogous conclusion |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | >1,15 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | Analogous conclusion |
| 12.2. Persistence and degradability: | | | | | | | Not biodegradable, Inorganic products cannot be eliminated from water through biological purification methods. |

Page 12 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.02.2021 / 0019
 Replacing version dated / version: 12.07.2019 / 0018
 Valid from: 04.02.2021
 PDF print date: 26.02.2021
 Flüssig-Metall

| | | | | | | | |
|--|--|--|--|--|--|--|------|
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.a. |
|--|--|--|--|--|--|--|------|

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Allow product to harden.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number: 3082

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

Classification code:

M6

LQ:

5 L

14.5. Environmental hazards:

environmentally hazardous

Tunnel restriction code:

-

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

EmS:

F-A, S-F

Marine Pollutant:

Yes

14.5. Environmental hazards:

environmentally hazardous

Transport by air (IATA)

14.2. UN proper shipping name:

Environmentally hazardous substance, liquid, n.o.s. (EPOXY RESIN)

14.3. Transport hazard class(es):

9

14.4. Packing group:

III

14.5. Environmental hazards:

environmentally hazardous

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.

All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.



Page 13 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 04.02.2021 / 0019
Replacing version dated / version: 12.07.2019 / 0018
Valid from: 04.02.2021
PDF print date: 26.02.2021
Fluessig-Metall

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.
For exceptions, see Regulation (EU) 2019/1148 and the guidelines for implementing Regulation (EU) 2019/1148.
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| E2 | | 200 | 500 |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC):

0 %

REGULATION (EC) No 648/2004

n.a.

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

15

Employee training in handling dangerous goods is required.
These details refer to the product as it is delivered.
Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|--|
| Eye Irrit. 2, H319 | Classification according to calculation procedure. |
| Skin Irrit. 2, H315 | Classification according to calculation procedure. |
| Skin Sens. 1, H317 | Classification according to calculation procedure. |
| Aquatic Chronic 2, H411 | Classification according to calculation procedure. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Eye Irrit. — Eye irritation

Page 14 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 04.02.2021 / 0019
 Replacing version dated / version: 12.07.2019 / 0018
 Valid from: 04.02.2021
 PDF print date: 26.02.2021
 Flüssig-Metall

Skin Irrit. — Skin irritation
 Skin Sens. — Skin sensitization
 Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BSEF The International Bromine Council
 bw body weight
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 dw dry weight
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EC European Community
 ECHA European Chemicals Agency
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride

Page 15 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 04.02.2021 / 0019
Replacing version dated / version: 12.07.2019 / 0018
Valid from: 04.02.2021
PDF print date: 26.02.2021
Fluessig-Metall

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.

Page 16 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 04.02.2021 / 0019
Replacing version dated / version: 12.07.2019 / 0018
Valid from: 04.02.2021
PDF print date: 26.02.2021
Fluessig-Metall

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Fluessig-Metall

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Adhesive sealant

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr
Tel.: (+49) 0731-1420-0
Fax: (+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|-----------------|-----------------|---|
| Skin Corr. | 1B | H314-Causes severe skin burns and eye damage. |
| Eye Dam. | 1 | H318-Causes serious eye damage. |
| Skin Sens. | 1 | H317-May cause an allergic skin reaction. |
| Aquatic Chronic | 3 | H412-Harmful to aquatic life with long lasting effects. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall



Danger

H314-Causes severe skin burns and eye damage. H317-May cause an allergic skin reaction. H412-Harmful to aquatic life with long lasting effects.

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.
P260-Do not breathe vapours or spray. P273-Avoid release to the environment. P280-Wear protective gloves / protective clothing / eye protection / face protection.
P301+P330+P331-IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303+P361+P353-IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P305+P351+P338-IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310-Immediately call a POISON CENTER / doctor.
P405-Store locked up.
P501-Dispose of contents / container to an approved waste disposal facility.

3,6-diazaoctanethylenediamin
3-aminopropyltriethoxysilane
Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

| Reaction products of pentaerythritol, propoxylated and 1-chloro-2,3-epoxypropane with hydrogen sulfide | |
|--|--|
| Registration number (REACH) | 01-2120118957-46-XXXX |
| Index | --- |
| EINECS, ELINCS, NLP | 701-196-7 (REACH-IT List-No.) |
| CAS | --- |
| content % | 50-<75 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Skin Sens. 1B, H317 Aquatic Chronic 3, H412 |

| 3,6-diazaoctanethylenediamin | |
|------------------------------|--------------|
| Registration number (REACH) | --- |
| Index | 612-059-00-5 |
| EINECS, ELINCS, NLP | 203-950-6 |
| CAS | 112-24-3 |
| content % | 5-10 |

Page 18 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.02.2020 / 0015
 Replacing version dated / version: 15.04.2019 / 0014
 Valid from: 27.02.2020
 PDF print date: 26.02.2021
 Flüssig-Metall

| | |
|--|--|
| Classification according to Regulation (EC) 1272/2008 (CLP) | Acute Tox. 4, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412 Eye Dam. 1, H318 |
| 2,4,6-tris(dimethylaminomethyl)phenol | |
| Registration number (REACH) | --- |
| Index | 603-069-00-0 |
| EINECS, ELINCS, NLP | 202-013-9 |
| CAS | 90-72-2 |
| content % | 1-5 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Acute Tox. 4, H302 Eye Irrit. 2, H319 Skin Irrit. 2, H315 |
| 3-aminopropyltriethoxysilane | |
| Registration number (REACH) | 01-2119480479-24-XXXX |
| Index | 612-108-00-0 |
| EINECS, ELINCS, NLP | 213-048-4 |
| CAS | 919-30-2 |
| content % | 1-2,5 |
| Classification according to Regulation (EC) 1272/2008 (CLP) | Acute Tox. 4, H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 |

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water - call doctor immediately, have Data Sheet available.
 Protect uninjured eye.
 Follow-up examination by an ophthalmologist.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.
 In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.
 Corrosive burns on skin as well as mucous membrane possible.
 Necrosis
 Risk of serious damage to eyes.
 Danger of blindness.
 Ingestion:
 Pain in the mouth and throat

Page 19 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall

stomach pain
Oesophageal perforation
Gastric perforation

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Adapt to the nature and extent of fire.

Water jet spray/foam/CO2/dry extinguisher

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Toxic gases

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure sufficient supply of air.

Avoid contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13.

Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid contact with eyes or skin.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.02.2020 / 0015

Replacing version dated / version: 15.04.2019 / 0014

Valid from: 27.02.2020

PDF print date: 26.02.2021

Fluessig-Metall

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Do not store with oxidizing agents.

Store at room temperature.

Store in a well ventilated place.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Chemical Name | Aluminium oxide | Content %: |
|--|------------------------|------------|
| WEL-TWA: 10 mg/m3 (total inhal. dust), 4 mg/m3 (resp. dust) (aluminium oxides) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Calcium carbonate | Content %: |
| WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3 (total inhalable dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |
| Chemical Name | Silica, amorphous | Content %: |
| WEL-TWA: 6 mg/m3 (total inh. dust), 2,4 mg/m3 (resp. dust) | WEL-STEL: --- | --- |
| Monitoring procedures: | --- | |
| BMGV: --- | Other information: --- | |

2,4,6-tris(dimethylaminomethyl)phenol

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|-----------------------------|------------|-------|--------------|------|
| | Environment - freshwater | | PNEC | 0,046 | mg/l | |
| | Environment - marine | | PNEC | 0,005 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 0,46 | mg/l | |
| | Environment - sewage treatment plant | | PNEC | 0,2 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,262 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 0,026 | mg/kg dw | |
| | Environment - soil | | PNEC | 0,025 | mg/kg dw | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 0,13 | mg/m3 | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 0,13 | mg/m3 | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 0,075 | mg/kg bw/day | |
| Consumer | Human - dermal | Short term, local effects | DNEL | 0,075 | mg/kg bw/day | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 0,075 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 0,53 | mg/m3 | |

Page 21 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall

| | | | | | | |
|---------------------|--------------------|-----------------------------|------|------|-------------------|--|
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 2,1 | mg/m ³ | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 0,15 | mg/kg bw/day | |
| Workers / employees | Human - dermal | Short term, local effects | DNEL | 0,6 | mg/kg bw/day | |

| 3-aminopropyltriethoxysilane | | | | | | |
|------------------------------|---|------------------------------|------------|-------|-------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 0,33 | mg/l | |
| | Environment - marine | | PNEC | 0,033 | mg/l | |
| | Environment - sporadic (intermittent) release | | PNEC | 3,3 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 0,26 | mg/kg dw | |
| | Environment - soil | | PNEC | 0,04 | mg/kg dw | |
| | Environment - sewage treatment plant | | PNEC | 13 | mg/l | |
| | Environment - sediment, marine | | PNEC | 0,026 | mg/kg dw | |
| Consumer | Human - oral | Short term, systemic effects | DNEL | 5 | mg/kg | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 5 | mg/kg bw/d | |
| Consumer | Human - dermal | Short term, systemic effects | DNEL | 5 | mg/kg | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 5 | mg/kg bw/d | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 17,4 | mg/m ³ | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 17,4 | mg/m ³ | |
| Workers / employees | Human - dermal | Short term, systemic effects | DNEL | 8,3 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 59 | mg/m ³ | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 8,3 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 59 | mg/m ³ | |

| Aluminium oxide | | | | | | |
|---------------------|--|------------------|------------|-------|-------------------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - sewage treatment plant | | PNEC | 20 | mg/l | |
| Industrial | Human - inhalation | Long term | DNEL | 3 | mg/m ³ | |
| Commercial | Human - inhalation | Long term | DNEL | 3 | mg/m ³ | |
| Consumer | Human - oral | Long term | DNEL | 6,22 | mg/kg bw/day | |

| Calcium carbonate | | | | | | |
|---------------------|--|------------------|------------|-------|------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - sewage treatment plant | | PNEC | 100 | mg/l | |

Page 22 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.02.2020 / 0015
 Replacing version dated / version: 15.04.2019 / 0014
 Valid from: 27.02.2020
 PDF print date: 26.02.2021
 Flüssig-Metall

| | | | | | | |
|---------------------|--------------------|-----------------------------|------|------|--------------|--|
| Consumer | Human - oral | Long term, systemic effects | DNEL | 6,1 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 10 | mg/m3 | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 1,06 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 4,26 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 10 | mg/m3 | |

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE).
 (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. EN 14042.
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).
 If applicable
 Face protection (EN 166).

Skin protection - Hand protection:
 Chemical resistant protective gloves (EN 374).
 With short-term contact:
 Protective gloves in butyl rubber (EN 374).
 Minimum layer thickness in mm:
 0,7
 Permeation time (penetration time) in minutes:
 > 120
 With long-term contact:
 Protective gloves in butyl rubber (EN 374).
 Minimum layer thickness in mm:
 0,7
 Permeation time (penetration time) in minutes:
 > 480
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.
 Protective hand cream recommended.

Page 23 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.02.2020 / 0015
 Replacing version dated / version: 15.04.2019 / 0014
 Valid from: 27.02.2020
 PDF print date: 26.02.2021
 Flüssig-Metall

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|--|---------------------------|
| Physical state: | Paste, liquid. |
| Colour: | Grey |
| Odour: | Characteristic |
| Odour threshold: | Not determined |
| pH-value: | n.a. |
| Melting point/freezing point: | Not determined |
| Initial boiling point and boiling range: | Not determined |
| Flash point: | n.a. |
| Evaporation rate: | Not determined |
| Flammability (solid, gas): | n.a. |
| Lower explosive limit: | Not determined |
| Upper explosive limit: | Not determined |
| Vapour pressure: | Not determined |
| Vapour density (air = 1): | Not determined |
| Density: | 1,35-1,45 g/ml |
| Bulk density: | n.a. |
| Solubility(ies): | Not determined |
| Water solubility: | Insoluble |
| Partition coefficient (n-octanol/water): | Not determined |
| Auto-ignition temperature: | Not determined |
| Decomposition temperature: | >150 °C |
| Viscosity: | Not determined |
| Explosive properties: | Product is not explosive. |
| Oxidising properties: | No |

9.2 Other information

| | |
|---------------------------|----------------|
| Miscibility: | Not determined |
| Fat solubility / solvent: | Not determined |
| Conductivity: | Not determined |
| Surface tension: | Not determined |
| Solvents content: | Not determined |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.02.2020 / 0015

Replacing version dated / version: 15.04.2019 / 0014

Valid from: 27.02.2020

PDF print date: 26.02.2021

Fluessig-Metall

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Strong heat

10.5 Incompatible materials

See also section 7.

Avoid contact with strong alkalis.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Fluessig-Metall

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|------|----------|-------------|--------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

3,6-diazaoctanethylenediamin

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|-------|-------|----------|-------------|---|
| Acute toxicity, by oral route: | LD50 | >2500 | mg/kg | Rat | | |
| Acute toxicity, by dermal route: | LD50 | 805 | mg/kg | Rabbit | | |
| Skin corrosion/irritation: | | | | | | Skin Corr. 1B |
| Serious eye damage/irritation: | | | | | | Eye Dam. 1 |
| Respiratory or skin sensitisation: | | | | | | Skin Sens. 1 |
| Germ cell mutagenicity: | | | | | | No indications of such an effect. |
| Carcinogenicity: | | | | | | No indications of such an effect. |
| Reproductive toxicity: | | | | | | No indications of such an effect. |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | respiratory distress, burning of the membranes of the nose and throat, coughing, mucous membrane irritation |

Page 25 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.02.2020 / 0015
 Replacing version dated / version: 15.04.2019 / 0014
 Valid from: 27.02.2020
 PDF print date: 26.02.2021
 Flüssig-Metall

| 2,4,6-tris(dimethylaminomethyl)phenol | | | | | | |
|---|-----------------|--------------|-------------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >1916-<2455 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Mouse | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Specific target organ toxicity - repeated exposure (STOT-RE): | NOAEL | 15 | mg/kg | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Symptoms: | | | | | | breathing difficulties, headaches, gastrointestinal disturbances, mucous membrane irritation, dizziness, nausea |

| 3-aminopropyltriethoxysilane | | | | | | |
|---|-----------------|--------------|-------------|-----------------|---|--------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | 1457 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | 4076 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >7,35 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | Aerosol |
| Acute toxicity, by inhalation: | LC50 | >16 | ppm/6h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours, Female |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Skin Corr. 1B |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Dam. 1 |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | Yes (skin contact) |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | NOAEL | 100 | mg/kg | Rat | OECD 414 (Prenatal Developmental Toxicity Study) | |

Page 26 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall

| | | | | | | |
|---|-------|-------|-------|--------|--|---|
| Symptoms: | | | | | | respiratory distress, burning of the membranes of the nose and throat, coughing, mucous membrane irritation |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 200 | mg/kg | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | 90d |
| Specific target organ toxicity - repeated exposure (STOT-RE), dermal: | NOAEL | 84 | mg/kg | Rabbit | | 9d |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 0,147 | mg/l | Rat | | 19d |

| Aluminium oxide | | | | | | |
|---|----------|-------|---------|------------|--|--|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by oral route: | NOAEL | 30 | mg/kg | Rat | | Analogous conclusion |
| Acute toxicity, by inhalation: | NOAEC | 70 | mg/m3 | Rat | | subchronic |
| Acute toxicity, by inhalation: | LC50 | 7,6 | mg/l/4h | Rat | | Aerosol, Maximum achievable concentration. |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Guinea pig | | Not sensitising |
| Germ cell mutagenicity: | | | | | in vivo | Negative, Analogous conclusion |
| Symptoms: | | | | | | constipation |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | LOAEL | 70 | mg/m3 | Rat | | Lung damage |

| Calcium carbonate | | | | | | |
|------------------------------------|----------|-------|---------|----------|--|-------------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >2000 | mg/kg | Rat | OECD 420 (Acute Oral toxicity - Fixe Dose Procedure) | |
| Acute toxicity, by dermal route: | LD50 | >2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | >3 | mg/l/4h | Rat | OECD 403 (Acute Inhalation Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Respiratory or skin sensitisation: | | | | Mouse | OECD 429 (Skin Sensitisation - Local Lymph Node Assay) | No (skin contact) |

Page 27 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall

| | | | | | | |
|---|-------|-------|------------|-----|--|-----------------------------------|
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Carcinogenicity: | | | | | | No indications of such an effect. |
| Reproductive toxicity: | NOEL | 1000 | mg/kg bw/d | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | No indications of such an effect. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | No indications of such an effect. |
| Aspiration hazard: | | | | | | No |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 1000 | mg/kg bw/d | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 0,212 | mg/l | Rat | OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study) | |

| Silica, amorphous | | | | | | |
|----------------------------------|----------|--------|-------|----------|---|--------------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | >5000 | mg/kg | Rat | OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method) | |
| Acute toxicity, by dermal route: | LD50 | > 2000 | mg/kg | Rat | OECD 402 (Acute Dermal Toxicity) | |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Not irritant |
| Germ cell mutagenicity: | | | | | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Aspiration hazard: | | | | | | No |

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

| Fluessig-Metall | | | | | | | |
|--|----------|------|-------|------|----------|-------------|--------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | | | | | | | n.d.a. |
| 12.1. Toxicity to daphnia: | | | | | | | n.d.a. |
| 12.1. Toxicity to algae: | | | | | | | n.d.a. |
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Other adverse effects: | | | | | | | n.d.a. |

Page 28 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall

| | | | | | | | |
|--------------------|--|--|--|--|--|--|---|
| Other information: | | | | | | | Does not contain any organically bound halogens which can contribute to the AOX value in waste water. |
| Other information: | | | | | | | DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a. |

| 3,6-diazaoctanethylenediamin | | | | | | | |
|--|----------|------|---------|------|-------------------------|---|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 570 | mg/l | Poecilia reticulata | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 495 | mg/l | Pimephales promelas | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 12-33,9 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to algae: | EC50 | 72h | >2,5 | mg/l | Scenedesmus subspicatus | | |
| 12.2. Persistence and degradability: | | 28d | 0 | % | | OECD 302 B (Inherent Biodegradability - Zahn-Wellens/EMPA Test) | Not biodegradable |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| 2,4,6-tris(dimethylaminomethyl)phenol | | | | | | | |
|--|----------|------|-------|------|-------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to daphnia: | LC50 | 96h | 718 | mg/l | | | |
| 12.2. Persistence and degradability: | | 28d | 4 | % | activated sludge | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Not readily biodegradable |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.1. Toxicity to fish: | LC50 | 96h | 153 | mg/l | Brachydanio rerio | ISO 7346 | |
| 12.1. Toxicity to fish: | LC50 | 96h | 175 | mg/l | Cyprinus carpio | | |
| 12.1. Toxicity to algae: | EC50 | 72h | 84 | mg/l | Desmodesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |

| 3-aminopropyltriethoxysilane | | | | | | | |
|--|-----------|------|-------|------|-------------------------|---|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 1,3 | mg/l | Scenedesmus subspicatus | Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST) | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| 12.1. Toxicity to fish: | LC50 | 96h | >934 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |

Page 29 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall

| | | | | | | | |
|--------------------------------------|---------|-----|-------|------|---------------------------------|---|---------------------------|
| 12.1. Toxicity to daphnia: | EC50 | 48h | 311 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | EC50 | 72h | >1000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | DOC | 28d | 67 | % | | OECD 301 A (Ready Biodegradability - DOC Die-Away Test) | Not readily biodegradable |
| 12.3. Bioaccumulative potential: | BCF | | 3,4 | | Cyprinus caprio | OECD 305 (Bioconcentration - Flow-Through Fish Test) | Not to be expected |
| 12.3. Bioaccumulative potential: | Log Pow | | 1,7 | | | | Low |
| Water solubility: | | | | | | | Insoluble |
| Toxicity to bacteria: | EC10 | 6h | 13 | mg/l | Pseudomonas putida | | |

Aluminium oxide

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|--|-----------|------|---------|------|---------------------------|--|---|
| 12.1. Toxicity to fish: | LC50 | 96h | 218,6 | mg/l | Pimephales promelas | | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 48h | >0,135 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to daphnia: | EC50 | | >100 | mg/l | Daphnia magna | | |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.1. Toxicity to algae: | EC50 | | >100 | mg/l | Selenastrum capricornutum | | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | >=0,052 | mg/l | Selenastrum capricornutum | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Inorganic products cannot be eliminated from water through biological purification methods. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

Calcium carbonate

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|----------------------------|----------|------|-------|------|---------------------|--|--|
| 12.1. Toxicity to fish: | LC50 | 96h | | | Oncorhynchus mykiss | OECD 203 (Fish, Acute Toxicity Test) | No observation with saturated solution of test material. |
| 12.1. Toxicity to daphnia: | EC50 | 48h | | | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | No observation with saturated solution of test material. |

Page 30 of 34
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 27.02.2020 / 0015
Replacing version dated / version: 15.04.2019 / 0014
Valid from: 27.02.2020
PDF print date: 26.02.2021
Fluessig-Metall

| | | | | | | | |
|--|-----------|-----|-------|----------|-------------------------|--|--|
| 12.1. Toxicity to algae: | EC50 | 72h | >14 | mg/l | Desmodesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | 14 | mg/l | Desmodesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Not relevant for inorganic substances. |
| 12.3. Bioaccumulative potential: | | | | | | | Not to be expected |
| 12.4. Mobility in soil: | | | | | | | n.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC50 | 3h | >1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Toxicity to bacteria: | NOEC/NOEL | 3h | 1000 | mg/l | activated sludge | OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation)) | |
| Other organisms: | EC50 | 21d | >1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Glycine max |
| Other organisms: | EC50 | 21d | >1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Lycopersicon esculentum |
| Other organisms: | EC50 | 21d | >1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Avena sativa |
| Other organisms: | NOEC/NOEL | 21d | 1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Glycine max |
| Other organisms: | NOEC/NOEL | 21d | 1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Lycopersicon esculentum |
| Other organisms: | NOEC/NOEL | 21d | 1000 | mg/kg dw | | OECD 208 (Terrestrial Plants, Growth Test) | Avena sativa |
| Other organisms: | EC50 | 14d | >1000 | mg/kg dw | Eisenia foetida | OECD 207 (Earthworm, Acute Toxicity Tests) | |
| Other organisms: | NOEC/NOEL | 14d | 1000 | mg/kg dw | Eisenia foetida | OECD 207 (Earthworm, Acute Toxicity Tests) | |
| Other organisms: | EC50 | 28d | >1000 | mg/kg dw | | OECD 216 (Soil Microorganisms - Nitrogen Transformation Test) | |

Page 31 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.02.2020 / 0015
 Replacing version dated / version: 15.04.2019 / 0014
 Valid from: 27.02.2020
 PDF print date: 26.02.2021
 Flüssig-Metall

| | | | | | | | |
|-------------------|-----------|-----|--------|----------|--|---|------|
| Other organisms: | NOEC/NOEL | 28d | 1000 | mg/kg dw | | OECD 216 (Soil Microorganisms - Nitrogen Transformation Test) | |
| Water solubility: | | | 0,0166 | g/l | | OECD 105 (Water Solubility) | 20°C |

| Silica, amorphous | | | | | | | |
|--|----------|------|---------|------|-------------------------|--|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | EC0 | 96h | >10000 | mg/l | Brachydanio rerio | OECD 203 (Fish, Acute Toxicity Test) | |
| 12.1. Toxicity to daphnia: | EC0 | 24h | >1000 | mg/l | Daphnia magna | OECD 202 (Daphnia sp. Acute Immobilisation Test) | |
| 12.1. Toxicity to algae: | ErC50 | 72h | >=10000 | mg/l | Scenedesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.2. Persistence and degradability: | | | | | | | Inorganic products cannot be eliminated from water through biological purification methods. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

08 04 09 waste adhesives and sealants containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number:

2259

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

UN 2259 TRIETHYLENETETRAMINE SOLUTION



Page 32 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.02.2020 / 0015
 Replacing version dated / version: 15.04.2019 / 0014
 Valid from: 27.02.2020
 PDF print date: 26.02.2021
 Fluessig-Metall

14.3. Transport hazard class(es): 8
 14.4. Packing group: II
 Classification code: C7
 LQ: 1 L
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code: E

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 TRIETHYLENETETRAMINE SOLUTION

14.3. Transport hazard class(es): 8
 14.4. Packing group: II
 EmS: F-A, S-B
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable



Transport by air (IATA)

14.2. UN proper shipping name:
 Triethylenetetramine solution
 14.3. Transport hazard class(es): 8
 14.4. Packing group: II
 14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
 Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 0,96 %

REGULATION (EC) No 648/2004

n.a.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 2
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|--|
| Skin Corr. 1B, H314 | Classification according to calculation procedure. |
| Eye Dam. 1, H318 | Classification according to calculation procedure. |

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 27.02.2020 / 0015

Replacing version dated / version: 15.04.2019 / 0014

Valid from: 27.02.2020

PDF print date: 26.02.2021

Fluessig-Metall

| | |
|-------------------------|--|
| Skin Sens. 1, H317 | Classification according to calculation procedure. |
| Aquatic Chronic 3, H412 | Classification according to calculation procedure. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H317 May cause an allergic skin reaction.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Skin Corr. — Skin corrosion

Eye Dam. — Serious eye damage

Skin Sens. — Skin sensitization

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Acute Tox. — Acute toxicity - dermal

Acute Tox. — Acute toxicity - oral

Eye Irrit. — Eye irritation

Skin Irrit. — Skin irritation

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

ATE Acute Toxicity Estimate

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level

DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community

ECHA European Chemicals Agency

EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera

EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number

gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer

IATA International Air Transport Association

Page 34 of 34
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 27.02.2020 / 0015
 Replacing version dated / version: 15.04.2019 / 0014
 Valid from: 27.02.2020
 PDF print date: 26.02.2021
 Fluessig-Metall

IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 n.a. not applicable
 n.av. not available
 n.c. not checked
 n.d.a. no data available
 OECD Organisation for Economic Co-operation and Development
 org. organic
 PBT persistent, bioaccumulative and toxic
 PE Polyethylene
 PNEC Predicted No Effect Concentration
 ppm parts per million
 PVC Polyvinylchloride
 REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
 REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
 RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
 SVHC Substances of Very High Concern
 Tel. Telephone
 UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
 VOC Volatile organic compounds
 vPvB very persistent and very bioaccumulative
 wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
 No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.