

Page 1 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Corrosion protection

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC 9a - Coastings and paints, thinners, paint removers

PC14 - Metal surface treatment products

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 7 - Industrial spraying

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 - Roller application or brushing

PROC11 - Non industrial spraying

PROC13 - Treatment of articles by dipping and pouring

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC 8d - Widespread use of non-reactive processing aid (no inclusion into or onto article, outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

(GB)

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification



Page 2 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class Hazard category Hazard statement

Flam. Liq. 3 H226-Flammable liquid and vapour.

STOT SE 3 H336-May cause drowsiness or dizziness.

Aquatic Chronic 3 H412-Harmful to aquatic life with long lasting effects.

STOT RE 2 H373-May cause damage to organs through prolonged

or repeated exposure by inhalation (central nervous

system).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Warning

H226-Flammable liquid and vapour. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H373-May cause damage to organs through prolonged or repeated exposure by inhalation (central nervous system).

P101-If medical advice is needed, have product container or label at hand. P102-Keep out of reach of children.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260-Do not breathe vapours or spray. P271-Use only outdoors or in a well-ventilated area.

P312-Call a POISON CENTRE / doctor if you feel unwell.

P405-Store locked up.

P501-Dispose of contents / container to an approved waste disposal facility.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9, aromatics

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0.1 %).

Hazardous to drinking water, on escape of even small quantities.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a. 3.2 Mixture

0.2	
Hydrocarbons, C9, aromatics	
Registration number (REACH)	



Page 3 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Index	
EINECS, ELINCS, NLP	918-668-5 (REACH-IT List-No.)
CAS	(64742-95-6)
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H335
	STOT SE 3, H336
	Aquatic Chronic 2, H411

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	
Registration number (REACH)	01-2119458049-33-XXXX
Index	
EINECS, ELINCS, NLP	919-446-0 (REACH-IT List-No.)
CAS	
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H336
	STOT RE 1, H372 (central nervous system) (as inhalation)
	Aquatic Chronic 2, H411

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	
Registration number (REACH)	01-2119463258-33-XXXX
Index	
EINECS, ELINCS, NLP	919-857-5 (REACH-IT List-No.)
CAS	
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 3, H226
	Asp. Tox. 1, H304
	STOT SE 3, H336

Methanol	Substance for which an EU exposure limit value applies.
Registration number (REACH)	
Index	603-001-00-X
EINECS, ELINCS, NLP	200-659-6
CAS	67-56-1
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP)	Flam. Liq. 2, H225
	Acute Tox. 3, H331
	Acute Tox. 3, H311
	Acute Tox. 3, H301
	STOT SE 1, H370

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

If, for example, the note P is applied for a hydrocarbon then this has already been taken into account for the classification named here.

Quote: "Note P - The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (EINECS No 200-753-7)."

Article 4 of the regulation (EC) no. 1272/2008 (CLP regulation) was also observed and taken into account for the classification named here.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.



ദ

Page 4 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1. In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media

Water jet spray

CO2

Extinction powder

Large fire:

Water jet spray / alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep unprotected persons away.

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth, sawdust) and dispose of according to Section 13. Fill the absorbed material into lockable containers.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.



Œ

Page 5 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019

PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.

Avoid aerosol formation.

Avoid inhalation, and contact with eyes or skin.

Keep away from sources of ignition - Do not smoke.

Take precautions against electrostatic charges.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.

Observe special storage conditions.

Not to be stored in gangways or stair wells.

Store product closed and only in original packing.

Store in a well ventilated place.

Store at room temperature.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40): 600 mg/m3

Chemical Name	Hydrocarbons, C9, aromatics	Content %:1-<10
WEL-TWA: 500 mg/m3 (Aromatics	WEL-STEL:	
Monitoring procedures:	 Draeger - Hydrocarbons 2/a (81 03 581) 	
	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 	
	- Compur - KITA-187 S (551 174)	
BMGV:	Other information:	
Chemical Name	Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Content %:1-<10
WEL-TWA: 800 mg/m3	WEL-STEL:	
Monitoring procedures:	 Draeger - Hydrocarbons 2/a (81 03 581) 	
	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 	
	 Compur - KITA-187 S (551 174) 	
BMGV:	Other information:	(OEL acc. to RCP-method,
	paragraphs 84-87, E	EH40)
Chemical Name	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Content %:1-<10
WEL-TWA: 800 mg/m3	WEL-STEL:	
Monitoring procedures:	 Draeger - Hydrocarbons 2/a (81 03 581) 	
	 Draeger - Hydrocarbons 0,1%/c (81 03 571) 	
	- Compur - KITA-187 S (551 174)	
BMGV:	Other information:	(OEL acc. to RCP-method,
	paragraphs 84-87, E	EH40)
Chemical Name	Methanol	Content %:0,1-<1



(B)

Page 6 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119			
WEL-TWA: 200 ppm (266 mg/m3) (WEL), 200 ppm (260 mg/m3) (EU)	WEL-STEL: 250 ppm (333 mg	g/m3 (WEL)	
Monitoring procedures: -	Compur - KITA-119 SA (549 640)		
-	Compur - KITA-119 U (549 657)		
-	Draeger - Alcohol 25/a Methanol (8	31 01 631)	
	DFG (D) (Loesungsmittelgemische	e 6), DFG (E) (Solvent mix	ktures 6) - 1998, 2002 - EU
-	project BC/CEN/ENTR/000/2002-1	6 card 65-1 (2004)	
-	Draeger - Alcohol 100/a (CH 29 70	01)	
BMGV:	-	Other information: Sk	k (WEL, EU)
© Chemical Name Bitumen			Content %:
WEL-TWA: 5 mg/m3 (Asphalt, petroleum fumes)	WEL-STEL: 10 mg/m3 (Aspha	alt, petroleum fumes)	
Monitoring procedures:	(p	, решене	1
BMGV:		Other information:	
Calairum aarkan	-1-		Content 0/.
© Chemical Name Calcium carbon			Content %:
WEL-TWA: 4 mg/m3 (respirable dust), 10 mg/m3	WEL-STEL:		
(total inhalable dust)			
Monitoring procedures:			
BMGV:		Other information:	
©B Chemical Name Oil mist, mineral			Content %:
WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal	WEL-STEL:		
working fluids, ACGIH)			
Monitoring procedures: -	Draeger - Oil 10/a-P (67 28 371)		
-	Draeger - Oil Mist 1/a (67 33 031)		
BMGV:	-	Other information:	

Hydrocarbons, C9, aroma	Hydrocarbons, C9, aromatics					
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - inhalation	Long term, systemic effects	DNEL	32	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	25	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	150	mg/m3	

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	26	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	71	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	44	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	330	mg/m3	

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics



(B)

Page 7 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 $\,/\,0013$

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - oral	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	900	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	185	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	125	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	300	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1500	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	208	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	871	mg/m3	

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	154	mg/l	
	Environment - marine		PNEC	15,4	mg/l	
	Environment - sediment, freshwater		PNEC	570,4	mg/kg	
	Environment - sediment, marine		PNEC	57,04	mg/kg	
	Environment - soil		PNEC	23,5	mg/kg	
	Environment - water, sporadic (intermittent) release		PNEC	1540	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - freshwater		PNEC	20,8	mg/l	
	Environment - marine		PNEC	2,08	mg/l	
	Environment - sediment		PNEC	77	mg/kg	
	Environment - sediment		PNEC	7,7	mg/kg	
Consumer	Human - inhalation	Long term, local effects	DNEL	50	mg/m3	
Consumer	Human - dermal	Short term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Short term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - dermal	Long term, systemic effects	DNEL	8	mg/kg body weight/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	50	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	8	mg/kg body weight/day	



Page 8 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Workers / employees	Human - dermal	Short term, systemic effects	DNEL	40	mg/kg body weight/day
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m3
Workers / employees	Human - inhalation	Short term, local effects	DNEL	260	mg/m3
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	40	mg/kg body weight/day
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	260	mg/m3
Workers / employees	Human - inhalation	Long term, local effects	DNEL	260	mg/m3

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Solvent resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

>= 0,12

Permeation time (penetration time) in minutes:

> 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

If OES or MEL is exceeded.

Gas mask filter A (EN 14387), code colour brown

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).

^{(8) =} Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.

^{** =} The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.



Page 9 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

At high concentrations:

Protective respirator with independent air supply.

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Pastelike, Liquid Physical state:

Colour: Black Odour:

Characteristic Odour threshold: Not determined pH-value: Not determined Not determined

Melting point/freezing point: 130 °C Initial boiling point and boiling range:

31 °C (DIN 53213 (Pensky-Martens, closed cup)) Flash point:

Evaporation rate: Not determined

Flammability (solid, gas): Lower explosive limit: 0,6 Vol-% Upper explosive limit: 7 Vol-% Vapour pressure: 2 hPa (20°C) Vapour pressure: 15 hPa (50°C)

Vapour density (air = 1): Not determined

Density: 1,28 g/cm3 (20°C, DIN 51757) Bulk density:

Solubility(ies): Not determined

Water solubility: Not miscible Partition coefficient (n-octanol/water): Not determined

>200 °C (Ignition temperature) Auto-ignition temperature:

Auto-ignition temperature: No Decomposition temperature: Not determined

17000 mPas (20°C) Viscosity:

Explosive properties: Possible build up of explosive/highly flammable vapour/air mixture.

n.a.

Product is not explosive. No

Oxidising properties:

9.2 Other information

Miscibility: Not determined Fat solubility / solvent: Not determined Conductivity: Not determined Surface tension: Not determined

24,7 % (Organic solvents) Solvents content:

SECTION 10: Stability and reactivity

10.1 Reactivity

Possible build up of flammable vapour/air mixture.

10.2 Chemical stability



Page 10 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Stable with proper storage and handling. 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

10.5 Incompatible materials

Avoid contact with oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by dermal route:	ATE	>2000	mg/kg			calculated value
Acute toxicity, by inhalation:	ATE	>20	mg/l/4h			calculated value, Vapours
Acute toxicity, by inhalation:	ATE	>5	mg/l/4h			calculated value, Aerosol
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3492	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,693	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Germ cell mutagenicity:					OECD 475 (Mammalian	Negative
					Bone Marrow	
					Chromosome	
					Aberration Test)	



Page 11 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Germ cell mutagenicity:		OECD 476 (In Vitro	Negative
		Mammalian Cell Gene Mutation Test)	
Germ cell mutagenicity:		OECD 479 (Genetic	Negative
		Toxicology - In Vitro Sister Chromatid	
		Exchange assay in	
		Mammalian Cells)	
Carcinogenicity:		Wariirialian Oclis)	Negative
Reproductive toxicity:		OECD 414 (Prenatal	Negative
. toproductive termony:		Developmental Toxicity	. rogairo
		Study)	
Reproductive toxicity:		OECD 416 (Two-	Negative
,		generation `	
		Reproduction Toxicity	
		Study)	
Specific target organ toxicity -			STOT SE 3,
single exposure (STOT-SE):			H335, STOT SE
			3, H336
Specific target organ toxicity -		OECD 408 (Repeated	Negative
repeated exposure (STOT-RE):		Dose 90-Day Oral	
		Toxicity Study in	
On a sifi a tangent annua tandaka		Rodents)	N th
Specific target organ toxicity -		OECD 452 (Chronic	Negative
repeated exposure (STOT-RE):		Toxicity Studies)	Yes
Aspiration hazard: Symptoms:			respiratory
Symptoms.			distress,
			coughing,
			burning of the
			membranes of
			the nose and
			throat,
			drowsiness,
			dizziness,
			headaches,
			nausea,
			unconsciousnes
			, fever, ear
			noises, drying o
			the skin.

Hydrocarbons, C9-C12, n-alkai	nes, isoalkane	s, cyclics, ard	matics (2-25%)			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>15000	mg/kg	Rat	OECD 401 (Acute Oral	
					Toxicity)	
Acute toxicity, by dermal route:	LD50	>3400	ml/kg	Rabbit	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>13100	mg/m3/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:					OECD 404 (Acute	Analogous
					Dermal	conclusion,
					Irritation/Corrosion)	Repeated
						exposure may
						cause skin
						dryness or
						cracking.
Serious eye damage/irritation:					OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Analogous
						conclusion
Reproductive toxicity (Effects on fertility):						Negative



Page 12 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Specific target organ toxicity -	OECD 408 (Repeated	Target organ(s):
repeated exposure (STOT-RE):	Dose 90-Day Oral	central nervous
	Toxicity Study in	system
	Rodents)	,
Aspiration hazard:		Yes
Symptoms:		drowsiness,
		abdominal pain,
		unconsciousness
		, vomiting,
		nausea
Symptoms:		drowsiness,
		fatigue
Specific target organ toxicity -		Target organ(s):
repeated exposure (STOT-RE),		central nervous
inhalat.:		system

Hydrocarbons, C9-C11, n-alkar	nes, isoalkane	s, cyclics, <2	% aromatics			
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LD50	>18,5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Carcinogenicity:					OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative, Analogous conclusion
Reproductive toxicity:					OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness.
Aspiration hazard:						Yes
Symptoms:						unconsciousness , headaches, dizziness, discoloration of the skin, vomiting, diarrhoea
Specific target organ toxicity - repeated exposure (STOT-RE), oral:					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Not to be expected

Methanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes



Page 13 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Acute toxicity, by oral route:	ATE	300	mg/kg	Human being		Experiences on
						persons.
Acute toxicity, by dermal route:	LD50	17100	mg/kg	Rabbit		Does not
						conform with EU
						classification.
Acute toxicity, by inhalation:	LC50	85	mg/l/4h	Rat		Not relevant for
						classification.,
						Vapours
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Mild irritant
					Irritation/Corrosion)	
Respiratory or skin				Guinea pig	OECD 406 (Skin	No (skin contact)
sensitisation:					Sensitisation)	
Germ cell mutagenicity:					OECD 471 (Bacterial	Negative
					Reverse Mutation Test)	
Symptoms:						abdominal pain,
						vomiting,
						headaches,
						gastrointestinal
						disturbances,
						drowsiness,
						visual
						disturbances,
						watering eyes,
						nausea, mental
						confusion

Calcium carbonate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>2000	mg/kg	Rat	OECD 420 (Acute Oral	
					toxicity - Fixe Dose	
					Procedure)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	OECD 402 (Acute	
					Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>3	mg/l/4h	Rat	OECD 403 (Acute	
					Inhalation Toxicity)	
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute	Not irritant
					Dermal	
					Irritation/Corrosion)	
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye	Not irritant,
					Irritation/Corrosion)	Mechanical
						irritation possible
Respiratory or skin						No (skin contact)
sensitisation:						
Germ cell mutagenicity:					in vitro	Negative
Carcinogenicity:						Negative,
						administered as
						Ca-lactate
Reproductive toxicity:						Negative,
						administered as
						Ca-carbonate

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Unterboden-Schutz strei	chbar - schwarz	z 2 kg					
Art.: 6119							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and							n.d.a.
degradability:							



Page 14 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

12.3. Bioaccumulative potential:	n.d.a.
12.4. Mobility in soil:	n.d.a.
12.5. Results of PBT and vPvB assessment	n.d.a.
12.6. Other adverse effects:	n.d.a.
Other information:	According to the recipe, contains no AOX.
Other information:	DOC-elimination degree(complexi ng organic substance)>= 80%/28d: n.a.

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	9,2	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	3,2	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	ErL50	72h	2,9	mg/l	Pseudokirchneriell	OECD 201 (Alga,	
					a subcapitata	Growth Inhibition	
						Test)	
12.2. Persistence and		28d	54-56	%		OECD 301 B	
degradability:						(Ready	
						Biodegradability -	
						Co2 Evolution	
						Test)	
12.2. Persistence and		28d	78	%		OECD 301 E	Readily
degradability:						(Ready	biodegradable
						Biodegradability -	
						Modified OECD	
						Screening Test)	
12.2. Persistence and		28d	78	%		OECD 301 F	
degradability:						(Ready	
						Biodegradability -	
						Manometric	
						Respirometry Test)	
12.3. Bioaccumulative ootential:	Log Pow		3,7 - 4,5				
12.5. Results of PBT							No PBT
and vPvB assessment							substance, No
							vPvB substance

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	10-30	mg/l	Oncorhynchus	OECD 203 (Fish,	
					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus	QSAR	
					mykiss		
12.1. Toxicity to daphnia:	NOELR	21d	0,28	mg/l	Daphnia magna	OECD 211	
						(Daphnia magna	
						Reproduction Test)	



Page 15 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

12.1. Toxicity to daphnia:	EC50	48h	10-22	mg/l	Daphnia magna	OECD 202
						(Daphnia sp.
						Acute
						Immobilisation
						Test)
12.1. Toxicity to algae:	ErL50	72h	4,1-10	mg/l	Pseudokirchneriell	OECD 201 (Alga,
					a subcapitata	Growth Inhibition
					·	Test)
12.1. Toxicity to algae:	NOELR	72h	0,22-	mg/l	Pseudokirchneriell	OECD 201 (Alga,
			0,76		a subcapitata	Growth Inhibition
					·	Test)
12.1. Toxicity to algae:	ErL50	72h	4,1-10	mg/l	Pseudokirchneriell	OECD 201 (Alga,
					a subcapitata	Growth Inhibition
						Test)
12.1. Toxicity to algae:	NOELR	72h	0,22-	mg/l	Pseudokirchneriell	OECD 201 (Alga,
			0,76		a subcapitata	Growth Inhibition
					·	Test)
12.2. Persistence and		28d	75	%		OECD 301 F
degradability:						(Ready
						Biodegradability -
						Manometric
						Respirometry Test)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	NOELR	28d	0,13	mg/l	Oncorhynchus mykiss	QSAR	
12.1. Toxicity to daphnia:	EC50	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.3. Bioaccumulative potential:			5-6,7				High
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to algae:	ErC50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EbC50	72h	>1000	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	NOELR	72h	100	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	80	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to algae:	NOELR	72h	3	mg/l	Pseudokirchneriell a subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.5. Results of PBT and vPvB assessment						7	No PBT substance, No vPvB substance

Methanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	15400	mg/l	Lepomis		
-					macrochirus		
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l	Daphnia magna		



Œ

Page 16 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

12.2. Persistence and degradability:		28d	99	%		OECD 301 D (Ready Biodegradability -	Readily biodegradable
100 5:	205		00.100		0.1	Closed Bottle Test)	N
12.3. Bioaccumulative	BCF		28400		Chlorella vulgaris		Not to be
potential:							expected
Other information:	DOC		<70	%			
Other information:	BOD		>60	%			

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus	OECD 203 (Fish,	
-					mykiss	Acute Toxicity	
						Test)	
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202	
						(Daphnia sp.	
						Acute	
						Immobilisation	
						Test)	
12.1. Toxicity to algae:	EC50	72h	>14	mg/l	Desmodesmus	OECD 201 (Alga,	
					subspicatus	Growth Inhibition	
						Test)	
Toxicity to bacteria:	EC50	3h	>1000	mg/l	activated sludge	OECD 209	
						(Activated Sludge,	
						Respiration	
						Inhibition Test	
						(Carbon and	
						Ammonium	
Toxicity to annelids:					Eisenia foetida	Oxidation)) OECD 207	Negative
TOXICITY TO ATTIEIRUS.					Liseriia luellua	(Earthworm,	ivegative
						Acute Toxicity	
						Tests)	
Water solubility:			0.014	g/l		10010)	

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.

Owing to the user's specific conditions for use and disposal, other waste codes may be

allocated under certain circumstances. (2014/955/EU)

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

E.g. dispose at suitable refuse site.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

SECTION 14: Transport information

General statements

14.1. UN number:



Page 17 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es):

14.4. Packing group:

15. not subject to ADR/RID, in accordance with to 2.2.3.1.5 (<= 450 l)

16. n.a.

17. n.a.

Classification code:

LQ:

14.5. Environmental hazards:

Tunnel restriction code:

n.a.

Tunnel restriction code:

n.a.

Transport by sea (IMDG-code)

14.2. UN proper shipping name:

COATING SOLUTION
Transport in accordance with 2.3.2.5 of the IMDG Code

14.3. Transport hazard class(es):
14.4. Packing group:
III
EmS:
F-E, S-E
Marine Pollutant:
n.a

14.5. Environmental hazards:

Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:

Coating solution

14.3. Transport hazard class(es):314.4. Packing group:III

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained. All persons involved in transporting must observe safety regulations.

Precautions must be taken to prevent damage.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Freighted as packaged goods rather than in bulk, therefore not applicable.

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)! Regulation (EC) No 1907/2006, Annex XVII

Methanol

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)! Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered

according to storage, handling etc.):

according to cicrago, narianing cic.	/ -		
Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of	Qualifying quantity (tonnes) of
		dangerous substances as	dangerous substances as
		referred to in Article 3(10) for the	referred to in Article 3(10) for the
		application of - Lower-tier	application of - Upper-tier
		requirements	requirements
P5c		5000	50000

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

2 i dati de la 12 i da 12 de la decentión de l							
Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity	Qualifying quantity			
			(tonnes) for the	(tonnes) for the			
			application of - Lower-tier	application of - Upper-tier			
			requirements	requirements			
22	Methanol		500	5000			
	Entry Nr	Entry Nr Dangerous substances	Entry Nr Dangerous substances Notes to Annex I	Entry Nr Dangerous substances Notes to Annex I Qualifying quantity (tonnes) for the application of - Lower-tier requirements			







Page 18 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 315,6 q/l Directive 2010/75/EU (VOC): 24,66 %

Observe incident regulations.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

2, 8 Revised sections:

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Flam. Liq. 3, H226	Classification based on test data.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
STOT RE 2, H373	Classification according to calculation procedure.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H372 Causes damage to organs through prolonged or repeated exposure by inhalation.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H370 Causes damage to organs.

H411 Toxic to aquatic life with long lasting effects.

Flam. Liq. — Flammable liquid STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Aquatic Chronic — Hazardous to the aquatic environment - chronic

STOT RE — Specific target organ toxicity - repeated exposure

Asp. Tox. — Aspiration hazard STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation

Acute Tox. — Acute toxicity - inhalation Acute Tox. — Acute toxicity - dermal

Acute Tox. — Acute toxicity - oral

STOT SE — Specific target organ toxicity - single exposure

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to



Page 19 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the

International Carriage of Dangerous Goods by Road) AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ASTM ASTM International (American Society for Testing and Materials)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BSEF The International Bromine Council

bw body weight

CAS Chemical Abstracts Service

CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances

and mixtures)

CMR carcinogenic, mutagenic, reproductive toxic

DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level

dw dry weight

e.g. for example (abbreviation of Latin 'exempli gratia'), for instance

EC European Community
ECHA European Chemicals Agency
EEC European Economic Community

EINECS European Inventory of Existing Commercial Chemical Substances

ELINCS European List of Notified Chemical Substances

EN European Norms

EPA United States Environmental Protection Agency (United States of America)

etc. et cetera EU European Union

EVAL Ethylene-vinyl alcohol copolymer

Fax. Fax number gen. general

GHS Globally Harmonized System of Classification and Labelling of Chemicals

GWP Global warming potential

IARC International Agency for Research on Cancer IATA International Air Transport Association IBC (Code) International Bulk Chemical (Code)

IMDG-code International Maritime Code for Dangerous Goods

incl. including, inclusive

IUCLID International Uniform Chemical Information Database

LQ Limited Quantities

MARPOL International Convention for the Prevention of Marine Pollution from Ships

n.a. not applicablen.av. not availablen.c. not checkedn.d.a. no data available

OECD Organisation for Economic Co-operation and Development

org. organic

PBT persistent, bioaccumulative and toxic

PE Polyethylene

PNEC Predicted No Effect Concentration

ppm parts per million PVC Polyvinylchloride

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration,

Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List

Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International

Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight



Page 20 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 25.07.2019 / 0014

Replacing version dated / version: 05.07.2018 / 0013

Valid from: 25.07.2019 PDF print date: 25.07.2019

Unterboden-Schutz streichbar - schwarz 2 kg

Art.: 6119

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge. No responsibility.

These statements were made by: Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.