

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name or designation of the mixture	JURID Brake Fluid
Registration number	-
Synonyms	DOT 3 – All grades, DOT 4 - grades with Wet Boiling Points < 165 °C.
Issue date	01-September-2015
Version number	01
Revision date	-
Supersedes date	-
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	Hydraulic fluid in automotive brake/clutch system.
Uses advised against	None known.
1.3. Details of the supplier of the	e safety data sheet
Manufacturer/Supplier	
Manufacturer/Supplier Company name	Federal Mogul Corporation (BE)
••	Federal Mogul Corporation (BE) Central Distribution Centre
Company name	
Company name	Central Distribution Centre
Company name	Central Distribution Centre Prins Boudewijnlaan 7
Company name Address:	Central Distribution Centre Prins Boudewijnlaan 7 B-2550 Kontich, Belgium
Company name Address:	Central Distribution Centre Prins Boudewijnlaan 7 B-2550 Kontich, Belgium Product Manager GA Europe, Middle-East and Africa
Company name Address:	Central Distribution Centre Prins Boudewijnlaan 7 B-2550 Kontich, Belgium Product Manager GA Europe, Middle-East and Africa e-mail: alexandru.nitu@federalmogul.com
Company name Address:	Central Distribution Centre Prins Boudewijnlaan 7 B-2550 Kontich, Belgium Product Manager GA Europe, Middle-East and Africa e-mail: alexandru.nitu@federalmogul.com Address: Alexandru Nitu – Calea Floreasca 169A – 014459 Bucharest-

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards		
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Specific target organ toxicity - repeated exposure	Category 2 (Kidney)	H373 - May cause damage to organs (Kidney) through prolonged or repeated exposure.

Hazard summary

Causes serious eye damage. May cause damage to the kidneys.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Diethylene glycol, Triethylene glycol monobutyl ether

Hazard pictograms

 $\wedge \wedge$



Signal word		
Hazard statements		
H319		
H373		

Causes serious eye irritation. May cause damage to organs (Kidney) through prolonged or repeated exposure.

Precautionary statements

Prevention P102

Keep out of reach of children.

JURID Brake Fluid

Warning

P270	Do not eat, drink or smoke when using this product.	
Response		
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337 + P313	If eye irritation persists: Get medical advice/attention.	
P301 + P311	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.	
Storage		
P410	Protect from sunlight.	
P411 + P235	Store at temperatures not exceeding 30°C/86°F. Keep cool.	
Disposal	Dispose of contents in accordance with local/regional/national/international regulations.	
Supplemental label information	None.	
2.3. Other hazards	Not a PBT or vPvB substance or mixture.	

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Triethylene glycol monobutyl e	ether 20 - 45	143-22-6 205-592-6	-	603-183-00-0	
Classification: Eye	Dam. 1;H318				В
Diethylene glycol	10 - 25	111-46-6 203-872-2	-	603-140-00-6	
Classification: Acu	te Tox. 4;H302, ST	OT RE 2;H373			
2-(2-Butoxyethoxy)-ethanol	1 - 3	112-34-5 203-961-6	-	603-096-00-8	#
Classification: Acu	te Tox. 4;H302, Eye	e Irrit. 2;H319			
2-(2-Methoxyethoxy)ethanol	0 - < 3	111-77-3 203-906-6	-	603-107-00-6	#
Classification: Rep	or. 2;H361d				

List of abbreviations and symbols that may be used above

#: This substance has been assigned Community workplace exposure limit(s).

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
4.1. Description of first aid meas	sures
Inhalation	Move injured person into fresh air and keep person calm under observation. Get medical attention if any discomfort continues.
Skin contact	Remove contaminated clothes and rinse skin thoroughly with water. Get medical attention if irritation develops or persists.
Eye contact	Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.
Ingestion	Rinse mouth thoroughly with water and give large amounts of milk or water to people not unconscious. Only induce vomiting at the instruction of medical personnel. Get medical attention if any discomfort continues.
4.2. Most important symptoms and effects, both acute and delayed	Exposed may experience eye tearing, redness, and discomfort. Defats the skin.
4.3. Indication of any immediate medical attention and special treatment needed	Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards

This product is not flammable. Will burn if involved in a fire.

5.1. Extinguishing media	
Suitable extinguishing media	Water spray, dry powder or carbon dioxide.
Unsuitable extinguishing media	Water jet.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing should be worn when fighting chemical fires. Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace.
Special fire fighting procedures	Use standard firefighting procedures and consider the hazards of other involved materials. Containers close to fire should be removed immediately or cooled with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	Extinguish all ignition sources. Avoid sparks, flames and smoking. Ventilate. Avoid contact with skin and eyes. Wear suitable protective clothing.	
For emergency responders	Use personal protection recommended in Section 8 of the SDS.	
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.	
6.3. Methods and material for containment and cleaning up	Absorb spillage with suitable absorbent material. Collect in containers and seal securely.	
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.	

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Avoid contact with skin and eyes. Wear appropriate personal protective equipment. Do not eat, drink or smoke when using the product. See Section 8 for personal protective equipment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Keep container in a well-ventilated place. Keep away from heat, sparks and open flame. Store away from incompatible materials.
7.3. Specific end use(s)	Hydraulic fluid in automotive brake/clutch system.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	
2-(2-Butoxyethoxy)-ethanol (CAS 112-34-5)	STEL	101.2 mg/m3	
. ,		15 ppm	
	TWA	67.5 mg/m3	
		10 ppm	
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)	TWA	50.1 mg/m3	
, ,		10 ppm	
Diethylene glycol (CAS 111-46-6)	TWA	101 mg/m3	
		23 ppm	

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU

Components	Туре	Value	
2-(2-Butoxyethoxy)-ethanol (CAS 112-34-5)	STEL	101.2 mg/m3	
, , , , , , , , , , , , , , , , , , ,		15 ppm	
	TWA	67.5 mg/m3	
		10 ppm	
2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)	TWA	50.1 mg/m3	
, , ,		10 ppm	
iological limit values	No biological exposure limits noted for th	e ingredient(s).	

Recommended monitoring procedures	Follow standard monitoring procedures.	
Derived no-effect level (DNEL)	Not available.	
Predicted no effect concentrations (PNECs)	Not available.	
Exposure guidelines UK EH40 WEL: Skin designa	tion	
2-(2-Methoxyethoxy)etha	nol (CAS 111-77-3) Can be absorbed through the skin.	
8.2. Exposure controls		
Appropriate engineering controls	Use explosion-proof equipment. Adequate ventilation should be provided whenever the material is heated or mists are generated. Provide easy access to water supply and eye wash facilities.	
Individual protection measures,	such as personal protective equipment	
General information	Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.	
Eye/face protection	Chemical goggles and face shield are recommended.	
Skin protection		
- Hand protection	Chemical resistant gloves. Butyl rubber gloves are recommended. Be aware that the liquid may penetrate the gloves. Frequent change is advisable. Suitable gloves can be recommended by the glove supplier.	
- Other	Wear appropriate clothing to prevent repeated or prolonged skin contact.	
Respiratory protection	In case of inadequate ventilation or when the product is heated, use suitable respiratory equipment with gas filter (type A2).	
Thermal hazards	When material is heated, wear gloves to protect against thermal burns.	
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Observe any medical surveillance requirements.	
Environmental exposure controls	Environmental manager must be informed of all major releases.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance		
Physical state	Liquid.	
Form	Liquid.	
Colour	Colourless to amber.	
Odour	Bland.	
Odour threshold	Not available.	
рН	7 - 11.5	
Melting point/freezing point	< -50 °C (< -58 °F)	
Initial boiling point and boiling range	> 205 °C (> 401 °F)	
Flash point	> 80.0 °C (> 176.0 °F)	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or explosive limits		
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Vapour pressure	< 0.002 bar	
Vapour density	Not available.	
Relative density	1.01 - 1.07	
Solubility(ies)	Miscible in water. Miscible with: Ethanol.	
Partition coefficient (n-octanol/water)	< 2	
Auto-ignition temperature	> 300 °C (> 572 °F)	
Decomposition temperature	Not available.	

Viscosity	5 - 10 cSt @ (20°C) Approximate
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Stable under normal temperature conditions. Glycol Ethers can form peroxides on storage – do not distil to dryness.
10.3. Possibility of hazardous reactions	Will not occur.
10.4. Conditions to avoid	Avoid exposure to high temperatures or direct sunlight.
10.5. Incompatible materials	Strong oxidising agents. Mineral oil.
10.6. Hazardous decomposition products	Carbon dioxide. Carbon monoxide. Formaldehyde. Formic acid.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes o	f exposure
Inhalation	Glycol does not easily form a vapour at normal temperatures. Therefore, it must be heated or misted before inhalation exposure can occur.
Skin contact	May cause skin irritation.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms	Exposed may experience eye tearing, redness, and discomfort. Defats the skin.

11.1. Information on toxicological effects

Acute toxicity	May cause discomfort if swallowed.	
Components	Species	Test results
2-(2-Butoxyethoxy)-ethanol (CA	AS 112-34-5)	
Acute		
Dermal		
LD50	Rabbit	2700 mg/kg
Oral		
LD50	Rat	4500 mg/kg
2-(2-Methoxyethoxy)ethanol (C	AS 111-77-3)	
Acute		
Dermal		
LD50	Rabbit	8980 ml/kg
Oral		
LD50	Rat	6700 ml/kg
Triethylene glycol monobutyl et	her (CAS 143-22-6)	
Acute		
Dermal		
LD50	Rabbit	3.54 ml/kg
Oral		
LD50	Rat	5300 mg/kg
Skin corrosion/irritation	May cause skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory sensitisation	No data available.	
Skin sensitisation	Not a skin sensitiser.	
Germ cell mutagenicity	No data available.	
Carcinogenicity	No data available.	
Reproductive toxicity	Not classified. The product contains a small a the unborn child.	amount of substance that is suspected of damaging

Specific target organ toxicity - single exposure	No data available.	
Specific target organ toxicity - repeated exposure	May cause damage to organs (Kidney) through prolonged or repeated exposure.	
Aspiration hazard	No data available.	
Mixture versus substance information	Not available.	
Other information	Glycol ethers: Some glycol ethers cause adverse effects in animals that include the reproductive system, offspring, blood, kidney and liver. Organic solvents may be absorbed into the body by inhalation and cause permanent damage to the nervous system, including the brain.	
SECTION 12: Ecological information		
12.1. Toxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.	

Test results

	possibility that l
Components	
Triethylene glycol monob	utyl ether (CAS 143-22-6)
Aquatic	
A (

Aquallo			
Acute			
Fish	LC50	Pimephales promelas	2400 mg/l, 96 hours
12.2. Persistence and degradability	Expected to	b be inherently biodegradable. Exp	pected to be readily biodegradable.
12.3. Bioaccumulative potential	Potential to	bioaccumulate is low.	
Partition coefficient n-octanol/water (log Kow) JURID Brake Fluid 2-(2-Butoxyethoxy)-ethanol (CAS 112-34-5	< 2) 0.56	
Bioconcentration factor (BCF)	Not availab	le.	
12.4. Mobility in soil	No data av	ailable.	
Mobility in general	The produc	t is miscible with water. May sprea	ad in water systems.
12.5. Results of PBT and vPvB assessment	Not a PBT	or vPvB substance or mixture.	
12.6. Other adverse effects	No data av	ailable.	

Species

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations.
Contaminated packaging	Since emptied containers retain product residue, follow label warnings even after container is emptied.
EU waste code	16 01 13* Waste codes should be assigned by the user based on the application for which the product was used.
Disposal methods/information	Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

SECTION 14: Transport information

ADR

Not regulated as dangerous goods.

RID

Not regulated as dangerous goods.

ADN

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

14.7. Transport in bulk Not applicable.

according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended Not listed.

Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended Not listed

- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended 2-(2-Butoxyethoxy)-ethanol (CAS 112-34-5)

2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended

Not listed.

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

2-(2-Methoxyethoxy)ethanol (CAS 111-77-3)

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances

Not listed.

Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

2-(2-Butoxyethoxy)-ethanol (CAS 112-34-5) 2-(2-Methoxyethoxy)ethanol (CAS 111-77-3) Diethylene glycol (CAS 111-46-6)

Triethylene glycol monobutyl ether (CAS 143-22-6)

Directive 94/33/EC on the protection of young people at work

Not listed.

Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended and respective national laws implementing EC directives. The product is classified and labelled in accordance with EC directives or respective national laws.
National regulations	Follow national regulation for work with chemical agents.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations	
	DNEL: Derived No-Effect Level. PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic.
	vPvB: Very Persistent and very Bioaccumulative.
References	Registry of Toxic Effects of Chemical Substances (RTECS) HSDB® - Hazardous Substances Data Bank
Information on evaluation method leading to the classification of mixture	The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any H-statements not written out in full under Sections 2 to 15

Training information Disclaimer H302 Harmful if swallowed.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Follow training instructions when handling this material.

The information provided on this data sheet was abstracted from supplier safety data sheets and standard references in occupational health and toxicology. Federal-Mogul makes no representation or warranty with respect to the information obtained from such references. The information is however, as of the date provided, true and accurate to the best of Federal-Mogul's knowledge, and should be used to make an independent determination of the methods to safeguard workers and the environment.