

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

Article number: 02324000, 02324050, 02324410, 02327050

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category

PC4 Anti-Freeze and de-icing products

PC35 Washing and cleaning products (including solvent based products)

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

Signal word Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Aqueous formulation of alcohol, glycol and tensides.

Dangerous components:

CAS: 64-17-5

EINECS: 200-578-6

Reg.nr.: 01-2119457610-43-xxxx

ethanol

Flam. Liq. 2, H225; Eye Irrit. 2, H319

Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %

25-<50%

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

CAS: 107-21-1 EINECS: 203-473-3 Reg.nr.: 01-2119456816-28-xxxx		ethanediol STOT RE 2, H373; Acute Tox. 4, H302	(Contd. of page 1) 1-<3%
Regulation (EC) No 648/2004 on detergents / Labelling for contents			
anionic surfactants			<5%
perfumes			
Additional information: For the wording of the listed hazard phrases refer to section 16.			

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Water spray

Fire-extinguishing powder

Alcohol resistant foam

Carbon dioxide

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. of page 2)

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 64-17-5 ethanol

WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm

CAS: 107-21-1 ethanediol

WEL (Great Britain) Short-term value: 104** mg/m³, 40** ppm
Long-term value: 10* 52** mg/m³, 20** ppm
Sk *particulate **vapour

IOELV (EU) Short-term value: 104 mg/m³, 40 ppm
Long-term value: 52 mg/m³, 20 ppm
Skin

Regulatory information

WEL (Great Britain): EH40/2018

IOELV (EU): (EU) 2017/164

DNELs

CAS: 64-17-5 ethanol

Oral	DNEL	87 mg/kg (consumer) (long-term exposure - systemic effects)
Dermal	DNEL	206 mg/kg bw/day (consumer) (long-term exposure - systemic effects)
		343 mg/kg bw/day (worker) (long-term exposure - systemic effects)
Inhalative	DNEL	950 mg/m ³ (consumer) (acute short-term exposure - local effects)
		1,900 mg/m ³ (worker) (acute short-term exposure - local effects)
	DNEL	114 mg/m ³ (consumer) (long-term exposure - systemic effects)
		950 mg/m ³ (worker) (long-term exposure - systemic effects)

CAS: 107-21-1 ethanediol

Dermal	DNEL	53 mg/kg bw/day (consumer) (long term (chronic) / systemic)
		106 mg/kg bw/day (worker) (long term (chronic) / systemic)
Inhalative	DNEL	7 mg/m ³ (consumer) (long term (chronic) / local)
		35 mg/m ³ (worker) (long term (chronic) / local)

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

(Contd. of page 3)

PNECs

CAS: 64-17-5 ethanol

PNEC	0.96 mg/l (water (fresh water))
	0.79 mg/l (water (sea water))
PNEC	3.6 mg/kg (sediment (fresh water))
	2.9 mg/kg (sediment (sea water))
	0.63 mg/kg (soil)

CAS: 107-21-1 ethanediol

PNEC	199.5 mg/l (STP)
	10 mg/l (water (intermittent release))
	10 mg/l (water (fresh water))
	1 mg/l (water (sea water))
PNEC	1.53 mg/kg (gro)
	37 mg/kg (sediment (fresh water)) (dry weight)
	3.7 mg/kg (sediment (sea water)) (dry weight)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Protection of hands: Not required in normal cases.

Eye protection: Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form:	Fluid
Colour:	Blue
Odour:	Characteristic
Odour threshold:	Not determined.

pH-value at 20 °C: 6.0 - 7.0

Change in condition

Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	78 - 200 °C

Flash point: 29 °C (EN ISO 1523)

Flammability (solid, gas): Not applicable.

Decomposition temperature: Not determined.

Auto-ignition temperature: Not determined.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

(Contd. of page 4)

Explosion limits:

Lower: 3.5 Vol.% (Main ingredient data)
Upper: 15 Vol.% (Main ingredient data)

Vapour pressure: Not determined.

Density at 20 °C: 0.96 - 0.97 g/cm³

Relative density Not determined.

Vapour density Not determined.

Evaporation rate Not determined.

Solubility in / Miscibility with water: Fully miscible.

Partition coefficient: n-octanol/water: Not determined.

Viscosity:

Flow time at 20 °C 10 - 15 s (DIN EN ISO 2431/4mm)

Kinematic at 40 °C: <20.5 mm²/s

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects There are no toxicological findings on this mixture.

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:
CAS: 64-17-5 ethanol

Oral	LD50	5,560 mg/kg (guinea pig)
		3,450 mg/kg (mouse)
		7,060 mg/kg (rat)
		6,300 mg/kg (rabbit)

Dermal	LD50	>2,000 mg/kg (rat)
--------	------	--------------------

Inhalative	LC50/4d	20,000 mg/l (rat)
------------	---------	-------------------

CAS: 107-21-1 ethanediol

Oral	LD50	7,712 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>3,500 mg/kg (mouse)
--------	------	----------------------

Inhalative	LC50 / 6 h	>2.5 mg/l (rat)
------------	------------	-----------------

Primary irritant effect:
Skin corrosion/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Serious eye damage/irritation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

Respiratory or skin sensitisation

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

(Contd. on page 6)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

(Contd. of page 5)

Repeated dose toxicity

CAS: 64-17-5 ethanol

Oral	LOAEL	3,160 mg/kg (rat)
	NOAEL	1,730 mg/kg (rat)

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

None of the ingredients are known to have effects which are carcinogenic, mutagenic or harmful to reproduction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

CAS: 64-17-5 ethanol

LC50 / 48h	8,140 mg/l (Leuciscus idus)
LC50 / 24h	>100 mg/l (Daphnia magna)
EC5 / 16h	6,500 mg/l (Pseudomonas putida)
EC50 / 48h	9,268 mg/l (Daphnia magna)

CAS: 107-21-1 ethanediol

LC50 / 96h	72,860 mg/l (Pimephales promelas)
EC20 / 0.5 h	>1,995 mg/l (activated sludge)
EC50 / 48h	>100 mg/l (Daphnia magna)
EC50 / 96 h	6,500-13,000 mg/l (Pseudokirchneriella subcapitata)
NOEC / 7 d	8,590 mg/l (Ceriodaphnia Dubia) (EPA 600/4-89/001)
	15,380 mg/l (Pimephales promelas) (EPA 600/4-89/001)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

12.3 Bioaccumulative potential

CAS: 107-21-1 ethanediol

log POW	1.36 log POW
---------	--------------

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dangerous waste in accordance with the Directive on the List of Waste Materials

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

(Contd. of page 6)

20 01 13*	solvents
15 01 10*	packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN-Number
ADR, IMDG, IATA

UN1170

14.2 UN proper shipping name
ADR 1170 ETHANOL SOLUTION
IMDG, IATA ETHANOL SOLUTION

14.3 Transport hazard class(es)
ADR, IMDG, IATA

Class 3 Flammable liquids.
Label 3

14.4 Packing group
ADR, IMDG, IATA III

14.5 Environmental hazards:
Marine pollutant: No

14.6 Special precautions for user Warning: Flammable liquids.

Transport/Additional information:
ADR
Limited quantities (LQ) 5L

Transport category 3

Tunnel restriction code D/E

UN "Model Regulation": UN 1170 ETHANOL SOLUTION, 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
National regulations:
Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Classification according to Regulation (EC) No 1272/2008

Flammable liquids On basis of test data

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 11.12.2019

Version: 5.02

Revision: 20.02.2019

Trade name: SONAX Xtreme Antifreeze & Clear View "ready to use -20°C"

(Contd. of page 7)

Abbreviations and acronyms:

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

*** Data compared to the previous version altered.**

GB