

Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Cockpit Spray New Car

Article number: 03563000

UFI: DAH0-A0WS-T008-H89H

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02

Signal word Danger

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

(Contd. on page 2)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and solvents with additives

Dangerous components:		
	butane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	20-<25%
	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	20-<25%
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 \$\infty\$ Asp. Tox. 1, H304	15-<20%
EC No 934-954-2 Reg.nr.: 01-2119826592-36-xxxx	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 \$\infty\$ Asp. Tox. 1, H304	10-<15%
	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 Asp. Tox. 1, H304, EUH066	10-<15%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%

Regulation (EC) No 648/2004 on detergents / Labelling for contents	
aliphatic hydrocarbons	≥30%
perfumes	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Remove soiled clothing

After inhalation:

Supply fresh air.

(Contd. on page 3)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 2)

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact: Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation For non-emergency personnel

Keep away from ignition sources.

Particular danger of slipping on leaked/spilled product.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 3)

Buildup of explosive mixtures possible without sufficient ventilation.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

o.i Control parameters		
Ingredients with limit values t	hat require monitoring at the workplace:	
CAS: 106-97-8 butane		
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	
OEL (Ireland)	Short-term value: 1000 ppm	
CAS: 74-98-6 propane		
OEL (Ireland) Asphx		
Hydrocarbons, C13-C16, n-alk	ranes, isoalkanes, cyclics, < 0.03% aromatics	
GERMAN RCP-METHOD (EU) Long-term value: 300 mg/m³ 2 (II) / AGW (German TRGS 900)		
Hydrocarbons, C12-C15, n-alk	ranes, isoalkanes, cyclics, < 2% aromatics	
GERMAN RCP-METHOD (EU) Long-term value: 300 mg/m³ 2 (II) / AGW (German TRGS 900)		
CAS: 75-28-5 isobutane		
OEL (Ireland)	Short-term value: 1000 ppm	

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

(Contd. on page 5)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 4)

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed.

Respiratory protection:

If the occupational exposure limit is exceeded: The following breathing protection is recommended: Respiratory filter for organic gases and vapours (Type A) Identification colour: Brown

[DIN EN 14387]

Hand protection Not required in normal cases. Eye/face protection Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:ColourlessOdour:WoodenMelting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

rangeNot applicable, as aerosol. **Flammability**Extremely flammable aerosol.

Lower and upper explosion limit

Lower:1.5 Vol % (CAS: 106-97-8 butane)Upper:10.9 Vol % (CAS: 74-98-6 propane)Flash point:Not applicable, as aerosol.

Decomposition temperature:pH
Not determined.
Not applicable.

Viscosity:

Kinematic viscosity at 40 °C <20.5 mm²/s

(Active ingredient data)

Not determined.

Not determined.

Solubility

water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)

Vapour pressure:

Density and/or relative density

Density at 20 °C: 0.8-0.82 g/cm³

Vapour density (Active ingredient data)
Not determined.

9.2 Other information

Appearance:

Form: Aerosol

Important information on protection of health and

environment, and on safety.

Auto-ignition temperature: Not determined.

Explosive properties: In use, may form flammable/explosive vapour-air

mixture.

Change in condition

Evaporation rate Not applicable.

Information with regard to physical hazard classes

Explosives Void Flammable gases Void

Aerosols

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Oxidising gases Void
Gases under pressure Void

(Contd. on page 6)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

		(Contd. of page 5)
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flammab	le	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- 10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

LD/LC50 values relevant for classification:

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

Hydrocar	bons, C15-	-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.266 mg/m³ (rat) (OECD 403)
Hydrocar	bons, C13-	C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.266 mg/m³ (rat) (OECD 403)
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.6 mg/m³ (rat) (OECD 403)
Skin corr	osion/irrita	ntion Based on available data, the classification criteria are not met.
Serious e	ye damage	e/irritation Based on available data, the classification criteria are not met.
Respirato	ory or skin	sensitisation Based on available data, the classification criteria are not met.
Germ cel	l mutageni	city Based on available data, the classification criteria are not met.
Carcinog	enicity Bas	sed on available data, the classification criteria are not met.
Reproduc	ctive toxici	ty Based on available data, the classification criteria are not met.
STOT-sin	gle exposi	ure Based on available data, the classification criteria are not met.

(Contd. on page 7)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 6)

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecolo	gical information
--------------------------	-------------------

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxici	ity:
CAS: 106-97-8	B butane
LC50 / 96 h 2	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)
CAS: 74-98-6	propane
	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)
Hydrocarbons	s, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
LC50 / 4 d >	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
LC50 / 48h	>3,193 mg/l (Acartia tonsa)
NOEC / 21 d >	>1,000 mg/l (Daphnia magna)
NOEC / 28d >	>1,000 mg/l (Oncorhynchus mykiss)
LC50/3d >	>10,000 mg/l (Skeletonema costatum)
-	s, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
LC50/2d >	>3,193 mg/l (Acartia tonsa)
LC50/4d >	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
NOEC / 21 d >	>1,000 mg/l (Daphnia magna)
NOEC / 28d >	>1,000 mg/l (Oncorhynchus mykiss)
	>10,000 mg/l (Skeletonema costatum)
•	s, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
	>1,000 mg/l (Daphnia magna) (OECD 202)
	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)
NOEC / 21 d >	>1,000 mg/l (Daphnia magna)
	>1,000 mg/l (Oncorhynchus mykiss)
	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
CAS: 75-28-5	isobutane
LC50 / 96 h 2	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)
	nce and degradability
-	s, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
Biodegradation 74 %	
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	

Biodegradation 74 %

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation 67.6 %

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 7)

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR/RID/ADN	
Class	2 5F Gases.
Label	2.1
Class	2.1 Gases.
Label	2.1
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user Stowage Code	Warning: Gases. SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

	(Contd. of page
Segregation Code	1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1
	litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2 For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2
14.7 Maritime transport in bulk according to	o IMO
instruments	Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 50.60 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

Contains gas under pressure; may explode if heated. H280

May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Aerosols On basis of test data

Date of previous version: 22.04.2021 Version number of previous version: 4.02

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level NOEC = No Observed Effect Concentration

LC = letal Concentration

(Contd. on page 10)



Printing date 22.03.2023 Version: 5.00 (replaces version 4.02) Revision: 26.07.2022

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 9)

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient
GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

INDEX. International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent IOELV = indicative occupational exposure limit values Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1 : Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas Asp. Tox. 1: Aspiration hazard – Category 1 * Data compared to the previous version altered.