

Printing date 29.10.2020

Version: 4.00

Revision: 10.10.2017

### SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: SONAX Professional Brake & Parts cleaner Article number: 836500.01, 836800.02 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) **Product category** PC35 Washing and cleaning products (including solvent based products) Application of the substance / the mixture Cleaning agent/ Cleaner 1.3 Details of the supplier of the safety data sheet Manufacturer/Supplier: SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0 Further information obtainable from: Product safety E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217 1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240 SECTION 2: Hazards identification 2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Flam. Liq. 2 H225 Highly flammable liquid and vapour. Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects. 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation. Hazard pictograms GHS02 GHS07 GHS08 GHS09 Signal word Danger Hazard-determining components of labelling: Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane cyclohexane n-hexane Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H336 May cause drowsiness or dizziness. H304 May be fatal if swallowed and enters airways. H411 Toxic to aquatic life with long lasting effects. Precautionary statements P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P261 Avoid breathing vapours. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P302+P352 IF ON SKIN: Wash with plenty of water. Do NOT induce vomiting. P331 (Contd. on page 2) GB



Printing date 29.10.2020

# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 10.10.2017

Version: 4.00

### Trade name: SONAX Professional Brake & Parts cleaner

(Contd. of page 1) P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. 2.3 Other hazards Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

22	Mixtures
3.Z	wixtures

Dangerous components:			
EC No 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane Alternative CAS number: 64742-49-0 Image: Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Image: Skin Irrit. 2, H315; STOT SE 3, H336	75 - 100%	
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119463273-41-xxxx	cyclohexane Flam. Liq. 2, H225; S Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	5 - <10%	
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane ♦ Flam. Liq. 2, H225; ♦ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	1 - <3%	
Regulation (EC) No 648/2004 on detergents / Labelling for contents			

aliphatic hydrocarbons

Additional information:

Hydrocarbon mixture:

Benzene content < 0.1%

Any entry in the EC-column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

### 4.1 Description of first aid measures

# General information:

Take affected persons out of danger area and lay down. Remove soiled clothing After inhalation: Supply fresh air. In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately . In case of unconsciousness place patient stably in side position for transportation. After skin contact: Wash the areas of skin affected with water and a mild detergent. If symptoms persist consult doctor. After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. After swallowing: Rinse out mouth and then drink plenty of water. Do not induce vomiting; call for medical help immediately. 4.2 Most important symptoms and effects, both acute and delayed Skin irritation Headache Dizziness

(Contd. on page 3)

≥30%

GB

Printing date 29.10.2020

ONAX

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Brake & Parts cleaner

Drowsiness Nausea Cramp (Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing agents: Foam Carbon dioxide Fire-extinguishing powder Water haze For safety reasons unsuitable extinguishing agents: Water with full jet 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures. In case of fire, the following can be released: Carbon monoxide and carbon dioxide 5.3 Advice for firefighters Protective equipment: Do not inhale explosion gases or combustion gases. Wear fully protective suit. Do not enter the hazardous area without a self-contained breathing apparatus. See Section 8 for information on personal protection equipment. Additional information Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

# SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Keep away from ignition sources. Ensure adequate ventilation Wear protective equipment. Keep unprotected persons away. 6.2 Environmental precautions: Do not allow to penetrate the ground/soil. Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

# SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:** 



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

**SONAX**®

Version: 4.00

Revision: 10.10.2017

(Contd. of page 3)

Trade name: SONAX Professional Brake & Parts cleaner

7.2 Conditions for safe storage, including any incompatibilities Storage:         Requirements to be met by storerooms and receptacles:         Provide solvent resistant, sealed floor.         Store in a cool location.         Information about storage in one common storage facility: Store away from foodstuffs.         Further information about storage conditions:         Store receptacle in a well ventilated area.         Keep container tightly sealed.         Protect from heat and direct sunlight.         Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         IOELS       699 mg/kg bw/day (consumer) (chronic exposition / systemic			
Provide solvent resistant, sealed floor.         Store in a cool location.         Information about storage in one common storage facility: Store away from foodstuffs.         Further information about storage conditions:         Store receptacle in a well ventilated area.         Keep container tightly sealed.         Protect from heat and direct sunlight.         Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)         Short-term value: 1050 mg/m³, 300 ppm         Long-term value: 700 mg/m³, 200 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DEVELS       Meta (Great Britain)         Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm			
Store in a cool location.         Information about storage in one common storage facility: Store away from foodstuffs.         Further information about storage conditions:         Store receptacle in a well ventilated area.         Keep container tightly sealed.         Protect from heat and direct sunlight.         Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELLS         MREL (Great Britain)         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELL (Great Britain)       Dong-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELL (Great Britain)       Dong-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELL (Great			
Information about storage in one common storage facility: Store away from foodstuffs.         Further information about storage conditions:         Store receptacle in a well ventilated area.         Keep container tightly sealed.         Protect from heat and direct sunlight.         Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         DELL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         DEL V (EU)       Long-term value: 72 mg/m³, 20 ppm         DEL S       Byster value: 72 mg/m³, 20 ppm         DINEL 699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dread       DNEL 699 mg/kg bw/day (consumer) (chronic exposition / systemic effects) <t< th=""><th></th></t<>			
Further information about storage conditions:         Store receptacle in a well ventilated area.         Keep container tightly sealed.         Protect from heat and direct sunlight.         Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)         Short-term value: 1050 mg/m³, 300 ppm         Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         Ourg-term value: 72 mg/m³, 20 ppm         DELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs         Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL         DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Oral       DNEL         DNEL       699 mg/kg bw/day (worker) (chronic exposition / systemic effects)         Oral       DNEL         DNEL       699 mg/kg bw/day (worker) (chronic exposition / systemic effects)         Oranal       DNEL         <			
Keep container tightly sealed.         Protect from heat and direct sunlight.         Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm         Long-term value: 350 mg/m³, 100 ppm       Long-term value: 350 mg/m³, 200 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 20 ppm         Determ value: 72 mg/m³, 20 ppm         Display to the form value: 72 mg/m³, 20 ppm         DOBLS         Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)       0pm/kg bw/day (worker) (chronic exposition / systemic effects)       773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
Protect from heat and direct sunlight.         Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm         Long-term value: 350 mg/m³, 100 ppm       Long-term value: 350 mg/m³, 200 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-hexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DRELs         Mydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL         Oral       DNEL         DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dremal       Oral         DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)         773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
Recommended storage temperature: 20 °C.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-hexane       MEL (Great Britain)         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs       Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL         Bermal       Gip mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dremal       DNEL			
7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-hexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELS         Mydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL         Dermal       DNEL         DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Drain       DNEL         Oral       DNEL         DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Drain       DNEL         Oral       DNEL         Oral       DNEL         Oral       DNEL         Oral       DNEL         Oral       DNEL         Oral       DNEL			
8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-hexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELS       Long-term value: 72 mg/m³, 20 ppm         DNELs       Long-term value: 72 mg/m³, 20 ppm         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)         Oral       DNEL       699 mg/kg bw/day (worker) (chronic exposition / systemi effects)			
8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-hexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELS       Long-term value: 72 mg/m³, 20 ppm         DNELs       Long-term value: 72 mg/m³, 20 ppm         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)         Oral       DNEL       699 mg/kg bw/day (worker) (chronic exposition / systemi effects)			
8.1 Control parameters         Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         Ourg-term value: 72 mg/m³, 20 ppm Long-term value: 72 mg/m³, 20 ppm         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm Long-term value: 72 mg/m³, 20 ppm         DELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs       Long-term value: 72 mg/m³, 20 ppm         DNELs         DNEL         Oral       DNEL         Oral       DNEL         OP mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Op mg/kg bw/day (worker) (chronic exposition / systemic effects)         Oral       DNEL         699 mg/kg bw/day (worker) (chronic exposition / systemic effects)         773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
Ingredients with limit values that require monitoring at the workplace:         CAS: 110-82-7 cyclohexane         WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-hexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         Oral       DNEL         Oral       DNEL         Bunez       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dermal       DNEL         699 mg/kg bw/day (worker) (chronic exposition / systemic effects)         773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
CAS: 110-82-7 cyclohexane         WEL (Great Britain)         Short-term value: 1050 mg/m³, 300 ppm         Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-hexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs         Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dermal       DNEL       699 mg/kg bw/day (worker) (chronic exposition / systemi effects)			
WEL (Great Britain)       Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-bexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs       Long-term value: 72 mg/m³, 20 ppm         Oral       DNEL         Oral       DNEL         Bit       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Ormal       DNEL         699 mg/kg bw/day (worker) (chronic exposition / systemic effects)         773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
IOELV (EU)       Long-term value: 350 mg/m³, 100 ppm         IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-bexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs         Hydrocarbors, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	-		
IOELV (EU)       Long-term value: 700 mg/m³, 200 ppm         CAS: 110-54-3 n-bexane         WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs         Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
CAS: 110-54-3 n-hexane         WEL (Great Britain)         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs         DNELs         Oral         DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dermal       DNEL         699 mg/kg bw/day (worker) (chronic exposition / systemic effects)         773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
WEL (Great Britain)       Long-term value: 72 mg/m³, 20 ppm         IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs         Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
IOELV (EU)       Long-term value: 72 mg/m³, 20 ppm         DNELs       Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dermal       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)         773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
DNELs         Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane			
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane         Oral       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)         Dermal       DNEL       699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)         773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
OralDNEL699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)DermalDNEL699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
Dermal DNEL 699 mg/kg bw/day (consumer) (chronic exposition / systemi effects) 773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
773 mg/kg bw/day (worker) (chronic exposition / systemic effects)			
Inhalative DNEL 608 mg/m <sup>3</sup> (consumer) (chronic exposition / systemic effects)			
2035 mg/m <sup>3</sup> (worker) (chronic exposition / systemic effects)			
Additional information: The lists valid during the making were used as basis.			
8.2 Exposure controls Suitable technical control devices			

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Personal protective equipment:

**General protective and hygienic measures:** The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: If the occupational exposure limit is exceeded: The following breathing protection is recommended: Respiratory filter for organic gases and vapours (Type A) Filter A/P2 Identification colour: Brown [DIN EN 14387] Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Material of gloves Nitrile rubber, NBR Fluorocarbon rubber (Viton) Recommended thickness of the material: ≥ 0.4 mm [EN 374]

(Contd. on page 5)

GB



Printing date 29.10.2020

Version: 4.00

Revision: 10.10.2017

(Contd. of page 4)

Trade name: SONAX Professional Brake & Parts cleaner

<b>Penetration time of glove material</b> Value for the permeation: Level 6 (>480min)	
Eye protection:	
Safety glasses	
[EN 166]	

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and c	homical proportios
General Information	nemical properties
Appearance:	
Form:	Fluid
Colour:	Colourless
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/freezing point:	< -40 °C
Initial boiling point and boiling range:	: 78 - 113 °C
Flash point:	< -18 °C
Flammability (solid, gas):	Not applicable.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Not determined.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Explosion limits:	
Lower:	0.8 Vol %
Upper:	7.7 Vol %
Vapour pressure at 20 °C:	61 hPa
Density at 20 °C:	0.71 - 0.73 g/cm <sup>3</sup>
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Flow time	Not determined.
Dynamic:	Not determined.
Kinematic at 40 °C:	0.49 mm²/s
9.2 Other information	No further relevant information available.

# SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Forms explosive gas mixture with air.
- 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 6)

GB

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Brake & Parts cleaner

(Contd.	of page 5)
---------	------------

		oxicological information n toxicological effects There are no toxicological findings on this mixture.
		ed on available data, the classification criteria are not met.
LD/LC50	values rel	levant for classification:
Hydrocar	bons, C6-	C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
Oral	LD50	>5840 mg/kg (rat) (OECD 401)
Dermal	LD50	>2920 mg/kg (rat) (OECD 402)
Inhalative	LC50/4h	25.2 mg/l (rat) (OECD 403)
CAS: 110	-82-7 cycl	ohexane
Oral	LD50	12000 mg/kg (rat)
Dermal	LD50	>18000 mg/kg (rabbit)
CAS: 110	-54-3 n-he	exane
Oral	LD50	5000 mg/kg (mouse)
Dermal	LD50	>2000 mg/kg (rabbit)
Inhalative	LC50/4h	172 mg/l (rat)
Primary in	rritant effe	ect:
<b>Skin corr</b> Causes sk		
		ge/irritation available data, the classification criteria are not complied with (Conventional Method).
		a sensitisation available data, the classification criteria are not complied with (Conventional Method).
Germ cell Carcinog	<i>mutagen</i> enicity Ba	nogenity, mutagenicity and toxicity for reproduction) Contains n-hexane! icity Based on available data, the classification criteria are not met. ised on available data, the classification criteria are not met. ity Based on available data, the classification criteria are not met.
STOT-sin May cause		s <b>ure</b> ess or dizziness.
STOT-rep	eated exp	<b>posure</b> Based on available data, the classification criteria are not met.
<b>Aspiration</b> Viscosity: May be fai	< 20,5mm	r²∕s (40°C) owed and enters airways.

# SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

EL50 / 48h	3 mg/l (Daphnia magna) (OECD 202)	
EL50 / 72h	30-100 mg/l (Pseudokirchneriella subcapitata)	
LL50 / 96h	11.4 mg/l (Oncorhynchus mykiss) (OECD 203)	
LOEC	0.32 mg/l (Daphnia magna)	
NOEC / 21d	0.17 mg/l (Daphnia magna)	
NOELR 72 h	3 mg/l (Pseudokirchneriella subcapitata)	
12.2 Persiste	ence and degradability	
Hydrocarbo	ns, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Biodegradiati	on 81 % (28d)	

Printing date 29.10.2020

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 29.10.2020

SONAX<sup>®</sup>

Version: 4.00

Revision: 10.10.2017

(Contd. of page 6)

Trade name: SONAX Professional Brake & Parts cleaner

12.3 Bioaccumulative potential

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

log POW 3.4 - 5.2 log POW

CAS: 110-54-3 n-hexane

log POW 3.9 log POW

12.4 Mobility in soil Highly volatile, will partition rapidly to air.

Additional ecological information:

General notes: The product may not be released into the environment without control.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

13.1 Waste treatment methods
Waste classified as hazardous according to Annex III to Directive 2008/98/EC.
Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Waste must be disposed of while observing the local, official regulations.
European waste catalogue
1) Disposal / product
2) Disposal / contaminated packaging
20 01 13\* solvents

15 01 10\* packaging containing residues of or contaminated by dangerous substances

14.1 UN-Number ADR, IMDG, IATA	UN3295
14.2 UN proper shipping name	
ADR	3295 HYDROCARBONS, LIQUID, N.O.S., ENVIRONMENTALLY HAZARDOUS
IMDG	HYDROCARBONS, LIQUID, N.O.S. (HEPTANE AND ISOMERS), MARINE POLLUTANT
ΙΑΤΑ	HYDROCARBONS, LIQUID, N.O.S.
14.3 Transport hazard class(es)	
ADR	
Class	3 Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	



Printing date 29.10.2020

Version: 4.00

Revision: 10.10.2017

Trade name: SONAX Professional Brake & Parts cleaner

	(Contd. of page
14.5 Environmental hazards:	
Marine pollutant:	Yes
Special marking (ADR):	absent due to package size =<5l >5l: Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
14.7 Transport in bulk according to Ann Marpol and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D/E
UN "Model Regulation":	UN3295, HYDROCARBONS, LIQUID, N.O.S., 3, II

# SECTION 15: Regulatory information

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane: CAS 64742-49-0 **European Directives:** EC/1907/2006 (REACh) EC/1272/2008 (CLP) EC/648/2004

### National regulations:

### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

### Classification according to Regulation (EC) No 1272/2008

On basis of test data
The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)



Printing date 29.10.2020

Version: 4.00

Revision: 10.10.2017

### Trade name: SONAX Professional Brake & Parts cleaner

(Contd. of page 8) NOEL = No Observed Effect Level NOEC = No Observed Effect Concentration LC = letal Concentration EC50 = half maximal effective concentration log POW = Octanol / water partition coefficient GHS: Globally Harmonized System of Classification and Labelling of Chemicals ATE: acute toxicity estimate ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent IOELV = indicative occupational exposure limit values Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 \* Data compared to the previous version altered. GB