

## SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)



### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : C3 CHAIN LUBE OFF ROAD

Product code : 23201

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

4-stroke engine lubricant

#### 1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL

Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE

Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .

Email : motul\_hse@motul.fr

#### 1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA

#### Other emergency numbers

UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 601 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336

Ireland : +353 1 8092566

24 hours a day, 7 days a week

### SECTION 2 : HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 1 (Aerosol 1, H222 - H229).

Repeated exposure may cause skin dryness or cracking (EUH066).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

#### 2.2. Label elements

Mixture for aerosol application.

##### In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07



GHS08

Signal Word :

DANGER

Product identifiers :

EC 203-692-4

PENTANE

Hazard statements :

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

H304

May be fatal if swallowed and enters airways.

H336

May cause drowsiness or dizziness.

H412

Harmful to aquatic life with long lasting effects.

EUH066

Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

If medical advice is needed, have product container or label at hand.

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P101

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

Precautionary statements - Response :

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...

P331 Do NOT induce vomiting.

Precautionary statements - Storage :

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements - Disposal :

P501 Dispose of contents / container according to prefectural ordinances.



### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances  $\geq 0.1\%$  with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures



#### Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 106-97-8 EC: 203-448-7 REACH: 01-2119474691-32  BUTANE	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	25 $\leq$ x % < 50
CAS: 109-66-0 EC: 203-692-4 REACH: 01-2119459286-30  PENTANE	GHS09, GHS07, GHS08, GHS02 Dgr Flam. Liq. 1, H224 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411 EUH:066	[1]	10 $\leq$ x % < 25
EC: 927-241-2 REACH: 01-2119471843-32  HYDROCARBONS C9-C10, N-ALKANES, ISO ALKANES, CYCLICS<2% AROMATICS	GHS07, GHS08, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH:066		10 $\leq$ x % < 25
CAS: 74-98-6 EC: 200-827-9 REACH: 01-2119486944-21  PROPANE	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	2.5 $\leq$ x % < 10
CAS: 75-28-5 EC: 200-857-2 REACH: 01-2119485395-27  BUTANE	GHS02 Dgr Flam. Gas 1, H220 Press. Gas, H280	[1] [7]	1 $\leq$ x % < 2.5



#### Information on ingredients :

(Full text of H-phrases: see section 16)

[7] Propellant gas

[1] Substance for which maximum workplace exposure limits are available.

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.



#### 4.1. description of first aid measures

##### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

Remove the victim to fresh air. If the symptoms persist, call a physician.



##### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Wash immediately and abundantly with water, including under the eyelids.



##### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

##### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

#### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.



##### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Dry agent, foam, carbon dioxide.



##### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

High volume water jet

#### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

Do not swallow

Do not get in eyes, on skin, or on clothing.

#### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Never inhale this mixture.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

No smoking.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Ensure good ventilation at the workplace

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

Do not breathe fumes, vapour, spray.

## 7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.

Only use hydrocarbon-resistant containers, joints and pipes.

### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

### Packaging

Always keep in packaging made of an identical material to the original.

## 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits :

- European Union (2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m3 :	VME-ppm :	VLE-mg/m3 :	VLE-ppm :	Notes :
109-66-0	3000	1000	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	1000 ppm				
109-66-0	600 ppm				
74-98-6	1000 ppm				
75-28-5	1000 ppm				

- Germany - AGW (BAuA - TRGS 900, 08/08/2019) :

CAS	VME :	VME :	Excess	Notes
106-97-8		1000 ppm 2400 mg/m <sup>3</sup>		4(II)
109-66-0		1000 ppm 3000 mg/m <sup>3</sup>		2(II)
74-98-6		1000 ppm 1800 mg/m <sup>3</sup>		4(II)
75-28-5		1000 ppm 2400 mg/m <sup>3</sup>		4(II)

- France (INRS - ED984 / 2020-1546) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
106-97-8	800	1900	-	-	-	-
109-66-0	1000	3000	-	-	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
106-97-8	600 ppm 1450 mg/m <sup>3</sup>	750 ppm 1810 mg/m <sup>3</sup>		Carc	
109-66-0	600 ppm 1800 mg/m <sup>3</sup>				

### 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.

Personnel shall wear regularly laundered overalls.

#### Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

**- Eye / face protection**

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

**- Hand protection**

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Glove thickness:	0.38 mm
Break-through time:	> 480 mn

Recommended properties :

- Impervious gloves in accordance with standard EN ISO 374-2 (Type A)

**- Body protection**

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605/A1 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034/A1 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

**- Respiratory protection**

Avoid inhaling vapors.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Type of FFP mask :

Wear a disposable half-mask aerosol filter in accordance with standard EN149/A1.

Category :

- FFP1

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

Particle filter according to standard EN143 :

- P1 (White)

Breathing apparatus only when aerosol or spray are formed.

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties****Physical state**

Physical state :	Fluid liquid.
------------------	---------------

**Colour**

Unspecified

**Odour**

Odour threshold :	Not stated.
-------------------	-------------

**Melting point**

Melting point/melting range :	Not relevant.
-------------------------------	---------------

**Freezing point**

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------

**Boiling point or initial boiling point and boiling range**

Boiling point/boiling range :	Not relevant.
-------------------------------	---------------

**Flammability**

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------

**Lower and upper explosion limit**

Explosive properties, lower explosivity limit (%) :	Not stated.
---	-------------

Explosive properties, upper explosivity limit (%) :	Not stated.
---	-------------

**Flash point**

Flash point interval :	Not relevant.
------------------------	---------------

**Auto-ignition temperature**

Self-ignition temperature :	Not relevant.
-----------------------------	---------------

**Decomposition temperature**

Decomposition point/decomposition range :	Not relevant.
---	---------------

**pH**

pH (aqueous solution) :	Not stated.
-------------------------	-------------

pH :	Not relevant.
------	---------------

**Kinematic viscosity**

Viscosity :	Not stated.
-------------	-------------

**Solubility**

Water solubility :	Insoluble.
--------------------	------------

Fat solubility :	Not stated.
------------------	-------------

**Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water :	Not stated.
--	-------------

**Vapour pressure**

Vapour pressure (50°C) :	Not relevant.
--------------------------	---------------

**Density and/or relative density**

Density :	< 1
-----------	-----

**Relative vapour density**

Vapour density :	Not stated.
------------------	-------------

**9.2. Other information**

No data available.

**9.2.1. Information with regard to physical hazard classes**

No data available.

**Aerosols**

Chemical combustion heat :	>= 30 kJ/g.
----------------------------	-------------

**9.2.2. Other safety characteristics**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY****10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

**10.5. Incompatible materials**

Strong oxidants

Acids

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

## SECTION 11 : TOXICOLOGICAL INFORMATION



### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness. Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

#### 11.1.1. Substances

No toxicological data available for the substances.

#### 11.1.2. Mixture



##### Skin corrosion/skin irritation :

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.



##### Serious damage to eyes/eye irritation :

Mild eye irritation



##### Aspiration hazard :

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

May cause lung damage if swallowed



### 11.2. Information on other hazards

## SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

### 12.1. Toxicity

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

### 12.5. Results of PBT and vPvB assessment

No data available.



### 12.6. Endocrine disrupting properties

No data available.



### 12.7. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.

## SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

### 13.1. Waste treatment methods

Do not pour into drains or waterways.

#### Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.



Give to a certified disposal contractor.

## SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 - ICAO/IATA 2021).

### 14.1. UN number or ID number

1950

### 14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

### 14.3. Transport hazard class(es)

- Classification :



2.1

### 14.4. Packing group

-

### 14.5. Environmental hazards

-

### 14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D
IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation	
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69	
IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ	
	2.1	-	-	Forbidden	Forbidden	203	150 kg	A1 A145 A167 A802	E0	
	2.1	-	-	Forbidden	Forbidden	-	-	A1 A145 A167 A802	E0	

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2020/217 (ATP 14)

#### - Container information:

No data available.

#### - Particular provisions :

No data available.

### 15.2. Chemical safety assessment

No data available.

## SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.



**Abbreviations :**

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.