# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)



#### SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name : FORK OIL FL MED 7,5W Product code : 31800

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Fluid for fork

# 1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE Telephone: 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: . Email : motul\_hse@motul.fr

## 1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : ORFILA.

#### Other emergency numbers

UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 601 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336 SEGTIONS 23:18 AZARDS IDENTIFICATION

24 hours a day, 7 days a week

# 2.1. Classification of the substance or mixture

# In compliance with EC regulation No. 1272/2008 and its amendments.

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

# 2.2. Label elements

#### In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling :

Hazard	statements	:
H412		

Harmful to aquatic life with long lasting effects. Precautionary statements - General :

P101

If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children.

Precautionary statements - Prevention :

P273 Avoid release to the environment.

Precautionary statements - Disposal :

Dispose of contents / container in accordance with local / regional / national /

international regulations

## 2.3. Other hazards

P501

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) >= 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006. The mixture does not contain substances> = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

#### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

## 3.2. Mixtures

#### **Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 72623-87-1		L	50 <= x % < 100
EC: 276-738-4			
REACH: 01-2119474889-13			

EC: 276-738-4 REACH: 01-2119474889-13 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL DIL-BASED CAS: 64742-54-7 EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 Dgr	L 25 <= x % < 50 L 25 <= x % < 10 C 2.5 <= x % < 10 C <= x % < 1
CAS: 72623-87-1       GHS08         EC: 276-738-4       Dgr         REACH: 01-2119474889-13       Asp. Tox. 1, H304         LUBRICATING OILS (PETROLEUM),       C20-50, HYDROTREATED NEUTRAL         OIL-BASED       CAS: 64742-54-7         EC: 265-157-1       REACH: 01-2119484627-25         DISTILLATES (PETROLEUM),       GHS07, GHS05, GHS09, GHS08         CAS: 112-90-3       GHS07, GHS05, GHS09, GHS08         EC: 204-015-5       Dgr	L 2.5 <= x % < 10
EC: 276-738-4 REACH: 01-2119474889-13 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED CAS: 64742-54-7 EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 Dgr	L 2.5 <= x % < 10
REACH: 01-2119474889-13 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL DIL-BASED CAS: 64742-54-7 EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 Dgr	
LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL DIL-BASED CAS: 64742-54-7 EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 Dgr	
C20-50, HYDROTREATED NEUTRAL DIL-BASED CAS: 64742-54-7 EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 GHS05, GHS09, GHS08 Dgr	
REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 Dgr	
EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 GHS05, GHS09, GHS08 Dgr	
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 EC: 204-015-5 Dgr	3 0 <= x % < 1
HYDROTREATED HEAVY PARAFFINIC CAS: 112-90-3 GHS07, GHS05, GHS09, GHS08 EC: 204-015-5 Dgr	3 0 <= x % < 1
EC: 204-015-5 Dgr	3 0 <= x % < 1
EC: 204-015-5 Dgr	
5	
26 0 6 0 7 10/72707 10 10 10 10 10 10 10 10 10 10 10 10 10	
REACH: 01-2119473797-19 Acute Tox. 4, H302	
Asp. Tox. 1, H304	
Z)-OCTADEC-9-ENYLAMINE Skin Corr. 1B, H314	
STOT SE 3, H335	
STOT RE 2, H373	
Aquatic Acute 1, H400	
M Acute = 10	
Aquatic Chronic 1, H410	
M Chronic = 10	
CAS: 128-39-2 GHS07, GHS09	0 <= x % < 1
EC: 204-884-0 Wng	
REACH: 01-2119490822-33 Skin Irrit. 2, H315	
Aquatic Acute 1, H400	
2,6-DI-TERT-BUTYLPHENOL M Acute = 1	
Aquatic Chronic 1, H410	
M Chronic = 1	
CAS: 34140-91-5 GHS07, GHS09, GHS08	0 <= x % < 1
EC: 251-846-4 Wng	
REACH: 01-2119974119-29-0000 Skin Irrit. 2, H315	
Exel Internet 2110374113-22-0000 Eye Irrit. 2, H319	
OLEIC ACID, COMPOUND WITH STOT RE 2, H373	
(Z)-N-OCTADEC-9-ENYLPROPANE-1,3 Aquatic Chronic 2, H411	
-DIAMINE Aquatic Acute 1, H400	
M Acute = 10	
ecific concentration limits:	
dentification Specific concentration limits	ATE
CAS: 72623-87-1	inhalation: ATE = 5.53 mg/l 4h
EC: 276-738-4	(dust/mist)
	(uusi/mst)
REACH: 01-2119474889-13	
LUBRICATING OILS (PETROLEUM),	
C20-50, HYDROTREATED NEUTRAL	
OIL-BASED	

Note L: The carcinogen classification does not apply because the substance contains less than 3 % w/w of dimethyl sulphoxide (DMSO) measured using the IP 346 method.

# **SECTION 4 : FIRST AID MEASURES**

2

7

As a general rule, in case of doubt or if symptoms persist, always call a doctor. NEVER induce swallowing by an unconscious person.

# 4.1. description of first aid measures

## In the event of exposure by inhalation :

Remove the victim to fresh air. If the symptoms persist, call a physician.

### In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

# In the event of splashes or contact with skin :

#### Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

# In the event of swallowing :

Seek medical attention, showing the label.

## 4.2. Most important symptoms and effects, both acute and delayed

No data available.

# 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

# **SECTION 5 : FIREFIGHTING MEASURES**

#### Non-flammable.

### 5.1. Extinguishing media

#### Suitable methods of extinction

Dry agent, foam, carbon dioxide.

Unsuitable methods of extinction

#### High volume water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)

- carbon dioxide (CO2)

# 5.3. Advice for firefighters

No data available.

# **SECTION 6 : ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

#### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

# 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

## 6.4. Reference to other sections

No data available.

# SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

# 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

#### Do not swallow

Do not get in eyes, on skin, or on clothing.

# Fire prevention :

Prevent access by unauthorised personnel.

Take precautionary measures against static discharges by bonding and grounding equipment.

SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH)
FORK OIL FL MED 7,5W - 31800

## No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Ensure good ventilation at the workplace

# Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Do not breathe fumes, vapour, spray.

# 7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.

Only use hydrocarbon-resistant containers, joints and pipes.

# Storage

Keep out of reach of children.

# Packaging

Always keep in packaging made of an identical material to the original.

# 7.3. Specific end use(s)

No data available.

Inhalation.

19.6 mg of substance/m3

Version 10.1 (19-08-2022) - Page 4/11

# SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters No data available.

#### Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2) Final use: Exposure method: Fotential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

#### Final use:

Exposure method: Potential health effects: DNEL :

Exposure method: Potential health effects: DNEL :

# Final use: Exposure method:

Potential health effects: DNEL :

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3) Final use: Exposure method: Potential health effects: DMEL :

Final use: Exposure method: Potential health effects: DNEL :

Final use: Exposure method: Potential health effects:

#### Workers.

Dermal contact. Long term systemic effects. 2.77 mg/kg body weight/day

Inhalation. Long term systemic effects. 19.6 mg of substance/m3

# Consumers.

Dermal contact. Long term systemic effects. 2.77 mg/kg body weight/day

## Long term systemic effects.

#### Man exposed via the environment.

Inhalation. Long term systemic effects. 5.8 mg of substance/m3

#### Workers.

Inhalation. Long term local effects. 0.38 mg of substance/m3

# LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1) Workers. Inhalation. Long term local effects. 5.4 mg of substance/m3

Consumers. Inhalation. Long term local effects.

ETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) K OIL FL MED 7,5W - 31800		Version 10.1 (19-08-2022) - Pag
DNEL :	1.2 mg of substance/m3	
edicted no effect concentration (PNEC):		
2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2	2)	
Environmental compartment:	Soil.	
PNEC :	38.9 µg/kg	
Environmental compartment:	Fresh water.	
PNEC :	0.45 µg/l	
Environmental compartment:	Sea water.	
PNEC :	0.045 µg/l	
Environmental compartment:	Intermittent waste water.	
PNEC :	4.5 µg/l	
Environmental compartment:	Fresh water sediment.	
PNEC :	0.196 mg/kg	
Environmental compartment:	Marine sediment.	
PNEC :	0.0196 mg/kg	
Environmental compartment:	Waste water treatment plant.	
PNEC :	10 mg/l	
(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3	3)	
Environmental compartment:	Soil.	
PNEC :	10 mg/kg	
Environmental compartment:	Fresh water.	
PNEC :	0.00026 mg/l	
Environmental compartment:	Sea water.	
PNEC :	0.00026 mg/l	
Environmental compartment:	Intermittent waste water.	
PNEC :	0.55 mg/l	
Environmental compartment:	Fresh water sediment.	
PNEC :	0.1794 mg/kg	
Environmental compartment:	Marine sediment.	
PNEC :	0.01794 mg/kg	

# 8.2. Exposure controls

#### Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction. Personnel shall wear regularly laundered overalls.

# Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained. Store personal protective equipment in a clean place, away from the work area. Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

# - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

# - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1. Gloves must be selected according to the application and duration of use at the workstation. Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

# SAFETY DATA SHEET (REGULATION (EC) n° 1907/2006 - REACH) FORK OIL FL MED 7,5W - 31800

Type of gloves recommended :			
Glove	0.38 mm		
thickness:			
Break-through	> 480 mn		
time:			

# - Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

# - Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

# **SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

of the mornation on basic physical and one moal properties	
Physical state	
Physical state :	Fluid liquid.
Colour	
Color:	Amber
Odour	
Odour threshold :	Not stated.
Melting point	
Melting point/melting range :	Not relevant.
Freezing point	
Freezing point / Freezing range :	Not stated.
Boiling point or initial boiling point and boiling range	
Boiling point/boiling range :	Not relevant.
Flammability	
Flammability (solid, gas) :	Not stated.
Lower and upper explosion limit	
Explosive properties, lower explosivity limit (%):	Not stated.
Explosive properties, upper explosivity limit (%):	Not stated.
Flash point	
Flash Point Interval :	FP > 100°C.
Auto-ignition temperature	
Self-ignition temperature :	Not relevant.
Decomposition temperature	
Decomposition point/decomposition range :	Not relevant.
pH	
pH (aqueous solution) :	Not stated.
pH:	Not relevant.
Kinematic viscosity	
Viscosity :	24,6 mm²/s à 40°C
Solubility	
Water solubility :	Insoluble.
Fat solubility :	Not stated.
Partition coefficient n-octanol/water (log value)	
Partition coefficient: n-octanol/water :	Not stated.
Vapour pressure	
Vapour pressure (50°C) :	Not relevant.
Density and/or relative density	
Density :	<1
Relative vapour density	I
Vapour density :	Not stated.
9.2. Other information	
No data available.	
9.2.1. Information with regard to physical hazard classes	
No data available.	

 $\sim$ 9.2.2. Other safety characteristics No data available.

# SECTION 10 : STABILITY AND REACTIVITY

# 10.1. Reactivity

No data available.

# 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

# 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

#### 10.5. Incompatible materials

Strong oxidants

Acids

# 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

1.1. Information on hazard classes as defin No data available. 1.1.1. Substances	ed in Regulation (EC) No 1272/2008	
Acute toxicity :		
OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)		
Oral route :	LD50 >= 2000 mg/kg Species : Rat OCDE Ligne directrice 423 (Toxicité aiguë par voie orale - Méthode classe de toxicité aiguë)	
Dermal route :	LD50 > 2000 mg/kg Species : Rat OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)	
2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39	D-2)	
Oral route :	LD50 > 5000 mg/kg Species : Rat	
Dermal route :	LD50 > 5000 mg/kg Species : Rabbit	
(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90	0-3)	
Oral route :	300 < LD50 <= 2000 mg/kg Species : Rat	
LUBRICATING OILS (PETROLEUM), C20-5 Oral route :	50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1) LD50 > 5000 mg/kg Species : Rat OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)	
Dermal route :	2,000 < LD50 <= 5000 mg/kg Species : Rabbit OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)	
Inhalation route (Dusts/mist) :	LC50 = 5.53 mg/l Species : Rat OCDE Ligne directrice 403 (Toxicité aiguë par inhalation) Duration of exposure : 4 h	

#### 11.1.2. Mixture

## Skin corrosion/skin irritation :

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

#### Serious damage to eyes/eye irritation :

Mild eye irritation

# Aspiration hazard :

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

May cause lung damage if swallowed

# 11.2. Information on other hazards

# Monograph(s) from the IARC (International Agency for Research on Cancer) :

CAS 140-88-5 : IARC Group 2B : The agent is possibly carcinogenic to humans.

### **SECTION 12 : ECOLOGICAL INFORMATION**

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

# 12.1. Toxicity

# 1

12.1. LOXICITY	
12.1.1. Substances	
(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)	
Fish toxicity :	0.01 < LC50 <= 0.1 mg/l
	Factor M = 10
	Species : Pimephales promelas
	OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	0.01 < EC50 <= 0.1 mg/l
	Factor M = 10
	Species : Daphnia magna
	OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)
Algae toxicity :	0.01 < ECr50 <= 0.1 mg/l
	Factor M = 10
	Species : Desmodesmus subspicatus
OLEIC ACID, COMPOUND WITH (Z)-N-OCTAD	EC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)
Fish toxicity :	LC50 = 0.13 mg/l
	Factor M = 10
	Species : Danio rerio
	Duration of exposure : 96 h
	OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	EC50 = 0.14 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h
Algae toxicity :	ECr50 = 0.041 mg/l
	Species : Pseudokirchnerella subcapitata
	Duration of exposure : 72 h
	OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)
2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)	
Fish toxicity :	LC50 >= 1.4 mg/l
	Duration of exposure : 96 h
	NOEC = 0.43 mg/l
	Duration of exposure : 14 jours
Crustacean toxicity :	EC50 = 0.45 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h

F	ORK OIL FL MED 7,5W - 31800		
	Algae toxicity :	ECr50 = 1.2 mg/l Duration of exposure : 72 h	
	LUBRICATING OILS (PETROLEUM), C20-50, H	YDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)	
	Fish toxicity :	LC50 > 100 mg/l	
		Duration of exposure : 96 h OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)	
	Crustacean toxicity :	EC50 > 10000 mg/l	
		Duration of exposure : 48 h	
		OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)	
		NOEC = 10 mg/l	
		Duration of exposure : 21 jours	
		OCDE Ligne directrice 211 (Daphnia magna, essai de reproduction)	
	Algae toxicity :	ECr50 >= 100 mg/l	
		Duration of exposure : 72 h OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)	
	12.1.2. Mixtures		
Fi	ish toxicity :	Harmful. 10 < LC50 <= 100 mg/l	
	12.2. Persistence and degradability	10 < EC30 <= 100 mg/i	
	12.2.1. Substances		
	OLEIC ACID, COMPOUND WITH (Z)-N-OCTADE	EC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)	
	Biodegradability :	Rapidly degradable.	
	2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)		
	Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.	
	(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)		
	Biodegradability :	Rapidly degradable.	
	DISTILLATES (PETROLEUM), HYDROTREATEI	D HEAVY PARAFFINIC (CAS: 64742-54-7)	
	Biodegradability :	no degradability data is available, the substance is considered as not degrading quickly.	
		YDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)	
	Biodegradability :	Non-rapidly degradable.	
	12.2.2. Mixtures		
в	iodegradation :	No data on decomposition is available, the mixture is not considered to decompose rapidly.	
	12.3. Bioaccumulative potential		
	12.3.1. Substances		
	(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3) Bioaccumulation :	BCF >= 500.	
	12.4. Mobility in soil		
	Not very mobile in soil.		
	The product is insoluble in water and will spread on the surface		
	12.5. Results of PBT and vPvB assessment		
	No data available. 12.6. Endocrine disrupting properties		
	No data available.		
	12.7. Other adverse effects		

## German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 3 : Extremely hazardous for water.

#### **SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

# 13.1. Waste treatment methods

Do not pour into drains or waterways.

# Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

#### Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

#### **SECTION 14 : TRANSPORT INFORMATION**

Exempt from transport classification and labelling.

- 14.1. UN number or ID number
  - 14.2. UN proper shipping name
  - -
  - 14.3. Transport hazard class(es)
  - 14.4. Packing group
  - \_
  - 14.5. Environmental hazards
  - -

\_

- 14.6. Special precautions for user
- -
- 14.7. Maritime transport in bulk according to IMO instruments

#### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### - Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

#### - Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): https://echa.europa.eu/substances-restricted-under-reach.

#### - Particular provisions :

No data available.

## - German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 3 : Extremely hazardous for water.

#### 15.2. Chemical safety assessment

No data available.

### **SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions. It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations. The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

# Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.	
H304	304 May be fatal if swallowed and enters airways.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H319 Causes serious eye irritation.		
H335	H335 May cause respiratory irritation.	
H373	H373 May cause damage to organs through prolonged or repeated exposure .	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
H411	Toxic to aquatic life with long lasting effects.	

# Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

ATE : Acute Toxicity Estimate

DNEL : Derived No-Effect Level

DMEL : Derived Minimal Effect Level

PNEC : Predicted No-Effect Concentration

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefahrdungsklasse (Water Hazard Class).

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.