



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

RAVENOL HCS SAE 5W-40

Article No.:

1112105

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Lubricant

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

Ravensberger Schmierstoffvertrieb GmbH

Produktsicherheit

Jöllenbecker Str. 2

33824 Werther

Germany

Telephone: +49 5203 9719 0

Telefax: +49 5203 9719 40

E-mail: kontakt@ravenol.de

Website: www.ravenol.de

E-mail (competent person): sdb@ravenol.de

1.4. Emergency telephone number

24 hr. emergency phone number, 24h: +49 700 24 112 112 (Contract ID: RAV) / +1 872 5888271
(Contract ID: RAV)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

* 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

According to EC directives or the corresponding national regulations the product does not have to be labelled.

Hazard statements: none

Supplemental hazard information

EUH208	Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Precautionary statements: none

2.3. Other hazards

Other adverse effects:

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

SECTION 3: Composition/information on ingredients

* 3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64742-54-7 EC No.: 265-157-1 REACH No.: 01-2119484627-25	Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified Asp. Tox. 1 (H304) Danger	15 - < 35 weight-%
CAS No.: 101316-72-7 EC No.: 309-877-7 REACH No.: 01-2119489969-06	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated The substance is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].	5 - < 15 weight-%
CAS No.: 68649-42-3 EC No.: 272-028-3	Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts Aquatic Acute 1 (H400), Aquatic Chronic 3 (H412), Eye Irrit. 2 (H319) Warning	0 - < 1 weight-%
CAS No.: 68584-23-6 EC No.: 271-529-4 REACH No.: 01-2119492627-25	Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts Skin Sens. 1B (H317) Warning	0 - < 0.2 weight-%
CAS No.: 61789-86-4 EC No.: 263-093-9 REACH No.: 01-2119488992-18	Sulfonic acids, petroleum, calcium salts Aquatic Chronic 4 (H413), Skin Sens. 1B (H317) Warning	0 - < 0.09 weight-%
CAS No.: 64742-47-8 EC No.: 920-107-4 Index No.: 649-422-00-2 REACH No.: 01-2119453414-43-0000	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics Asp. Tox. 1 (H304) Danger	0 - < 0.05 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. Consult a doctor immediately.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Consult a doctor immediately.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Following ingestion:

Rinse mouth thoroughly with water. Do NOT induce vomiting. Consult a doctor immediately.

Self-protection of the first aider:

Use personal protection equipment. No direct artificial respiration to be given by first aider.

* 4.2. Most important symptoms and effects, both acute and delayed

Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts. May produce an allergic reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Observe risk of aspiration if vomiting occurs.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Co-ordinate fire-fighting measures to the fire surroundings.
Carbon dioxide (CO2)



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Extinguishing powder
alcohol resistant foam
Use water spray jet to protect personnel and to cool endangered containers.

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

During heating or in case of fire, toxic gases is possible.
The formation of combustible vapours is possible at temperatures above: Flash point

Hazardous combustion products:

Carbon monoxide, Carbon dioxide (CO₂), Nitrogen oxides (NO_x),
During heating or in case of fire, toxic gases is possible.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

5.4. Additional information

Do not inhale explosion and combustion gases. Move undamaged containers from immediate hazard area if it can be done safely. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Use personal protection equipment. Special danger of slipping by leaking/spilling product.

Protective equipment:

Personal protection equipment: see section 8

Emergency procedures:

Eliminate all ignition sources if safe to do so. Remove persons to safety. Provide adequate ventilation.

6.1.2. For emergency responders

Personal protection equipment:

Use personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3. Methods and material for containment and cleaning up

For containment:

Suitable material for taking up: Sand, Kieselguhr, Universal binder, Chemical binding agents, containing acids

Prevent spread over a wide area (e.g. by containment or oil barriers).

For cleaning up:

Remove from the water surface (e.g. skimming, sucking). Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

Other information:

Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

6.5. Additional information

Clear spills immediately. Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Personal protection equipment: see section 8.



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

When using do not eat, drink, smoke, sniff. Wash hands before breaks and after work. Do not put any product-impregnated cleaning rags into your trouser pockets. Clear spills immediately. Use appropriate container to avoid environmental contamination.

Fire prevent measures:

No special fire protection measures are necessary.

Environmental precautions:

Shafts and sewers must be protected from entry of the product.

Advices on general occupational hygiene

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Suitable container/equipment material: Floors should be impervious, resistant to liquids and easy to clean. Shafts and sewers must be protected from entry of the product.

Keep/Store only in original container.

Hints on storage assembly:

not required

Storage class (TRGS 510, Germany): 10 - Combustible liquids that cannot be assigned to any of the above storage classes

Further information on storage conditions:

Store in a cool dry place. Keep away from heat.

7.3. Specific end use(s)

Recommendation:

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

* **8.1. Control parameters**

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
PL from 12 Jun 2018	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Mgła olejowa mineralny)
MAK (AT)	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Ölnebel, mineralisch (einatembare Fraktion))
BE	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Brouillard d'huile minéral)
Québec (CA)	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ② 10 mg/m ³ ⑤ (Oil mist mineral)
HU from 28 May 2022	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Olajköd ásványi) T



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
SE	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 1 mg/m ³ ② 3 mg/m ³ ⑤ (Oljeånga eller rök)
ES	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ② 10 mg/m ³ ⑤ (Niebla de aceite mineral) am
NL	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Olienevel mineraal)
OSHA (US)	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Oil mist mineral)
NIOSH (US)	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ② 10 mg/m ³ ⑤ (Oil mist mineral)
ACGIH (US) from 1 Jan 2010	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Oil mist mineral, inhalable fraction)
CZ	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ② 10 mg/m ³ ⑤ (Rozprášený olej (olejová mlhovina) minerální)
NO	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 1 mg/m ³ ⑤ (Oljetåke mineralsk)
NPEL (SK) from 23 Nov 2011	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 ppm (1 mg/m ³) ② 15 ppm (3 mg/m ³) ⑤ (Olejová hmlovina minerálny)
Alberta (CA)	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ② 10 mg/m ³ ⑤ (Oil mist mineral)
HTP (FI)	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Oljeånga)
LT	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 1 mg/m ³ ② 3 mg/m ³ ⑤ (Tepalo rūkas arba dūmai)



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
BC (CA) from 1 Jan 2007	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 0.2 mg/m ³ ⑤ (Oil mist mineral) 1
MY from 1 Jan 2000	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Kabus minyak mineral)
BC (CA) from 1 Jan 2007	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 1 mg/m ³ ⑤ (Oil mist mineral, severely refined)
TW	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (## ##)
GR from 1 Oct 2016	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Εκκνέφωμα λαδιού, ορυκτό)
MY from 1 Jan 2000	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 10 mg/m ³ ⑤ (Kabus minyak, vegetal)
RO from 21 Aug 2018	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ② 10 mg/m ³ ⑤ (Ceata uleioasa mineral)
CH from 1 Jan 2022	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (einatebare Fraktion) C2; Tox: Lunge; Messmeth: NIOSH DFG
LV from 12 Jul 2018	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Eļļas migla)
JP	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 3 mg/m ³ ⑤ (Oil mist mineral)
IDLH (US) from 1 Jan 1994	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 2,500 mg/m ³
IE from 1 Apr 2016	Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	① 5 mg/m ³ ⑤ (Oil mist mineral, inhalable fraction)



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
TRGS 900 (DE) from 1 Sept 2015	Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	① 5 mg/m ³ ② 20 mg/m ³ ⑤ (alveolengängige Fraktion) DFG
SI from 4 Dec 2018	Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	① 5 mg/m ³ ② 20 mg/m ³ ⑤ (alveolarna frakcija)
TRGS 900 (DE) from 30 Nov 2017	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 300 mg/m ³ ② 600 mg/m ³ ⑤ (C9-C14 Aliphaten)
VLA (FR)	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 1,000 mg/m ³ ② 1,500 mg/m ³ ⑤ (hydrocarbures C9-C12)
NO	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 50 ppm (275 mg/m ³) ⑤ (White Spirit (aromatinnhold < 22 %))
DFG (DE) from 1 Jul 2015	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 5 mg/m ³ ② 20 mg/m ³ ⑤ (Aerosol, alveolengängige Fraktion)
MAK (AT)	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 200 mL/m ³ ② 400 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/Isohexanen von weniger als 25 %)
MAK (AT)	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 170 mL/m ³ ② 340 mL/m ³ ⑤ (für Kohlenwasserstoffgemische mit einem Gehalt an aromatischen Kohlenwasserstoffen von weniger als 1 %, an n-Hexan von weniger als 5 % und an Cyclo-/Isohexanen von 25 % oder mehr)
WEL (GB)	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 1,200 mg/m ³ ⑤ (> or = C7, Normal and branched chain alkanes)
WEL (GB)	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 800 mg/m ³ ⑤ (> or = C7, Cycloalkanes)
DFG (DE) from 1 Jul 2015	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 50 ppm (350 mg/m ³) ② 100 ppm (700 mg/m ³) ⑤ (Dampf)
RU	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 100 mg/m ³ ③ 300 mg/m ³
CH from 1 Jan 2022	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 50 ppm (350 mg/m ³) ② 100 ppm (700 mg/m ³) ⑤ (Dampf) SSC; Tox: ZNS; Messmeth: OSHA
SI from 4 Dec 2018	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 700 mg/m ³



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
RO from 21 Aug 2018	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 700 mg/m ³ ② 1,000 mg/m ³
CH from 1 Jan 2022	Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8 EC No.: 920-107-4	① 5 mg/m ³ ⑤ (Aerosol; einatembare Fraktion) SSC; Tox: Lunge

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	2.73 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	5.58 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	0.97 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	11.75 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	3.33 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	1.03 mg/cm ²	① DNEL worker ② Long-term - dermal, local effects

Substance name	PNEC Value	① PNEC type
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7 EC No.: 309-877-7	9.33 mg/kg bw/day	① PNEC secondary poisoning
Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	1 mg/L	① PNEC aquatic, freshwater
Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	1 mg/L	① PNEC aquatic, marine water
Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9	1,000 mg/L	① PNEC sewage treatment plant



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

8.2. Exposure controls

8.2.1. Appropriate engineering controls

See section 7. No additional measures necessary.

8.2.2. Personal protection equipment



Eye/face protection:

During transfer: Eye glasses with side protection
 Wear eye/face protection. EN 166

Skin protection:

Hand protection

Suitable material: NBR (Nitrile rubber), PVC (polyvinyl chloride), CR (polychloroprene, chloroprene rubber)
 Thickness of the glove material: $\geq 0,4$ mm

Breakthrough time: 480 min

Breakthrough times and swelling properties of the material must be taken into consideration.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Tested protective gloves must be worn: EN ISO 374

Suitable protective clothing: Protective clothing

Respiratory protection:

Usually no personal respirative protection necessary.

8.2.3. Environmental exposure controls

See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: tawny

Odour: characteristic

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	<i>not applicable</i>		
Melting point	<i>not determined</i>		
Freezing point	<i>not determined</i>		
Initial boiling point and boiling range	<i>not determined</i>		
Decomposition temperature	<i>not determined</i>		
Flash point	232 °C		
Evaporation rate	<i>not determined</i>		
Auto-ignition temperature	<i>not determined</i>		
Upper/lower flammability or explosive limits	<i>not determined</i>		
Vapour pressure	<i>not determined</i>		
Vapour density	<i>not determined</i>		
Density	851 kg/m ³	15 °C	
Relative density	<i>not determined</i>		
Bulk density	<i>not determined</i>		
Water solubility	practically insoluble		
Partition coefficient: n-octanol/water	<i>not determined</i>		
Dynamic viscosity	<i>not determined</i>		
Kinematic viscosity	88 mm ² /s	40 °C	



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

9.2. Other information

Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No known hazardous reactions. Risk of explosion if heated under confinement.

10.2. Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

To avoid thermal decomposition do not overheat.

10.5. Incompatible materials

Materials to avoid: Acid, Oxidising agent, Reducing agent

10.6. Hazardous decomposition products

Hazardous combustion products: Carbon monoxide, Carbon dioxide (CO₂), Nitrogen oxides (NO_x),
 During heating or in case of fire, toxic gases is possible.

SECTION 11: Toxicological information

* 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified	CAS No.: 64742-54-7
EC No.: 265-157-1	
LD₅₀ oral: 5,000 mg/kg (Rat) OECD 401	
LD₅₀ dermal: 5,000 mg/kg (Rabbit) OECD 402	
LC₅₀ Acute inhalation toxicity (dust/mist): 5.53 mg/L 4 h (Rat) OECD 403	
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	CAS No.: 101316-72-7
EC No.: 309-877-7	
LD₅₀ oral: >5,000 mg/kg (Rat)	
LD₅₀ dermal: >2,000 mg/kg (Rabbit)	
LC₅₀ Acute inhalation toxicity (dust/mist): >5 mg/L (Rat)	
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	CAS No.: 68649-42-3 EC No.: 272-028-3
LD₅₀ oral: >2,154 - <3,100 mg/kg (Rat)	
LD₅₀ dermal: >6,965 mg/kg (Rabbit)	
LC₅₀ Acute inhalation toxicity (dust/mist): >5,000 mg/L (Mouse)	
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	CAS No.: 68584-23-6 EC No.: 271-529-4
LD₅₀ oral: <5,000 mg/kg (rat) OECD Guideline 401 (Acute Oral Toxicity)	
LD₅₀ dermal: <5,000 mg/kg (rat) OECD Guideline 402 (Acute Dermal Toxicity)	
LC₅₀ Acute inhalation toxicity (gas): <1.9 ppmV 4 h (rat) OECD Guideline 403 (Acute Inhalation Toxicity)	
Sulfonic acids, petroleum, calcium salts	CAS No.: 61789-86-4 EC No.: 263-093-9
LD₅₀ oral: >5,000 mg/kg (Rat)	
LD₅₀ dermal: >5,000 mg/kg (Rat)	
LC₅₀ Acute inhalation toxicity (gas): >1.9 ppmV 4 h (Rat)	
Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	CAS No.: 64742-47-8
EC No.: 920-107-4	
LD₅₀ oral: >5,000 mg/kg (Rat)	
LD₅₀ dermal: >5,000 mg/kg (Rabbit)	
LC₅₀ Acute inhalation toxicity (vapour): 4,951 mg/L 4 h	

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Contains Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts. May produce an allergic reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Observe risk of aspiration if vomiting occurs.

For viscosity data, see section 9.

Additional information:

Frequently or prolonged contact with skin may cause dermal irritation.

11.2. Information on other hazards

Endocrine disrupting properties:

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information

* **12.1. Toxicity**

Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified	CAS No.: 64742-54-7
EC No.: 265-157-1	
LC₅₀: 100 mg/L 4 d (fish)	
LC₅₀: 10,000 mg/L 4 d (crustaceans)	
EC₅₀: 10,000 mg/L 2 d (crustaceans)	
NOEC: 100 mg/L 4 d (fish)	
NOEC: 100 mg/L 3 d (Algae/water plant)	
NOEC: ≥100 mg/L 3 d (Algae/water plant, Algen)	
Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts	CAS No.: 68584-23-6 EC No.: 271-529-4
LC₅₀: >1,000 mg/L 4 d (fish, Freshwater fish)	
LC₅₀: >10,000 mg/L 4 d (fish, marine water fish)	
EC₅₀: >1,000 mg/L 4 d (crustaceans, fresh water invertebrates)	
NOEC: >1,000 mg/L 21 d (Algae/water plant, fresh water algae)	
Sulfonic acids, petroleum, calcium salts	CAS No.: 61789-86-4 EC No.: 263-093-9
LC₅₀: 1,000 mg/L 4 d (fish)	
EC₅₀: 1,000 mg/L 2 d (crustaceans)	
EC₅₀: 1,000 mg/L 3 d (Algae/water plant)	
Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics	CAS No.: 64742-47-8
EC No.: 920-107-4	
LC₅₀: >100 mg/L 4 d (fish, Oncorhynchus mykiss (Rainbow trout))	
EC₅₀: >100 mg/L 2 d (crustaceans, Daphnia magna (Big water flea))	
ErC₅₀: >100 mg/L 3 d (Algae/water plant, Skeletonema costatum)	

Assessment/classification:

The substance/mixture does not fulfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

Additional ecotoxicological information:

Do not allow uncontrolled discharge of product into the environment.



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

* **12.2. Persistence and degradability**

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7
 EC No.: 309-877-7

Biodegradation: not determined

Remark: The base oil / mineral oil used has a value of less than 3% DMSO, so it is not classified as a carcinogen.

Biodegradation:

Not readily biodegradable (according to OECD criteria)

* **12.3. Bioaccumulative potential**

Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8
 EC No.: 920-107-4

Log K_{ow}: 7

Accumulation / Evaluation:

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

* **12.5. Results of PBT and vPvB assessment**

Distillates (petroleum), hydrotreated heavy paraffinic; Base oil - not specified CAS No.: 64742-54-7
 EC No.: 265-157-1

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated CAS No.: 101316-72-7
 EC No.: 309-877-7

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts CAS No.: 68649-42-3 EC No.: 272-028-3

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Benzenesulfonic acid, C10-16-alkyl derivs., calcium salts CAS No.: 68584-23-6 EC No.: 271-529-4

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Sulfonic acids, petroleum, calcium salts CAS No.: 61789-86-4 EC No.: 263-093-9

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

Hydrocarbons, C12-C15, n-alkanes, iso-alkanes, cyclenes, <2% aromatics CAS No.: 64742-47-8
 EC No.: 920-107-4

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation.

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation.

Appropriate disposal / Package:

Non-contaminated packages may be recycled.

Other disposal recommendations:

Consult the appropriate local waste disposal expert about waste disposal.

13.2. Additional information

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.2. UN proper shipping name			
No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.	No dangerous good in sense of these transport regulations.
14.3. Transport hazard class(es)			
not relevant	not relevant	not relevant	not relevant
14.4. Packing group			
not relevant	not relevant	not relevant	not relevant
14.5. Environmental hazards			
not relevant	not relevant	not relevant	not relevant
14.6. Special precautions for user			
not relevant	not relevant	not relevant	not relevant

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive]: This product is not assigned to a hazard category.
 Safety data sheet available on request.

15.1.2. National regulations



[DE] National regulations

Störfallverordnung (12. BImSchV)

for substances contained in the product:

This product is not assigned to a hazard category.

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:

To follow: 5.2.5

Water hazard class

WGK:

2 - deutlich wassergefährdend

Source:

Self-classification (mixture; calculation rule).
 Identification number 436

Technische Regeln für Gefahrstoffe

TRGS 510
 TRGS 500

Berufsgenossenschaftliche Vorschriften (DGUV-Vorschriften)

Berufsgenossenschaftliche Informationen (DGUV-Informationen) 868
 Berufsgenossenschaftliche Regeln (DGUV-Regeln) 189, 190, 192, 195

Other regulations, restrictions and prohibition regulations

Altöl-Verordnung (AltöIV)



[DK] National regulations

Other regulations, restrictions and prohibition regulations

Dänemark: Bekendtgørelse af lov om arbejdsmiljø: Beskæftigelsesministeriets lovbekendtgørelse nr. 1072 af 7. september 2010
 Lister over stoffer og processer, der anses for at være kræftfremkaldende



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

[FR] National regulations

Other regulations, restrictions and prohibition regulations

Frankreich: Tableaux de maladies professionnelles
 Nomenclature des installations classées pour la protection de l'environnement
 Articles L. 4523-1 à L. 4523-17, L. 4611-1 à L. 4614-16, R. 4523-1 à R. 4523-17 et R. 4612-1 à R. 4615-21
 du Code du travail

[NL] National regulations

Other regulations, restrictions and prohibition regulations

Nederlande: Lijst vank kankerverwekkende, mutagene en voor de voortplanting giftige stoffen (SZW)
 Algemeene beoordelingsmethodiek Water (ABM)
 Nederlandse emissierichtlijn (NeR)
 NIET-Limitatieve lijst an voor de voortplanting giftige stoffen - Borstvoeding
 NIET-Limitatieve lijst an voor de voortplanting giftige stoffen - Vruchtbaarheid
 NIET-Limitatieve lijst an voor de voortplanting giftige stoffen - Ontwikkeling
 SZW-lijst van kankerverwekkende stoffen
 SZW-lijst van mutagene stoffen
 Wet van 18 maart 1999, houdende bepalingen ter verbetering van de arbeidsomstandigheden
 (Arbeidsomstandighedenwet)
 Wet op de ondernemingsraden 1971

[CH] National regulations

Other regulations, restrictions and prohibition regulations

Mengenschwelle (Schweiz - StFV)
 Gefahrencode
 Brandverhütung, BVD (Schweiz)

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

15.3. Additional information

No data available.

SECTION 16: Other information

* 16.1. Indication of changes

2.2.	Label elements
3.2.	Mixtures
4.2.	Most important symptoms and effects, both acute and delayed
8.1.	Control parameters
11.1.	Information on hazard classes as defined in Regulation (EC) No 1272/2008
12.1.	Toxicity
12.2.	Persistence and degradability
12.3.	Bioaccumulative potential
12.5.	Results of PBT and vPvB assessment
16.1.	Indication of changes
16.5.	Relevant R-, H- and EUH-phrases (Number and full text)

16.2. Abbreviations and acronyms

See overview table at www.euphrac.eu

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

16.3. Key literature references and sources for data

67/548/EEC - Dangerous Substances Directive
 1999/45/EEC - Dangerous Preparations Directive
 EC 1907/2006 - REACH Regulation
 1272/2008 EC - Regulation on classification, labeling and packaging of substances and mixtures, and amending Directives 67/548/EEC and 1999/45/EC and Regulation (EC) No 1907/2006
 Regulation (EC) No 1907/2006 (REACH), Annex II
 European Chemicals Agency (ECHA), C & L classification and labeling inventory
 European Chemicals Agency (ECHA), ECHA CHEM Registered substances
 OECD The Global Portal to Information on Chemical Substances (ChemPortal)
 Institute for Occupational Safety and Health of the German Social Accident Insurance (IFA): GESTIS substance database and International limit values for chemical substances



Revision date: 17 Jan 2023 Version: 9 Print date: 17 Jan 2023

Federal Environment Agency, Section IV 2.4: Documentation and Information Centre substances hazardous to water Rigoletto (catalog substances hazardous to water)

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

* 16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H400	Very toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

* Data changed compared with the previous version.