Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

# **SAFETY DATA SHEET**



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product name	Castrol Magnatec 5W-30 C3
Product code	462209-DE01
SDS #	462209
Product type	Liquid.
1.2 Relevant identified uses	of the substance or mixture and uses advised against
Use of the substance/ mixture	Automotive engine crankcase lubricant. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
1.3 Details of the supplier of	the safety data sheet
Supplier	Lubricants UK Limited, Chertsey Road, Sunbury On Thames, Middlesex, TW16 7BP
	+44 (0)345 600 8125
E-mail address	MSDSadvice@bp.com

 1.4 Emergency telephone number

 EMERGENCY
 Carechem: +44 (0) 1235 239 670 (24/7)

 TELEPHONE NUMBER

## **SECTION 2: Hazards identification**

 2.1 Classification of the substance or mixture

 Product definition
 Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Not classified.

See sections 11 and 12 for more detailed information on health effects and symptoms and environmental hazards.

#### 2.2 Label elements

2.2 Laber elements		
Signal word	No signal word.	
Hazard statements	No known significant effects or critical hazards.	
Precautionary statements		
Prevention	Not applicable.	
Response	Not applicable.	
Storage	Not applicable.	
Disposal	Not applicable.	
Hazardous ingredients	Not applicable.	
Supplemental label elements EU Regulation (EC) No. 1907	Contains Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl of Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated. May produ Safety data sheet available on request. 7/2006 (REACH)	
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	Not applicable.	
Product name Castrol Magnate	ec 5W-30 C3 Product code 462209-DE0	01 Page: 1/11
Version 3.01 Date of issue	25 June 2024 Format United La Kingdom (UK)	anguage ENGLISH
Date of previous issue	26 March 2024. (United Kingdom)	

## Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

# **SECTION 2: Hazards identification**

Special packaging requireme	nts
Containers to be fitted with child-resistant fastenings	Not applicable.
Tactile warning of danger	Not applicable.
2.3 Other hazards	
Results of PBT and vPvB assessment	Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	Defatting to the skin. USED ENGINE OILS Used engine oil may contain hazardous components which have the potential to cause skin cancer. See Toxicological Information, section 11 of this Safety Data Sheet.

## **SECTION 3: Composition/information on ingredients**

Mixture

#### 3.2 Mixtures

Product definition

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 UK (GB) REACH #: UK-01-1759217276-5 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	EC: 682-816-2 CAS: 722503-68-6	<1	Skin Sens. 1B, H317	-	[1]
Alkyl (C18-C28) toluenesulfonic acid, calcium salts, borated	EC: 953-650-0 CAS: -	<1	Skin Sens. 1B, H317 Repr. 2, H361d	-	[1]

See Section 16 for the full text of the H statements declared above.

#### Туре

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

### **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

Eye contact	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.	
Skin contact	Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if irritation develops.	
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.	
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. Get medical attention it symptoms occur.	
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training.	

#### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms. <u>Potential acute health effects</u>

Product name Castrol Magnatec 5W-30 C3		Product code 462209-DE01		Page: 2/11	
Version 3.01 Date of issue	25 June 2024	Format	United Kingdom (UK)	Language	ENGLISH
Date of previous issue	26 March 2024.		(United Kingdom)		

## Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by Commission Regulation (EU) 2020/878

# SECTION 4: First aid measures

Inhalation	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.
Ingestion	No known significant effects or critical hazards.
Skin contact	Defatting to the skin. May cause skin dryness and irritation.
Eye contact	No known significant effects or critical hazards.
Delayed and immediate effects	s as well as chronic effects from short and long-term exposure
Inhalation	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.
Skin contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.
Eye contact	Potential risk of transient stinging or redness if accidental eye contact occurs.

# 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects.
--------------------	---

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media	
Suitable extinguishing media	In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet. The use of a water jet may cause the fire to spread by splashing the burning product.
5.2 Special hazards arising fro	om the substance or mixture
Hazards from the substance or mixtureIn a fire or if heated, a pressure increase will occur and the container may burst.	
Hazardous combustion productsCombustion products may include the following: carbon oxides (CO, CO2) (carbon monoxide, carbon dioxide)	
5.3 Advice for firefighters	
Special precautions for fire-fighters	No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire.
<b>Special protective</b> <b>equipment for fire-fighters</b> Fire-fighters should wear appropriate protective equipment and self-contained apparatus (SCBA) with a full face-piece operated in positive pressure mode. fighters (including helmets, protective boots and gloves) conforming to Europ 469 will provide a basic level of protection for chemical incidents.	

# SECTION 6: Accidental release measures

6.1 Personal precautions, prot	ective equipment and emergency procedures		
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touc or walk through spilt material. Floors may be slippery; use care to avoid falling. Put on appropriate personal protective equipment.		
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".		
6.2 Environmental precautions	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).		
6.3 Methods and material for c	containment and cleaning up		
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.		
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.		
<b>F</b>			

Product name Castrol Magnat	tec 5W-30 C3		Product code 462209-E	DE01	Page: 3/11
Version 3.01 Date of issue	25 June 2024	Format	United Kingdom (UK)	Language	ENGLISH
Date of previous issue	26 March 2024.		(United Kingdom)		

## **SECTION 6: Accidental release measures**

	6.4 Reference to other	See Section 1 for emergency contact information.
	sections	See Section 5 for firefighting measures.
		See Section 8 for information on appropriate personal protective equipment.
		See Section 12 for environmental precautions.
		See Section 13 for additional waste treatment information.

## **SECTION 7: Handling and storage**

7.1 Precautions for safe hand	dling
Protective measures	Put on appropriate personal protective equipment.
Advice on general occupational hygiene	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
7.2 Conditions for safe storage, including any incompatibilities	Store in accordance with local regulations. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Keep away from heat and direct sunlight. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store and use only in equipment/ containers designed for use with this product. Do not store in unlabelled containers.
Not suitable	Prolonged exposure to elevated temperature.
7.3 Specific end use(s)	
Recommendations	See section 1.2 and Exposure scenarios in annex, if applicable.

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control parameters

#### **Occupational exposure limits**

#### Product/ingredient name

**Exposure limit values** 

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Recommended monitoring procedures

Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

(United Kingdom)

#### Derived No Effect Level

No DNELs/DMELs available.

#### **Predicted No Effect Concentration**

No PNECs available

Date of previous issue

26 March 2024.

8.2 Exposure controls						
Appropriate engineering controls	Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards. The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.					
Individual protection measures	<u>5</u>					
Hygiene measures	Wash hands, forearms and face the smoking and using the lavatory and stations and safety showers are clo	at the er	nd of the workir	ng period.		0.
Respiratory protection						
Product name Castrol Magnatec	5W-30 C3		Product code	462209-D	)E01	Page: 4/11
Version 3.01 Date of issue 25	5 June 2024	Format	United Kingdom (UK)		Language	ENGLISH

# SECTION 8: Exposure controls/personal protection

	le sess of insufficient contilution, communicatelle respiratements
	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Eye/face protection	Safety glasses with side shields.
Skin protection	
Hand protection	General Information:
	Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. The correct choice of protective gloves depends upon the chemicals being handled, and the conditions of work and use. Most gloves provide protection for only a limited time before they must be discarded and replaced (even the best chemically resistant gloves will break down after repeated chemical exposures).
	Gloves should be chosen in consultation with the supplier / manufacturer and taking account of a full assessment of the working conditions.
	Recommended: Nitrile gloves. Breakthrough time:
	Breakthrough time data are generated by glove manufacturers under laboratory test conditions and represent how long a glove can be expected to provide effective permeation resistance. It is important when following breakthrough time recommendations that actual workplace conditions are taken into account. Always consult with your glove supplier for up-to-date technical information on breakthrough times for the recommended glove type. Our recommendations on the selection of gloves are as follows:
	Continuous contact:
	Gloves with a minimum breakthrough time of 240 minutes, or >480 minutes if suitable gloves can be obtained. If suitable gloves are not available to offer that level of protection, gloves with shorter breakthrough times may be acceptable as long as appropriate glove maintenance and replacement regimes are determined and adhered to.
	Short-term / splash protection:
	Recommended breakthrough times as above. It is recognised that for short-term, transient exposures, gloves with shorter breakthrough times may commonly be used. Therefore, appropriate maintenance and replacement regimes must be determined and rigorously followed.
	Glove Thickness:
	For general applications, we recommend gloves with a thickness typically greater than 0.35 mm.
	It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times. Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers' technical data should always be taken into account to ensure selection of the most appropriate glove for the task.
	Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:
	• Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.
	• Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential.

Product name Castrol Magnatec 5W-30 C3		Product code 462209-DE01		Page: 5/11		
Version 3.01	Date of issue	25 June 2024	Format	United Kingdom (UK)	Language	ENGLISH
Date of previo	ous issue	26 March 2024.		(United Kingdom)		

## **SECTION 8: Exposure controls/personal protection**

	• •
Skin and body	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
<u>Refer to standards:</u>	Respiratory protection: EN 529 Gloves: EN 420, EN 374 Eye protection: EN 166 Filtering half-mask: EN 149 Filtering half-mask with valve: EN 405 Half-mask: EN 140 plus filter Full-face mask: EN 136 plus filter Particulate filters: EN 143 Gas/combined filters: EN 14387
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

or information on subio physical c	
Physical state	Liquid.
Colour	Amber.
Odour	Not available.
Odour threshold	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flammability	Not available.
Lower and upper explosion limit	Not available.
Flash point	Closed cup: 210°C (410°F) [Pensky-Martens ASTM D 93]
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
рН	Not available.
Kinematic viscosity	Kinematic: 69.3 mm²/s (69.3 cSt) at 40°C Kinematic: 10.6 to 12.4 mm²/s (10.6 to 12.4 cSt) at 100°C
Solubility	

Not available.

Not applicable.

Partition coefficient n-octanol/ water (log value)

Vapour pressure

Vapour Pressure at 20°C Vapour pressure at 50°C mm Hg kPa Method kPa Method **Ingredient name** mm Hg **P**istillates (petroleum), <0.07501 <0.01 ASTM D 5191 hydrotreated heavy paraffinic Distillates (petroleum), <0.07501 <0.01 ASTM D 5191 hydrotreated heavy paraffinic Distillates (petroleum), <0.07501 < 0.01 ASTM D 5191 solvent-dewaxed heavy paraffinic Distillates (petroleum), <0.07501 < 0.01 ASTM D 5191 hydrotreated light paraffinic Product code 462209-DE01 Page: 6/11 Product name Castrol Magnatec 5W-30 C3 Version 3.01 Date of issue 25 June 2024 **Format United** Language ENGLISH Kingdom (UK) (United Kingdom) Date of previous issue 26 March 2024.

# **SECTION 9: Physical and chemical properties**

Pour point	-39 °C
Oxidising properties	Not available.
Explosive properties	Not available.
Evaporation rate	Not available.
9.2 Other information	
Median particle size	Not applicable.
Particle characteristics	
Relative vapour density	Not available.
Density and/or Relative density	<1000 kg/m³ (<1 g/cm³) at 15°C

# SECTION 10: Stability and reactivity

10.1 Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.
10.2 Chemical stability	The product is stable.
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerisation will not occur.
10.4 Conditions to avoid	Avoid all possible sources of ignition (spark or flame).
10.5 Incompatible materials	Reactive or incompatible with the following materials: oxidising materials.
10.6 Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Acute toxicity estimates

Not available.

#### **Aspiration hazard**

Product/ingredient name		Result			
Distillates (petroleum), hydrotreated heavy paraffinic		ASPIRATION	HAZARD - Category	/ 1	
Conclusion/Summary	Not classified. Based on ava	Not classified. Based on available data, the classification criteria are not met.			
Information on likely routes of exposure	Routes of entry anticipated: 0	Koutes of entry anticipated: Oral, Dermal, Inhalation, Eyes.			
Potential acute health effe	<u>cts</u>				
Inhalation	Vapour inhalation under amb pressure.	Vapour inhalation under ambient conditions is not normally a problem due to low vapour pressure.			
Ingestion	No known significant effects	No known significant effects or critical hazards.			
Skin contact	Defatting to the skin. May ca	Defatting to the skin. May cause skin dryness and irritation.			
Eye contact	No known significant effects	or critical hazard	S.		
Symptoms related to the p	hysical, chemical and toxicologi	cal characteris	<u>tics</u>		
Inhalation	No specific data.	No specific data.			
Ingestion	No specific data.	No specific data.			
Skin contact	Adverse symptoms may inclu irritation dryness cracking	dryness			
Eye contact	No specific data.	No specific data.			
Delayed and immediate effects as well as chronic effects from short and long-term exposure					
Inhalation	Overexposure to the inhalation respiratory tract.	Overexposure to the inhalation of airborne droplets or aerosols may cause irritation of the respiratory tract.			
Ingestion	Ingestion of large quantities may cause nausea and diarrhoea.				
Skin contact	Prolonged or repeated contact	Prolonged or repeated contact can defat the skin and lead to irritation and/or dermatitis.			
Eye contact	Potential risk of transient stin	Potential risk of transient stinging or redness if accidental eye contact occurs.			
Product name Castrol Magn	atec 5W-30 C3		Product code 462209	9-DE01	Page: 7/11
Version 3.01 Date of issu	ie 25 June 2024		United Kingdom (UK)	Language	ENGLISH
Date of previous issue	26 March 2024.		(United Kingdom)		

## **SECTION 11: Toxicological information**

Potential chronic health eff	<u>ects</u>
General	USED ENGINE OILS Combustion products resulting from the operation of internal combustion engines contaminate engine oils during use. Used engine oil may contain hazardous components which have the potential to cause skin cancer. Frequent or prolonged contact with all types and makes of used engine oil must therefore be avoided and a high standard of personal hygiene maintained.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Developmental effects	No known significant effects or critical hazards.
Fertility effects	No known significant effects or critical hazards.
11.2 Information on other h	azards
11.2.1 Endocrine disruptin	g properties
Not available.	

Remarks -Endocrine Not available. disrupting properties for human health Conclusion/ Summary 11.2.2 Other information

Not available.

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Environmental hazards Not classified as dangerous

12.2 Persistence and degradability

Expected to be biodegradable.

### 12.3 Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	Not available.
Mobility	Spillages may penetrate the soil causing ground water contamination.

#### 12.5 Results of PBT and vPvB assessment

Product does not meet the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII.

12.6 Endocrine disrupting properties	Not available.
Remarks - Endocrine disrupting properties for environment Conclusion/ Summary	Not available.
Other ecological information	Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.
12.7 Other adverse effects	No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

13.1 Waste treatment methods	
Product	
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Hazardous waste	Yes.
European waste catalogue (E	EWC)

Product name	Castrol Magnatec 5W-30 C3		Product code 462209-D	DE01	Page: 8/11
Version 3.01	Date of issue 25 June 2024	Format	United Kingdom (UK)	Language	ENGLISH
Date of previo	bus issue 26 March 2024.		(United Kingdom)		

## **SECTION 13: Disposal considerations**

Waste code	Waste designation
13 02 05*	mineral-based non-chlorinated engine, gear and lubricating oils
However, deviation from t disposal code to be assign	he intended use and/or the presence of any potential contaminants may require an alternative waste ned by the end user.
Packaging	
Methods of disposal	Where possible, arrange for product to be recycled. Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations.
Special precautions	This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

References

soil, waterways, drains and sew Commission 2014/955/EU Directive 2008/98/EC

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	ΙΑΤΑ
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

14.6 Special precautions for Not available. user

 14.7 Maritime transport in
 Not available.

 bulk according to IMO
 instruments

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture EU Regulation (EC) No. 1907/2006 (REACH) Annex XIV - List of substances subject to authorisation **Annex XIV** None of the components are listed. Substances of very high concern None of the components are listed. Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances. mixtures and articles No listed substance Labelling Not applicable. **Other regulations REACH Status** The company, as identified in Section 1, sells this product in the EU in compliance with the current requirements of REACH.

All components are active or exempted.

United States inventory (TSCA 8b)

Product name Castro	ol Magnatec 5W-30 C3		Product code 462209-E	DE01	Page: 9/11
Version 3.01 Date	e of issue 25 June 2024	Format	Kingdom (UK)	Language	ENGLISH
Date of previous is	ssue 26 March 2024.		(United Kingdom)		

# **SECTION 15: Regulatory information**

Australia inventory (AIIC)	All components are listed or exempted.				
Canada inventory	All components are listed or exempted.				
China inventory (IECSC)	At least one component is not listed.				
Japan inventory (CSCL)	All components are listed or exempted.				
Korea inventory (KECI)	All components are listed or exempted.				
Philippines inventory (PICCS)	All components are listed or exempted.				
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.				
Explosive precursors	Not applicable.				
Ozone depleting substances (1005/2009/EU)					
Not listed.					
Prior Informed Consent (PIC) Not listed.	<u>(649/2012/EU)</u>				
Persistent Organic Pollutants Not listed.					
EU - Water framework directive - Priority substances					
None of the components are lis	ted.				
Seveso Directive					

This product is not controlled under the Seveso Directive.

15.2 Chemical safety	A Chemical Safety Assessment has been carried out for one or more of the substances within
assessment	this mixture. A Chemical Safety Assessment has not been carried out for the mixture itself.

# SECTION 16: Other information

Abbreviations and acronyms	ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway							
	ADR = The European Agreement c Road	oncerning	the Internation	al Carria	ge of Dange	rous Goods by		
	ATE = Acute Toxicity Estimate							
	BCF = Bioconcentration Factor							
	CAS = Chemical Abstracts Service							
	CLP = Classification, Labelling and	Packagin	a Regulation [R	equilation	(FC) No 1	272/20081		
	CSA = Chemical Safety Assessme	0	g rogulation [r	logulation	. (20)	212/2000]		
	CSR = Chemical Safety Report							
	DMEL = Derived Minimal Effect Lev	/el						
	DNEL = Derived No Effect Level							
	EINECS = European Inventory of E	xisting Co	ommercial chem	nical Subs	stances			
	ES = Exposure Scenario	Ũ						
		EUH statement = CLP-specific Hazard statement						
	EWC = European Waste Catalogue	e						
	GHS = Globally Harmonized System of Classification and Labelling of Chemicals							
	IATA = International Air Transport Association							
	IBC = Intermediate Bulk Container							
	IMDG = International Maritime Dangerous Goods							
	LogPow = logarithm of the octanol/water partition coefficient							
	MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as							
	modified by the Protocol of 1978. ("Marpol" = marine pollution)							
	OECD = Organisation for Economic Co-operation and Development							
	PBT = Persistent, Bioaccumulative and Toxic							
	PNEC = Predicted No Effect Concentration							
	REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation							
	[Regulation (EC) No. 1907/2006] RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail							
			ational Carriage	e of Dang	jerous Good	is by Rall		
	RRN = REACH Registration Number SADT = Self-Accelerating Decomposition		mporaturo					
	SVHC = Substances of Very High (		mperature					
	STOT-RE = Specific Target Organ		Penested Expo	euro				
	STOT-SE = Specific Target Organ							
	TWA = Time weighted average	TONICITY -		6				
Product name Castrol Magnate	5 5		Product codo	462200 F		Page: 10/11		
Ũ			Product code	402209-L		•		
Version 3.01 Date of issue	25 June 2024	Format	United		Language	ENGLISH		
			Kingdom					
			(UK)					
Date of previous issue	26 March 2024.		(United Kingdo	) (1)				

## **SECTION 16: Other information**

UN = United Nations UVCB = Complex hydrocarbon substance VOC = Volatile Organic Compound vPvB = Very Persistent and Very Bioaccumulative Varies = may contain one or more of the following 64741-88-4 / RRN 01-2119488706-23, 64741-89-5 / RRN 01-2119487067-30, 64741-95-3 / RRN 01-2119487081-40, 64741-96-4/ RRN 01-2119483621-38, 64742-01-4 / RRN 01-2119488707-21, 64742-44-5 / RRN 01-2119985177-24, 64742-45-6, 64742-52-5 / RRN 01-2119467170-45, 64742-53-6 / RRN 01-2119480375-34, 64742-54-7 / RRN 01-2119484627-25, 64742-55-8 / RRN 01-2119487077-29, 64742-56-9 / RRN 01-2119480132-48, 64742-57-0 / RRN 01-2119489287-22, 64742-58-1, 64742-62-7 / RRN 01-2119480472-38, 64742-63-8, 64742-65-0 / RRN 01-2119471299-27, 64742-70-7 / RRN 01-2119487080-42, 72623-85-9 / RRN 01-2119555262-43, 72623-86-0 / RRN 01-2119474878-16, 72623-87-1 / RRN 01-2119474889-13

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification			Justification
Not classified.			
Full text of abbreviated H statements	H304	Ma	ay be fatal if swallowed and enters airways.
Full text of classifications [CLP/GHS]	Asp. Tox. 1	AS	SPIRATION HAZARD - Category 1
<u>History</u>			
Date of issue/ Date of revision	25/06/2024.		
Date of previous issue	26/03/2024.		
Prepared by	Product Stewardship Group		
Indicates information that	has changed from previously	้เรรเ	ied version.

#### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

						_
Product name Castrol Magnatec 5W-30 C3			Product code 462209-DE01		Page: 11/11	
Version 3.01 Date of is	<b>sue</b> 25 June 2024	Format	United Kingdom (UK)	Language	ENGLISH	
Date of previous issue	26 March 2024.		(United Kingdom)			
						-