

Page 1/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Presto Multi Wax 1000ml
- · Article number: 432132
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category

PROC7 Industrial spraying

PROC10 Roller application or brushing

PROC11 Non industrial spraying

- · Application of the substance / the mixture Protective coating
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

- *Formerly known as Motip Dupli GmbH
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3

H226 Flammable liquid and vapour.

(Contd. on page 2)

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

(Contd. of page 1)



Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

Naphtha (petroleum), hydrotreated heavy

Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics

· Hazard statements

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH208 Contains Calcium Sulfonate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

Dangerous components:		
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304 TOT SE 3, H336	25-<50%
EC number: 927-241-2 Reg.nr.: 01-2119471843-32	Hydrocarbons, C9-C10, n-alkanes, iso-alkanes, cyclics, <2% aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 3, H412 EUH066	12.5-<20%
CAS: 61789-86-4 EINECS: 263-093-9 Reg.nr.: 01-2119488992-18	Calcium Sulfonate ◆ Skin Sens. 1B, H317 Specific concentration limit: Skin Sens. 1B; H317: C ≥ 10 %	5-<10%
CAS: 154518-38-4 EC number: 800-484-0 Reg.nr.: 01-2119976356-25	Phosphoric acid, C11-14-isoalkyl esters, C13-rich Eye Dam. 1, H318 Aquatic Chronic 2, H411 Skin Irrit. 2, H315	2.5-<5%
CAS: 68526-86-3 EINECS: 271-235-6	alcohols, C11-14-iso-, C13-rich Aquatic Acute 1, H400; Aquatic Chronic 2, H411	<1%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

- · 5.3 Advice for firefighters -
- · Protective equipment: No special measures required.

GB

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

(Contd. of page 3)

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- \cdot 7.3 *Specific end use(s) No further relevant information available.*

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

(Contd. on page 5)

Printing date 17.12.2021 *Version number 4 (replaces version 3)* Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

· Hand protection



Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min Butyl acetate: 60 min Ethyl acetate: 170 min Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42-480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

General Information

· Physical state Fluid · Colour: Beige · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

136 °C (276.8 °F) range · Flammability Not applicable.

· Lower and upper explosion limit

0.6 Vol % · Lower: 7 Vol % · Upper: 28 °C (82.4 °F) · Flash point: · Decomposition temperature: Not determined.

Mixture is non-soluble (in water). $\cdot pH$

· Viscosity:

30 s (DIN 53211/4) · Kinematic viscosity at 20 °C (68 °F) · Dynamic: Not determined.

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C (68 °F): 5 hPa (3.8 mm Hg)

· Density and/or relative density

· Density at 20 °C (68 °F): $0.9 \ g/cm^3 (7.5 \ lbs/gal)$ · Relative density Not determined.

· Vapour density Not determined.

(Contd. on page 6)

(Contd. of page 4)

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

(Contd. of page 5)

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

• Ignition temperature: $>200 \, ^{\circ}C \, (>392 \, ^{\circ}F)$

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

• Organic solvents: 54.6 %
• VOC (EC) --- 469.6 g/l

· VOC-EU% 54.60 % *· Solids content:* 42.0 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures, which emit flammable gases in contact with water

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50	values	rolovant	for cla	ssification.
LULLUSU	ruiucs	<i>i</i> cicvaiii	ivi ciu	ssiiicaiicii.

Hydrocarbons.	C9-C10	n_alkanes	iso-alkanes	cyclics	<2%	romatics

Oral	LD50	>15000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3160 mg/kg (rabbit) (OECD 402)

(Contd. on page 7)

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

			(Contd. of page 6)
	Inhalative	LC50/4 h	>6100 mg/m3 (rat) (OECD 403)
Ī	<i>154518-38</i>	-4 Phosphori	ic acid, C11-14-isoalkyl esters, C13-rich
Ī	Oral	LD50	>2000 mg/kg (rat)
	Dermal	LD50	>2000 mg/kg (rat)
		LC50 / 96 h	24 mg/l (fish)

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

154518-38-4 Phosphoric acid, C11-14-isoalkyl esters, C13-rich

EC50 / 48 h 6.31 mg/l (Daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

SECTION 14: Transport information

- · 14.1 UN number or ID number
- · ADR, IMDG, IATA UN1139
- · 14.2 UN proper shipping name
- · ADR 1139 COATING SOLUTION

(Contd. on page 8)

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

THE C. THE	(Contd. of pa
IMDG, IATA	COATING SOLUTION
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class Label	3 Flammable liquids. 3
	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
<u> </u>	
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Flammable liquids. 30
EMS Number:	F-E,S-E
Stowage Category	A 2, <u>5 2</u>
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	11
ADR Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
Блеериса циининев (Б <u>У</u>)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
- · · 	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1139 COATING SOLUTION, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

(Contd. on page 9)

Printing date 17.12.2021 Version number 4 (replaces version 3) Revision: 16.12.2021

Trade name: Presto Multi Wax 1000ml

(Contd. of page 8)

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H336 May cause drowsiness or dizziness.
- *H400 Very toxic to aquatic life.*
- *H411 Toxic to aquatic life with long lasting effects.*
- H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* * Data compared to the previous version altered.