#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 1 / 11

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

**Product identifier** 

febi 48785 Gear oil 75W - 85 Article number: 48785

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.2.1 Relevant uses

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Ferdinand Bilstein GmbH + Co. KG

> Wilhelmstr. 47 58256 Ennepetal / GERMANY

Phone +49 2333 911-0 Fax +49 2333 911-444 Homepage www.febi.com E-mail info@febi.com

Address enquiries to

**Technical information** info@febi.com Safety Data Sheet info@febi.com

1.4 Emergency telephone number

**Advisory body** +49 (0)89-19240 (24h) (English)

**SECTION 2: Hazards identification** 

Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Eye Irrit. 2: H319 Causes serious eye irritation.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms

Signal word WARNING

**Hazard statements** H319 Causes serious eye irritation.

**Precautionary statements** P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice / attention.

P501 Dispose of contents / container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of

disposal.

Special labelling Contains: Polysulfides, di-tert-Bu. EUH208 May produce an allergic reaction.

2.3 Other hazards

**Environmental hazards** Does not contain any PBT or vPvB substances.

Other hazards No particular hazards known.

# **ebi**

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 2 / 11

#### **SECTION 3: Composition / Information on ingredients**

#### Product-type:

3.2 The product is a mixture.

Range [%]	Substance
20 - < 25	Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)
	CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX
	GHS/CLP: Asp. Tox. 1: H304
1 - < 3	Phosphoric acid esters, amine salt
	EINECS/ELINCS: 942-466-6
	GHS/CLP: Eye Dam. 1: H318
1 -< 5	Polysulfides, di-tert-Bu
	CAS: 68937-96-2, EINECS/ELINCS: 273-103-3, Reg-No.: 01-2119540515-43
	GHS/CLP: Skin Sens. 1B: H317 - Aquatic Chronic 3: H412
0,1 - < 0,25	(Z)-2-(8-heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol
·	CAS: 21652-27-7, EINECS/ELINCS: 244-501-4
	GHS/CLP: Acute Tox. 4: H302 - Skin Corr. 1C: H314 - Eye Dam. 1: H318 - Aquatic Acute 1: H400 - Aquatic Chronic 1: H410

Comment on component parts

Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.

For full text of H-statements: see SECTION 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**General information** Change soaked clothing.

**Inhalation** Ensure supply of fresh air.

In the event of symptoms seek medical treatment.

Skin contact In case of contact with skin wash off immediately with soap and water.

Consult a doctor if skin irritation persists.

Eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

**Ingestion** Do not induce vomiting.

Consult a doctor immediately.

Rinse out mouth and give plenty of water to drink.

#### 4.2 Most important symptoms and effects, both acute and delayed

No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Forward this sheet to the doctor.

#### **SECTION 5: Fire-fighting measures**

#### 5.1 Extinguishing media

**Suitable extinguishing media** Foam, dry powder, water spray jet, carbon dioxide.

Extinguishing media that must not

be used

Full water jet.

#### 5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.

Nitrogen oxides (NOx).

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 3 / 11

#### 5.3 Advice for firefighters

Do not inhale explosion and/or combustion gases.

Use self-contained breathing apparatus.

Fire residues and contaminated firefighting water must be disposed of in accordance within

the local regulations.

Cool containers at risk with water spray jet.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Some risk of slipping due to spillage of product.

Forms slippery surfaces with water.

#### 6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).

Do not discharge into the drains/surface waters/groundwater.

#### 6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. oil binder).

Dispose of absorbed material in accordance within the regulations.

#### 6.4 Reference to other sections

See SECTION 8+13

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

No special measures necessary if used correctly.

Use only in well-ventilated areas.

Use solvent-resistant equipment.

The product is combustible.

Do not eat, drink or smoke when using this product.

After worktime and before work breaks the affected skin areas must be thoroughly cleaned.

Use barrier skin cream.

Contaminated work clothing should not be allowed out of the workplace.

Take off contaminated clothing and wash before reuse.

Cloths contaminated with product should not be kept in trouser pockets.

#### 7.2 Conditions for safe storage, including any incompatibilities

Keep only in original container.

Prevent penetration into the ground.

Do not store together with oxidizing agents.

Keep container in a well-ventilated place.

Keep container tightly closed.

#### 7.3 Specific end use(s)

See product use, SECTION 1.2

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 4 / 11

#### SECTION 8: Exposure controls / personal protection

#### 8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract)

CAS: 64742-54-7, EINECS/ELINCS: 265-157-1, EU-INDEX: 649-467-00-8, Reg-No.: 01-2119484627-25-XXXX

Long-term exposure: 5 mg/m³, oil mist

Short-term exposure (15-minute): 10 mg/m³

#### **DNEL**

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

Industrial, dermal, Long-term - systemic effects: 1 mg/kg bw/day.

Industrial, inhalative, Long-term - local effects: 5,6 mg/m<sup>3</sup>.

Industrial, inhalative, Long-term - systemic effects: 2,7 mg/m³.

general population, oral, Long-term - systemic effects: 0,74 mg/kg bw/day.

Polysulfides, di-tert-Bu, CAS: 68937-96-2

Industrial, dermal, Long-term - systemic effects: 3.33 mg/kg bw/day.

Industrial, inhalative, Long-term - systemic effects: 14.5 mg/m<sup>3</sup>.

general population, dermal, Long-term - systemic effects: 1.66 mg/kg bw/day.

general population, inhalative, Long-term - systemic effects: 2.6 mg/m³.

#### **PNEC**

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

oral (food), 9,33 mg/kg.

Polysulfides, di-tert-Bu, CAS: 68937-96-2

soil, 1513 mg/kg soil dw

4.51 mg/L.

sediment (seawater), 0.094 mg/kg sediment dw

4.51 mg/L.

sediment (freshwater), 0.94 mg/kg sediment dw

4.51 mg/L

sewage treatment plants (STP), 4.51 mg/L

4.51 mg/L.

seawater, 0.024 µg/L.

freshwater, 0.24 µg/L.

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 5 / 11

#### 8.2 Exposure controls

Additional advice on system design Ensure adequate ventilation on workstation.

General exposure limit for oil mist should be noted.

Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of

hazardous substances.

Eye protection Safety glasses. (EN 166:2001)

The details concerned are recommendations. Please contact the glove supplier for further Hand protection

> 0,4 mm: Nitrile rubber, >120 min (EN 374-1/-2/-3).

Skin protection Light protective clothing.

Other Personal protective equipment should be selected specifically for the working place,

depending on concentration and quantity handled. The resistance of this equipment to

chemicals should be ascertained with the respective supplier.

Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin.

Respiratory protection Breathing apparatus in the event of aerosol or mist formation.

Short term: filter apparatus, combination filter A-P1. (DIN EN 14387)

Thermal hazards No information available.

Delimitation and monitoring of the

environmental exposition

Comply with applicable environmental regulations limiting discharge to air, water and soil.

#### **SECTION 9: Physical and chemical properties**

#### Information on basic physical and chemical properties 9.1

Form liauid Color brown

Odor characteristic

**Odour threshold** No information available.

pH-value not applicable pH-value [1%] not applicable Boiling point [°C] not applicable

Flash point [°C]

Flammability (solid, gas) [°C] Not explosive. Lower explosion limit not self-igniting Upper explosion limit not applicable

**Oxidising properties** 

Vapour pressure/gas pressure [kPa] No information available.

Density [g/ml] 0,85 (DIN 51757) (15 °C / 59,0 °F)

Bulk density [kg/m³] not applicable Solubility in water immiscible

Partition coefficient [n-octanol/water] No information available. 78 mm<sup>2</sup>/s 40°C (DIN 51562) Viscosity Relative vapour density determined

in air

No information available.

**Evaporation speed** No information available. Melting point [°C] No information available.

Autoignition temperature [°C] not applicable

Decomposition temperature [°C] No information available.

#### 9.2 Other information

No information available.

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 6 / 11

#### **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

See SECTION 10.3.

#### 10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

#### 10.3 Possibility of hazardous reactions

Reactions with strong oxidizing agents. Reactions with strong alkalies. Reactions with strong acids.

#### 10.4 Conditions to avoid

Strong heating.

#### 10.5 Incompatible materials

Strong oxidizing agent. Strong basic compounds strong acids

#### 10.6 Hazardous decomposition products

No hazardous decomposition products known.



#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 7 / 11

#### **SECTION 11: Toxicological information**

#### 11.1 Information on toxicological effects

Acute toxicity

Product

inhalative, Based on the available information, the classification criteria are not fulfilled.:

dermal, Based on the available information, the classification criteria are not fulfilled.:

oral, Based on the available information, the classification criteria are not fulfilled .:

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

LD50, dermal, Rabbit: > 2000 mg/kg.

LD50, oral, Rat: > 5000 mg/kg.

LC50, dermal, Rat: 2,18 mg/l.

(Z)-2-(8-heptadecenyl)-4,5-dihydro-1H-imidazole-1-ethanol, CAS: 21652-27-7

ATE, oral, 500 mg/kg bw.

Polysulfides, di-tert-Bu, CAS: 68937-96-2

LD0, dermal, Rat: 2000 mg/kg bw (OECD 402).

LD0, oral, Rat: 2000 mg/kg bw (OECD 401).

Serious eye damage/irritation Toxicological data of complete product are not available.

Irritant

Calculation method

Skin corrosion/irritation Based on the available information, the classification criteria are not fulfilled.

Respiratory or skin sensitisation Non-sensitizing.

On basis of test data

Specific target organ toxicity —

single exposure

Based on the available information, the classification criteria are not fulfilled.

Specific target organ toxicity —

repeated exposure

Based on the available information, the classification criteria are not fulfilled.

Mutagenicity

Based on the available information, the classification criteria are not fulfilled.

Based on the available information, the classification criteria are not fulfilled.

Reproduction toxicity

Based on the available information, the classification criteria are not fulfilled.

Carcinogenicity

Based on the available information, the classification criteria are not fulfilled.

Aspiration hazard General remarks

Toxicological data of complete product are not available.

The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists.

# ebi bilstein

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 8 / 11

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product

Based on the available information, the classification criteria are not fulfilled .:

Substance

Destillates (petroleum), hydrotreated heavy paraffinic (containing < 3% DMSO-extract), CAS: 64742-54-7

EL50, (24h), Daphnia magna: > 10000 mg/l.

NOELR, (14d), Oncorhynchus mykiss: >= 1000 mg/l.

LL50, (96h), Pimephales promelas: >100 mg/l.

NOEL, (72h), Pseudokirchneriella subcapitata: >= 100 mg/l.

NOEL, (21d), Daphnia magna: 10 mg/l.

Polysulfides, di-tert-Bu, CAS: 68937-96-2

LC50, (96h), Danio rerio: >0.088 mg/L (OECD 203).

EC50, (72h), Pseudokirchneriella subcapitata: 2.45 mg/L (OECD 201).

EC50, (24h), Daphnia magna: >0.27 mg/L (OECD 202).

#### 12.2 Persistence and degradability

Behaviour in environment

not determined

compartments

Behaviour in sewage plant not determined Biological degradability not determined

#### 12.3 Bioaccumulative potential

No information available.

#### 12.4 Mobility in soil

No information available.

#### 12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

#### 12.6 Other adverse effects

Ecological data of complete product are not available.

Do not discharge product unmonitored into the environment or into the drainage.

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 9 / 11

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

**Product** 

In according to RoHS!

Disposal in an incineration plant in accordance with the regulations of the local authorities.

Waste no. (recommended) 130208\*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.

Packaging that cannot be cleaned should be disposed of as for product.

150110\* Waste no. (recommended)

#### **SECTION 14: Transport information**

#### 14.1 UN number

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN) not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

#### 14.2 UN proper shipping name

Transport by land according to

ADR/RID

NO DANGEROUS GOODS

Inland navigation (ADN) NO DANGEROUS GOODS

Marine transport in accordance with

**IMDG** 

NOT CLASSIFIED AS "DANGEROUS GOODS"

Air transport in accordance with IATA NOT CLASSIFIED AS "DANGEROUS GOODS"

#### 14.3 Transport hazard class(es)

Transport by land according to

not applicable

ADR/RID

Inland navigation (ADN) not applicable

Marine transport in accordance with

not applicable

Air transport in accordance with IATA not applicable

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019

Version 06. Supersedes version: 05

Page 10 / 11

#### 14.4 Packing group

Transport by land according to

ADR/RID

not applicable

Inland navigation (ADN)

not applicable

Marine transport in accordance with not applicable

**IMDG** 

Air transport in accordance with IATA not applicable

#### 14.5 Environmental hazards

Transport by land according to

ADR/RID

no

Inland navigation (ADN)

no

Marine transport in accordance with no

**IMDG** 

Air transport in accordance with IATA no

#### 14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

#### 14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

#### **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**EEC-REGULATIONS** 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008;

75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)

**NATIONAL REGULATIONS (GB):** EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- Observe employment restrictions

for people

Observe employment restrictions for mothers-to-be and nursing mothers. Observe employment restrictions for young people.

- VOC (2010/75/CE) not applicable

#### 15.2 Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

#### **SECTION 16: Other information**

#### 16.1 Hazard statements (SECTION 03)

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

H400 Very toxic to aquatic life.

H318 Causes serious eye damage.

H314 Causes severe skin burns and eye damage.

H302 Harmful if swallowed.

H412 Harmful to aquatic life with long lasting effects.

H317 May cause an allergic skin reaction.

#### Ferdinand Bilstein GmbH + Co. KG

Date printed 05.09.2019, Revision 05.09.2019



Version 06. Supersedes version: 05 Page 11 / 11

#### 16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par

RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses

ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure

ATE = acute toxicity estimate CAS = Chemical Abstracts Service

CLP = Classification, Labelling and Packaging

DMEL = Derived Minimum Effect Level DNEL = Derived No Effect Level EC50 = Median effective concentration

ECB = European Chemicals Bureau EEC = European Economic Community

EINECS = European Inventory of Existing Commercial Chemical Substances

ELINCS = European List of Notified Chemical Substances

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC-Code = International Code for the Construction and Equipment of Ships carrying

Dangerous Chemicals in Bulk

IC50 = Inhibition concentration, 50%

IMDG = International Maritime Code for Dangerous Goods IUCLID = International Uniform ChemicaL Information Database

LC50 = Lethal concentration, 50% LD50 = Median lethal dose LC0 = lethal concentration, 0%

LOAEL = lowest-observed-adverse-effect level

MARPOL = International Convention for the Prevention of Marine Pollution from Ships

NOAEL = No Observed Adverse Effect Level NOEC = No Observed Effect Concentration

PBT = Persistent, Bioaccumulative and Toxic substance PNEC = Predicted No-Effect Concentration

REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals

STP = Sewage Treatment Plant

TLV®/TWA = Threshold limit value - time-weighted average TLV®STEL = Threshold limit value - short-time exposure limit

VOC = Volatile Organic Compounds

vPvB = very Persistent and very Bioaccumulative

#### 16.3 Other information

Classification procedure Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method)

**Modified position** none