

## Carry out replacement in the following order:



Replace stabilizer links on Nissan X-Trail T30 in pairs

1

Tighten the parking brake lever.

2

Place wedge blocks under the rear wheels.

3



Loosen the wheel mounting bolts.

4

Raise the front of the car and secure on supports.

5



Remove the front wheels.

6



Unscrew the lower fastener of the stabilizer rod/link

7



Unscrew the stabilizer link upper fastening.

8



Remove the stabilizer rod.

**i** **AutoDoc recommends:**

Examine stabiliser bushes. Replace them if needed.

9



Install the new stabilizer rod / link.

10



Tighten the lower fastener of the stabilizer rod/link

11



Tighten the stabilizer link upper fastening.

12



Install the wheel.

13



Lower the car and working in a cross order, tighten the wheel bolts.

We hope that this information have been useful for you!

 [Video tutorials](#)

Watch our detailed video guides about your NISSAN X-TRAIL T30 repair on our youtube channel. Watch video guides.

 [AutoDoc online](#)

Highest quality stabilizer rods for your car NISSAN X-TRAIL T30 are available on AutoDoc. Go to the website.

**AUTODOC — TOP QUALITY AND AFFORDABLE CAR PARTS ONLINE**

**QUALITY AUTO PARTS**



**NISSAN**



**STABILIZER RODS**



**NISSAN X-TRAIL T30**



**STABILIZER RODS FOR NISSAN**



**STABILIZER RODS FOR NISSAN X-TRAIL T30**



**Disclaimer:**

The document contains only general recommendations that may be useful for you when you perform repair or replacement works. AutoDoc shall not be liable for any loss, injury, damage of property, acquired in the repair or replacement process due to incorrect usage or misinterpretation of the provided information.

AutoDoc shall not be liable for any possible mistakes and uncertainties in this guide. The information provided is for informative purposes only and cannot replace advice from specialists.

AutoDoc shall not be liable for incorrect or hazardous usage of equipment, tools and car parts. AutoDoc strongly recommends to be careful and observe the safety rules when performing repair or replacement works. Remember: usage of low quality auto parts does not guarantee you the appropriate level of road safety.

**AUTODOC IN SOCIAL MEDIA**

